INCH POUND

MIL-C-915/22H
29 September 1989
SUPERSEDING
MIL-C-915/22G
18 June 1985

MILITARY SPECIFICATION SHEET

CABLE, SPECIAL PURPOSE ELECTRICAL, 300 VOLTS, FOR OUTBOARD USE ONLY (NOT FOR INBOARD USE), TYPE TSP (INCLUDING VARIATION TYPE TSPA)

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation: MIL-C-915.

REQUIREMENTS:

Qualification required.

This cable can be manufactured in two variations: TSP (unarmored) and TSPA (armored).

Construction (watertight)

First - Copper conductor, AWG size 22, class K stranding, tin coated.
Second - Polyvinyl chloride insulation (80°C). Nominal wall thickness 0.015 inch. Telephone identification code applied by method 3.
Third - Two conductors cabled together to form a pair with a lay not greater than 2-1/2 inches.
Fourth - The specified number of pairs (see table I) cabled with a lay not greater than 10 inches in the outer layer. Non-fibrous fillers shall be employed. Cabling sequence shall be consecutive, starting with pair no. 1, from center outward.
Fifth - Binder tape applied helically with overlap.

AMSC N/A FSC 6145
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:08Z
Check the source to verify that this is the current version before use.

REQUIREMENTS - Continued

Construction variant for type TSP

Sixth - Special thermoplastic jacket (gray). Nominal wall thickness 0.080 inch. Cable surface marking required.

Construction variant for type TSPA

Sixth - Special thermoplastic jacket (gray). Nominal wall thickness 0.080 inch.
Seventh - Braided metal armor and paint.

TABLE I. Details.

Size 1/	Number of pairs	Overall diameter (inches)			
		Type TSP		Type TSPA	
		min	max	min	max
11	11	0.680	0.730	0.730	0.785
31	31	.982	1.062	1.032	1.112

1/ Type TSP and TSPA.

EXAMINATION AND TESTS:

	Requirements
Basic electrical	
Conductor resistance - ohms/1000 feet at 25°C, maximum.	18.73
Voltage withstand - volts, root mean square, minimum	
Conductor to conductor	2000
Conductor to water	1000
Insulation resistance - megohms/1000 feet, minimum	
Conductor to conductor and conductor to water (TSP only)	100
Conductor to conductor and conductor to armor (TSPA only)	100
Group A:	
Visual and dimensional	No failure
Watertightness - see MIL-C-915, table XXII, for limits of water leakage	No failure

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:08Z
Check the source to verify that this is the current version before use.

EXAMINATION AND TESTS - Continued.

	Requirements
Group B:	
Physicals (unaged)	
Insulation (conductor)	
Tensile strength - lbf/in^2, minimum	1800
Elongation - percent, minimum	125
Jacket (cable)	
Tensile strength - lbf/in^2, minimum	2300
Elongation - percent, minimum	250
Drip - at 95 ± 1°C	Zero
Group C:	
Flammability - inches, maximum	2
Physicals (aged)	
Insulation (conductor)	
Air oven	
Elongation - percent of unaged, minimum	80
Jacket (cable)	
Air oven (168 hours at 136°C)	
Tensile strength - percent of unaged, minimum	80
Elongation - percent of unaged, minimum	60
Hot oil immersion	
Tensile strength - percent of unaged, minimum	75
Elongation - percent of unaged, minimum	50
Permanence of printing, type TSP only, (jacket) - cycles, minimum	250
Cable filler removability	No failure
Armor - conformance to material construction and coverage (type TSPA only)	No failure

QUALIFICATION INSPECTION:

Qualification inspection shall include basic electrical, all of groups A, B, and C, plus the following:

Cable aging and compatibility (95 ± 3°C)	No failure
Flame propagation	No failure
Jacket durometer (type A) hardness, minimum	80

UNIT ORDERING LENGTHS:

Size	Feet (nominal)
11	2500
31	1000

Source: https://assist.dla.mil -- Downloaded: 202610-16T12:08Z
Check the source to verify that this is the current version before use.

NOTE: Not for Air Force use.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Custodians:
Army - MI
Navy - SH

Review activities:
Army - CR, ER
Navy - EC
DLA - IS

User activities:
Army - AL, AR, ME
Navy - CG

Preparing activity:
Navy - SH
(Project 6145-1127-10)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:08Z
Check the source to verify that this is the current version before use.