INCH-POUND
MIL-DTL-915/22J
22 August 2002
SUPERSEDING
MIL-C-915/22H
29 September 1989

DETAIL SPECIFICATION SHEET

CABLE, SPECIAL PURPOSE ELECTRICAL, 300 VOLTS, FOR OUTBOARD USE ONLY (NOT FOR INBOARD USE), TYPE TSP (INCLUDING VARIATION TYPE TPSA)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-915 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

REQUIREMENTS:

Qualification required.

Construction (watertight)

First	-	Copper conductor, AWG size 22, class K stranding, tin coated.
Second	-	Polyvinyl chloride insulation (80°C). Nominal wall thickness 0.015 inch. Telephone identification code applied by method 3.
Third	-	Two conductors cabled together to form a pair with a lay not greater than 2-1/2 inches.
Fourth	-	The specified number of pairs (see table I) cabled with a lay not greater than 10 inches in the outer layer. Non-fibrous fillers shall be employed. Cabling sequence shall be consecutive, starting with pair no. 1, from center outward.
Fifth	-	Binder tape applied helically with overlap.

Construction variant for type TSP

Sixth	-	Thermoplastic jacket (gray). Nominal wall thickness 0.080 inch. Cable surface marking required.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:08Z
Check the source to verify that this is the current version before use.

TABLE I. Details.

Size	Number of pairs	Overall diameter (inches) Type TSP	
		Min	Max
11	11	0.680	0.730
31	31	0.982	1.062

EXAMINATION AND TESTS:

	Requirements
Basic electrical:	
Conductor resistance – ohms/1000 feet at 25°C, maximum	18.73
Voltage withstand - volts, root mean square, minimum	
Conductor to conductor	2000
Conductor to water	1000
Insulation resistance – megohms-1000 feet, minimum	
Conductor to conductor and conductor to water	100
Group A:	
Visual and dimensional	No failure
Watertightness - see MIL-DTL-915, Table XXIII, for limits of water leakage	No failure
Group B:	
Physicals (unaged)	
Insulation (conductor)	
Tensile strength - lbf/in^2, minimum	1800
Elongation - percent, minimum	125
Jacket (cable)	
Tensile strength - lbf/in^2, minimum	2300
Elongation - percent, minimum	250
Drip - at 95 ± 1°C	Zero
Group C:	
Flammability - inches, maximum	2
Physicals (aged)	
Insulation (conductor)	
Air oven	
Elongation - percent of unaged, minimum	80
Jacket (cable)	
Air oven (168 hours at 136°C)	
Tensile strength - percent of unaged, minimum	80
Elongation - percent of unaged, minimum	60
Hot oil immersion	
Tensile strength - percent of unaged, minimum	75
Elongation - percent of unaged, minimum.	50
Permanence of printing, , (jacket) - cycles, minimum	250

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:08Z
Check the source to verify that this is the current version before use.

Cable filler removability ..... No failure

QUALIFICATION INSPECTION:

Qualification inspection shall include basic electrical, all of groups A, B, and C, plus the following:

Cable aging and compatibility (95 ± 3°C) ..... No failure
Flame propagation ..... No failure
Jacket durometer (type A) hardness, minimum 80

UNIT ORDERING LENGTHS:

Size	Feet (nominal)
11	2500
31	1000

PART OR IDENTIFYING NUMBER (PIN): The PIN consists of the letter M, the general specification number along with the specification sheet, and a dash number compiled from a code. Refer to MIL-DTL-915 for the Type and Size code.

PART OR IDENTIFYING NUMBER (PIN): The PIN consists of the letter M, the general specification number along with the specification sheet, and a dash number representing type and size. Refer to MIL-DTL-915 for an example.

M	**915**	**/22-**	**X-X**
Prefix for Military Specification	Specification Number	Specification Sheet Number	Type and Size

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army – MI
Navy – SH

Preparing activity:
Navy - SH
(Project 6145-2317-007)

Review activities:
Army – AR, CR
Navy - CG, EC
DLA - CC

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:08Z
Check the source to verify that this is the current version before use.