INCH POUND

MIL-C-915/47C
29 September 1989
SUPERSEDING
MIL-C-915/47B
18 June 1985

MILITARY SPECIFICATION SHEET

CABLE, SPECIAL PURPOSE, ELECTRICAL, FOR OUTBOARD USE ONLY (NOT FOR INBOARD USE), TYPE 1SWF

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation: MIL-C-915.

REQUIREMENTS:

Qualification required.

Construction (watertight)

First - Copper, conductor, in accordance with ASTM B 286, size 22-7, uncoated. Maximum diameter 0.033 inch.

Second - Polyethylene insulation, natural, type II, class L, grade 3 in accordance with L-P-390. Nominal thickness 0.045 inch.

Third - Braided shield of AWG no. 36 uncoated copper. Braid angle of 30 to 35 degrees; minimum coverage of 85 percent.

Fourth - Shield insulation of one polyester tape, type G in accordance with MIL-I-631, plus a jacket of clear polyamide in accordance with ASTM D 4066. Nominal thickness of 0.003 inch. Standard identification code applied by method 2.

- Alternate shield insulation of two polyester tapes, type G in accordance with MIL-I-631, sealed. Standard identification code applied by method 2, on inner tape.

Fifth - Two conductors, one black and one white, cabled with a lay not greater than 3 inches. Nonfibrous fillers shall be used.

Sixth - Binder tape applied helically with overlap.

Seventh - Arctic type polychloroprene jacket (black). Cable jacket thickness 0.100-inch maximum. Cable surface marking required.

AMSC N/A FSC 6145

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:11Z
Check the source to verify that this is the current version before use.

TABLE I. Details.

		Overall diameter	
Type and size	Number of conductors	Minimum (inch)	Maximum (inch)
1SWF-2	2	0.600	0.625

EXAMINATION AND TESTS:

	Requirements
Basic electrical:	
Conductor resistance - ohms/1000 feet, at 25°C, maximum	17.03
Voltage withstand - volts, root mean square, minimum	
Conductor to shield	3000
Shield to shield	500
Insulation resistance - megohms/1000 feet, minimum	
Conductor to shield	5000
Shield to shield	100
Group A.	
Visual and dimensional	No failure
Hydrostatic (open end) - leakage at 1000 lbf/in², in 6 hours, in³, test each shipping length	Zero
Capacitance - at 1 kHz, pF/ft, maximum	28
Characteristic impedance - at 1 MHz, ohms	61 ± 3
Thermoplastic flow at 95 ± 3°C	No failure
Group B:	
Cold working (minus 54 ± 2°C)	No damage
Drip - at 75 ± 1°C	Zero
Physicals (unaged)	
Insulation (conductor)	
Tensile strength - lbf/in², minimum	1400
Elongation - percent, minimum	300
Jacket (cable)	
Tensile strength - lbf/in², minimum	1800
Elongation - percent, minimum	300
Set - inch, maximum	3/8
Group C:	
Physicals (aged)	
Insulation (conductor)	
Air oven	
Elongation - percent of unaged, minimum	60

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:11Z
Check the source to verify that this is the current version before use.

EXAMINATION AND TESTS - Continued

	Requirements
Permanence of printing (jacket) - cycles, minimum.....	250
Cable filler removability.....	No failure
Shield-conformance to material coverage and construction.....	No failure

QUALIFICATION INSPECTION:

Qualification inspection shall include basic electrical, all of groups A, B and C, plus the following:

Cable aging and compatibility (95 ± 3°C).....	No failure
Cold working (minus 54 ± 2°C).....	No failure

UNIT ORDERING LENGTHS:

All sizes 1000 feet (nominal).

NOTE: Not for Air Force use.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Custodians:
Army - MI
Navy - SH

Preparing activity:
Navy - SH
(Project 6145-1127-11)

Review activities:
Army - CR, ER
Navy - EC
DLA - IS

User activities:
Army - AL, AR, ME
Navy - CG

Source: https://assist.dla.mil -- Downloaded: 202610-16T12:11Z
Check the source to verify that this is the current version before use.