INCH-POUND
MIL-DTL-915/47D
22 August 2002
SUPERSEDING
MIL-C-915/47C
29 September 1989

DETAIL SPECIFICATION SHEET

CABLE, SPECIAL PURPOSE, ELECTRICAL, FOR OUTBOARD USE ONLY (NOT FOR INBOARD USE), TYPE 1SWF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-915 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

REQUIREMENTS:

Qualification required.

Construction (watertight)

First	-	Copper, conductor, in accordance with ASTM B 286, size 22-7, uncoated.
Second	-	Polyethylene insulation, natural, type II, class L, grade 3 in accordance with L-P-390. Nominal thickness 0.045 inch.
Third	-	Braided shield of AWG No. 34 or No. 36 uncoated copper. Braid angle of 30 to 35 degrees; minimum coverage of 85 percent.
Fourth	-	Shield insulation of one polyester tape, in accordance with NEMA FI 4, plus a jacket of clear polyamide in accordance with ASTM D 4066. Nominal thickness of 0.003 inch. Standard identification code applied by method 2.
	-	Alternate shield insulation of two polyester tapes, in accordance with NEMA FI 4, sealed. Standard identification code applied by method 2 on inner tape.
Fifth	-	Two conductors, one black and one white, cabled with a lay not greater than 3 inches. Nonfibrous fillers shall be used.
Sixth	-	Binder tape applied helically with overlap.
Seventh	-	Arctic type polychloroprene jacket (black). Cable jacket thickness 0.100-inch maximum. Cable surface marking required.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:11Z
Check the source to verify that this is the current version before use.

TABLE I. Details.

		Overall diameter	
Type and size	Number of conductors	Minimum (inches)	Maximum (inch)
1SWF-2	2	0.600	0.625

EXAMINATI0N AND TESTS:

Requirements

Basic electrical:
Conductor resistance - ohms/1000 feet, at 25°C, maximum 17.03
Voltage withstand - volts, root mean square, minimum
Conductor to shield 3000
Shield to shield 500
Insulation resistance – megohms-1000 feet, minimum
Conductor to shield 5000
Shield to shield 100

Group A:
Visual and dimensional ..... No failure
Hydrostatic (open end) - leakage at 1000 lbf/in^2, in 6 hours, in^3, test each shipping length ..... Zero
Capacitance - at l kHz, pF/ft, maximum 28
Characteristic impedance - at l MHz, ohms ..... 61 ± 3
Thermoplastic flow at 95 ± 3° C ..... No failure

Group B:
Cold working (minus 54 ± 2°C) ..... No damage
Drip - at 75 ± 1°C ..... Zero
Physicals (unaged)
Insulation (conductor)
Tensile strength - lbf/in^2, minimum 1400
Elongation - percent, minimum 300
Jacket (cable)
Tensile strength - lbf/in^2 1800
Elongation - percent, minimum 300
Set - inch, maximum 3/8

Group C:
Physicals (aged)
Insulation (conductor)
Air oven
Elongation - percent of unaged, minimum. 60
Permanence of printing (jacket) - cycles, minimum 250
Cable filler removability ..... No failure

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:11Z
Check the source to verify that this is the current version before use.

Shield-conformance to material coverage and construction ..... No failure

QUALIFICATION INSPECTION:

Qualification inspection shall include basic electrical, all of groups A, B and C, plus the following:

Cable aging and compatibility (95 ± 3°C) ..... No failure
Cold working (minus 54 ± 2°C) ..... No failure

UNIT ORDERING LENGTH:
All sizes 1000 feet (nominal).

PART OR IDENTIFYING NUMBER (PIN): The PIN consists of the letter M, the general specification number along with the specification sheet, and a dash number representing type and size. Refer to MIL-DTL-915 for an example.

M	**915**	**/47-**	**X-X**
Prefix for Military Specification	Specification Number	Specification Sheet Number	Type and Size

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army – MI
Navy – SH

Preparing activity:
Navy - SH
(Project 6145-2317-008)

Review activities:
Army – AR, CR
Navy - CG, EC
DLA - CC

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:11Z
Check the source to verify that this is the current version before use.