MIL-C-50413A (AR)
AMENDMENT 2
5 February 1982
SUPERSEDING
AMENDMENT 1
4 November 1981

MILITARY SPECIFICATION

CARTRIDGE, 165MM, TP, M623
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-C-50413A (AR) dated 18 May 1979 and is approved for use by the U.S. Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 6

* Add to Notes block: "Test is performed with handle assembly removed from cartridge."

PAGE 16

4.4.2.9: Delete Critical "1" in its entirety and substitute "None Defined."

* Delete Major category 103 in its entirety.

Add to Major Category:

"104 Base plug rotates (moves) when minimum assembly torque is reapplied (see Note 1) 0.40% 3.1 Gage"

Add to Notes: "1. Minimum assembly torque is to be reapplied while the adhesive is still wet."

NOTE: The margins of this amendment are marked with an asterisk (*) to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1320-A645)

FSC 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:24Z
Check the source to verify that this is the current version before use.