MIL-B-44224A
2 June 1988
SUPERSEDING
MIL-B-44224
24 June 1986

MILITARY SPECIFICATION

BEEF IN BARBECUE SAUCE, THERMOSTABILIZED, TRAY PACK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers beef in barbecue sauce, thermostabilized in tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

TT-C-495 - Coatings, Exterior, for Tinned Food Cans
PPP-B-636 - Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-22T00:43Z
Check the source to verify that this is the currentversion before use.

MILITARY

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Personal Equipment and Equipage; General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-900 - Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks and Sugars Used in the Preparation of Thermostabilized Foods for the Armed Forces

(Copies of specifications, standards, and handbooks required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Copies may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

U.S. Standards for Grades of Tomato Paste

(Copies may be obtained from the Director, Fruit and Vegetable Division, Agricultural Marketing Service, U.S. Department of Agriculture, P.O. Box 96456, Washington, DC 20090-6456.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

Institutional Meat Purchase Specifications for Beef

(Copies may be obtained from the Director, Livestock and Seed Division, Agricultural Marketing Service, P.O. Box 96456, U.S. Department of Agriculture, Room 2092, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

Meat and Poultry Inspection Regulations

Food Safety and Inspection Services, Canning of Meat and Poultry Products (9 CFR Part 318)

(Copies may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

U.S. Standards for Condition of Food Containers

(Copies may be obtained from the Chairman, Condition of Food Container Committee, Agricultural Marketing Service, Room 0610, South Building, P.O. Box 96456, U.S. Department of Agriculture, Washington, DC 20090-6456.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Copies may be obtained from the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Copies should be obtained from the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Copies should be obtained from the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Copies should be obtained from the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

AMERICAN DEHYDRATED ONION AND GARLIC ASSOCIATION (ADOGA)

Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products

(Copies should be obtained from the American Dehydrated Onion and Garlic Association, 650 California Street, Suite 800, San Francisco, CA 94108.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3330 - Peel Adhesion of Pressure-sensitive Tape

(Copies should be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.4, 6.1, and 6.3).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

3.2.1 Beef. The beef shall be from steers, heifers, or cows and shall be derived from any combination or portion of recognizable primal rounds (shank off, heel out, and knuckles, peeled) or subprimal cuts of the round, shank off (top round, bottom round, heel out, and knuckles, peeled). Recognizable cuts are those which, when compared to Institutional Meat Purchase Specifications (IMPS) cuts, have no more than a minor amount of lean, fat, or bone removed or included from an adjacent cut. A portion is a certified recognizable cut from which objectionable tissue, such as tendons or heavy connective tissue, has been removed. The beef shall be in the fresh-chilled state and shall be in excellent condition, i.e. exposed lean and fat surfaces shall be of a color and bloom normally associated with the class and cut of meat and typical of meat which has been properly stored and handled. Cut surfaces and naturally exposed lean surfaces shall show no more than slight darkening or discoloration due to dehydration, aging, or microbial activity. The fat shall show no more than slight discoloration due to oxidation or microbial activity. No odors foreign to fresh meat shall be present. Changes in color and odor characteristically associated with vacuum-packaged meat in excellent condition shall be acceptable. Also, meat shall show no evidence of freezing, defrosting, or mishandling.

3.2.1.1 Boning and trimming. The beef shall be boned and trimmed to remove objectionable material such as bone, cartilage, or heavy connective tissue. The boneless trimmed beef shall meet the limitations specified in tables I and II.

3.2.1.2 Handling and storage. Handling and storage of the boned and trimmed beef prior to processing into the finished product shall be in accordance with the following requirements:

a. Beef processed on the day of initial certification shall be maintained in the temperature range of 28° to 50°F (inclusive).

b. Holding in the fresh chilled state for not more than 4 days after initial certification is permitted provided that the beef is maintained in the temperature range of 28° to 40°F (inclusive).

c. Holding in the frozen state for not more than 120 days after initial certification is permitted provided that the beef is:

- frozen to 0°F or lower within 72 hours after initial certification
- stored at 0°F or lower
- protected from freezer deterioration and damage
- stored in containers that are adequate to maintain product excellence
- held after storage at an internal temperature not to exceed 40°F when further processing is resumed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

3.2.1.3 Beef, cooked, frozen. Frozen cooked beef shall be prepared from beef that complies with 3.2.1, 3.2.1.1, and 3.2.1.2. The beef shall be processed in accordance with 3.3.1 and 3.3.2. The cooked beef shall be packaged and vacuum sealed in water-impermeable material having an oxygen permeability rate of not more than 10cc of oxygen per square meter per 24 hours at 73°F and 0 percent humidity and shall be frozen to 0°F or below within 72 hours. The beef shipped between plants shall be accompanied by a USDA Agricultural Marketing Service (AMS) Livestock Division Certificate to certify the initial freezing (in-storage) date and compliance with the above stated requirements. The packaged, frozen, cooked beef shall have been held at 0°F or below for a period not to exceed 30 days prior to slicing (see 3.3.1).

3.2.2 Tomato paste. Tomato paste shall be U.S. Grade A or better of the U.S. Standards for Grades of Tomato Paste. See formulation (3.3.2) for required soluble solids content.

3.2.3 Starch, waxy maize, modified. The starch shall be a white, odorless, finely pulverized, modified waxy maize starch for use in canned foods. The modified starch shall demonstrate initial viscosity development in the temperature range of 140° to 170°F and a typical viscosity (be fully hydrated) at common retort temperatures. The starch shall resist breakdown at low pH, under shear stress, and under conditions of cold storage. The starch shall be bland with essentially no cereal or starch taste and shall comply with MIL-STD-900.

3.2.4 Salt. Salt shall be noniodized, clear, white, refined, sodium chloride with or without anticaking agents and shall comply with the purity standards for sodium chloride of the Food Chemicals Codex.

3.2.5 Mustard flour. Mustard flour shall be a bright yellow powder prepared from a blend derived from the endosperm of the seed of Brassica hirta Moench and Brassica juncea. Mustard flour shall contain not less than 0.4 mL of volatile oil per 100 grams and be of such size that not less than 95 percent shall pass through a U.S. Standard No. 60 sieve.

3.2.6 Garlic powder. Garlic powder shall be fancy grade of the Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products.

3.2.7 Clove, ground. Ground clove shall be prepared from the dried, unopened flower buds of Caryophyllus aromaticus L. The powder shall be dark reddish-brown in color and shall possess a strong aromatic odor with a hot pungent taste. The clove shall contain not less than 15.0 mL of volatile oil per 100 grams of ground clove and be of such size that not less than 95 percent shall pass through a U.S. Standard No. 30 sieve.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

3.2.8 Sugar, brown, light. The brown sugar shall be partially refined cane or beet sugar. It shall be light brown in color and shall have a sweet, molasses-like flavor.

3.2.9 Vinegar, cider. Cider vinegar shall be prepared from apple cider, be clear, light amber in color, and free of haze, sediment, suspended matter, and floating particles. The cider vinegar shall contain not less than 4.0 percent and not more than 5.0 percent acetic acid.

3.2.10 Cinnamon, ground. Ground cinnamon shall be the dried bark of Cinnamomum burmanii Blume, commonly know as "Korintje Cinnamon." The cinnamon shall contain not less than 1.5 mL of volatile oil per 100 grams of ground cinnamon and be of such size that not less than 95 percent shall pass through a U.S. Standard No. 60 sieve.

3.2.11 Sauce, Worcestershire. The sauce shall be a brown or dark brown colored liquid having a pleasant, tart, peppery, fruit-spice flavor and shall possess the body and character typical of this sauce. The sauce shall have a titratable acidity (as acetic acid) of not less than 2.8 nor more than 3.8 percent.

3.2.12 Onion, dehydrated, chopped. The dehydrated chopped onion shall be fancy grade of the Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products.

3.2.13 Flavoring, smoke. Smoke flavoring shall be an aqueous solution of natural maple and/or oak wood smoke and shall be dark brown-black in color with a clean smoke odor. The smoke flavoring shall have a titratable acidity of 6.2 to 7.2 percent expressed as acetic acid, carbonyl level (butanone-2) of 7.0 to 8.0 grams per 100 mL and a phenolic level (dimethoxphenol) of 7.5 to 9.0 mg per mL.

3.2.14 Pepper, red, ground. Ground red pepper shall be derived from red, ripe fruit of Capsicum frutescens L. and shall possess the characteristic yellowish-red to red color with a perceptible sensation of pungency. It shall be uniformly ground to allow a minimum of 95 percent by weight to pass through a U.S. Standard No. 40 sieve, and not less than 95 percent by weight to be retained on a U.S. Standard No. 60 sieve. The Scoville Pungency Value shall be not less than 30,000 units.

3.2.15 Allspice, ground. Ground allspice shall be derived from dried, nearly ripe fruit of Pimenta officinalis Lindl and shall have a fragrant clove-like aroma, a strongly aromatic pungent clove-like flavor, and a dark reddish-brown color. Allspice shall contain not less than 3.0 mL of volatile oil per 100 grams of ground allspice with 80.0 percent eugenol as a principal constituent. A minimum of 95 percent, by weight, shall pass through a U.S. Standard No. 25 sieve.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

3.2.16 Fat, beef. Beef fat shall be stabilized edible beef tallow with the following characteristics: Moisture: 0.2 percent maximum; Free fatty acid: 0.5 percent maximum as oleic; Color: slight yellow; Melting point: 110-112°F; AOM: 20 hrs. The fat shall be maintained at 35°F or lower and held for no more than 30 days from time of rendering.

3.2.17 Lecithin. Lecithin shall comply with the Food Chemicals Codex.

3.2.18 Water. Water used for formulation, ice making, and washing shall conform to the National Primary Drinking Water Regulations.

3.2.19 Preblended spice and seasoning mixture. Preblended spices and seasonings may be used. The spices and seasonings in the mixture shall comply with the requirements of this document. The containers used for the spice and seasoning blend shall be labeled with each ingredient and the percentage of each ingredient in the blend. The ingredients shall be in the same proportions as specified in the ingredient formula.

3.3 Preparation and further processing. Processing shall be on a continuous basis.

3.3.1 Beef preparation. The beef shall be prepared as follows:

a. Boned and trimmed meat meeting the requirements of 3.2.1.1 shall be further trimmed, if necessary, so as to ensure compliance with finished product requirements (see 3.6).

b. The boned and trimmed meat cuts shall be cooked by a commercially acceptable cook method to provide a product meeting the finished product requirements.

c. The cooked meat cuts shall be cooled to 40°F or below within 24 hours following the cooking process. The cooled meat cuts shall be held not longer than 48 hours and at a temperature not to exceed 40°F after removal from the cooking process and prior to grinding. Alternatively, if the cooked meat cuts are to be held longer than 48 hours after cooking, they shall be placed in a freezer within 4 hours after cooking, and frozen to 0°F or lower within 24 hours after being placed in the freezer. If the meat cuts are to be frozen, the meat shall not have been previously frozen and the meat shall be placed into separate oxygen impermeable casing materials approved by the USDA and FDA, and securely closed. The frozen, cooked meat shall be held at 0°F for a period of not more than 30 days prior to grinding. The frozen meat shall be tempered to a range of 28° to 40°F prior to grinding.

d. The tempered meat shall be mechanically ground through a grinder equipped with a 2-blade knife and a plate having openings measuring 1 inch in diameter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

3.3.2 Preparation of the sauce. The sauce shall be formulated and prepared as follows:

Ingredients	Percent by weight
Tomato paste (24% solids) 1/	36.00
Water	30.20
Sugar, brown, light	11.00
Vinegar, cider (50 grain)	8.30
Beef fat, rendered	6.00
Starch, waxy maize, modified	2.50
Salt 2/	1.50
Sauce, Worcestershire	1.50
Flavoring, smoke	0.50
Onion, dehydrated, chopped	0.95
Mustard, flour	0.50
Garlic powder	0.50
Lecithin	0.30
Red pepper, ground	0.10
Clove, ground	0.10
Allspice, ground	0.03
Cinnamon, ground	0.02

1/ If the specified tomato solids are not available, the tomato solids that are used must be calculated to bring the solids level to that specified and water shall be adjusted accordingly.

2/ The total amount of salt in the sauce shall be adjusted as necessary to produce a product that complies with the finished product salt requirements (see 3.6).

a. A slurry shall be made with the starch and part of the water. The remaining ingredients shall be mixed together and heated to not less than 140°F. The starch slurry shall be added and the final mixture heated to not less than 180°F but not more than 190°F and held for approximately 5 minutes at this temperature.

b. The volume of the final mixture shall be adjusted with water to compensate for evaporation loss during heating.

c. The sauce shall be used within 4 hours after cooking and held at a temperature of not less than 150°F during this interval.

3.3.3 Preparation of beef and barbecue sauce. The ground beef shall be mechanically mixed with 25 percent of the sauce until the beef is partially shredded but not to the extent that a paste or homogeneous mixture appears. The balance of the sauce shall then be added and uniformly mixed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

3.4 Tray pack filling and sealing. Each tray pack can (see 5.1.1) shall be filled with product such as to conform to the finished product requirements and to the following requirements:

a. Each tray pack can shall be filled with 106 ounces of product.

b. Each can shall be hermetically sealed under a vacuum established by a processing authority and specified in the scheduled process so as to assure compliance with the finished product requirements (see 3.6q).

c. Each filled and sealed tray pack can shall be in the retort process within 2 hours after product preparation.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized by retorting until a sterilization value (F_o) of not less than 6 has been achieved.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, dirt, insect parts, hair, wood, glass, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour, rancid, or moldy.

c. There shall be no color foreign to the product.

d. No individual can shall contain less than 56 ounces drained weight of beef pieces.

e. The average drained weight shall be not less than 60 ounces.

f. Total weight of cartilage, coarse connective tissue, sections of tendons or ligaments, and glandular material, collectively, in any individual can shall not be greater than 2 ounces.

g. No individual can shall contain a bone piece measuring 0.3 inch or more in any dimension.

h. The texture of the beef shall not be dry, tough, rubbery, or mushy.

i. Sauce consistency shall be smooth.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

j. There shall be a uniform mixture of beef and sauce.

k. The average net weight shall be not less than 106 ounces.

l. No individual can shall have a net weight of less than 104 ounces of product.

m. The average fat content of the finished product shall be not greater than 8.0 percent.

n. No individual tray pack shall have a fat content greater than 10.0 percent.

o. No individual tray pack shall have a salt content greater than 1.5 percent or less than 1.0 percent.

p. The product shall show no evidence of excessive heating (materially darkened or scorched).

q. Filled, sealed, and retorted cans shall show evidence of proper vacuum as determined by concavity of the can lid (see 4.5.6).

3.6.1 Palatability. The finished product shall be equal to or better than the preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The beef component and the finished product shall originate and be produced, processed, and stored in plants regularly operating under Meat and Poultry Inspection Regulations of the U.S. Department of Agriculture.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all the requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection necessary to assure compliance with the requirements of this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

4.3 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this document and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this document or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.5.1.1 Beef examination for condition and cut. All beef shall be examined in either the bone-in or boneless state for conformance to the condition and cut requirements in 3.2.1. Cuts initially examined in the boneless state shall be in the form of whole boneless recognizable cuts or portions thereof. Any nonconforming beef shall be rejected.

4.5.1.2 Boned and trimmed beef examination. After boning and trimming and prior to any further processing or to any freezing, the beef shall be examined for the defects listed in table II. The lot size, expressed in terms of pounds, shall be declared to the Agricultural Marketing Service (AMS) agent by the contractor. However, the AMS agent reserves the right to declare as a lot a portion of a declared lot, if, in his or her opinion, that portion may be out of compliance with any requirement. The sample unit shall be a minimum of 12 pounds of adjacent boneless beef. The sample size shall be as specified in table I. If all or a portion of the sample unit falls within a larger cut, the entire cut shall be examined. Failure of the beef to meet the acceptance criteria as indicated in table I shall be cause for rejection of the lot. Except for beef rejected because of freezing, defrosting, or not being in excellent condition, the beef may be reworked by the contractor and reoffered for examination. For reexamination, the sampling plan used shall be the one in table I designed for the next larger lot size than the one under which the lot was initially rejected. Beef shall not be reexamined more than one time.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

TABLE I. Sampling plan for boned and trimmed beef

Lot size (pounds)	Sample size (sample units)	Defect categories Major AC	Major RE	Minor AC	Minor RE
500 or less	20	2	3	5	6
501 to 1,200	32	3	4	7	8
1,201 to 3,200	50	5	6	10	11
3,201 to 10,000	80	7	8	14	15
10,001 to 38,000	125	10	11	21	22
Reinspection lots of 10,001 to 38,000	200	14	15	21	22

TABLE II. Boned and trimmed beef defects 1/ 2/

Category		Defect
Major	Minor	
101		Presence of popliteal, prescapular, prefemoral, or any exposed lymph gland measuring 0.5 inch or more in any dimension.
102		Presence of blood clot measuring 1.0 inch or more in any dimension.
	201	Presence of blood clot measuring 0.5 inch or more but less than 1.0 inch in any dimension.
103		Presence of bruise measuring 1.0 inch or more in any dimension.
	202	Presence of bruise measuring 0.5 inch or more but less than 1.0 inch in any dimension.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

TABLE II. Boned and trimmed beef defects 1/ 2/ - Continued

Category		Defect
Major	Minor	
104		Presence of bone measuring 0.3 inch or more in any dimension.
105		Presence of cartilage measuring 0.5 inch or more in any dimension.
106		Presence of backstrap measuring 1.0 inch or more in one dimension and 0.2 inch or more in a second dimension (when measured at right angles to each other).
107		Presence of heavy connective tissue (for example, on the surface of the outside round adjacent to the knuckle, along the skin surface of the strip loin, or the gracilis membrane) measuring 2.0 square inches or more.
	203	Presence of backstrap measuring 0.5 inch or more but less than 1.0 inch in one dimension and 0.2 inch or more in a second dimension (when measured at right angles to each other).
	204	Presence of heavy connective tissue (for example, on the surface of the outside round adjacent to the knuckle, along the skin surface of the strip loin, or gracilis membrane) measuring 0.5 square inch or more but less than 2.0 square inches.
	205	Presence of heavy connective tissue on lower edge of short plate or flank.
	206	Presence of heavy connective (abdominal tunic) tissue on the flank measuring 1.0 inch or more in any dimension.
	207	Presence of membranous portion of diaphragm or membranous covering from skirt, flank, or abdominal section of short plate measuring 3.0 square inches or more.
108		Presence of knuckle cover.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

TABLE II. Boned and trimmed beef defects 1/ 2/ - Continued

Category		Defect
Major	Minor	
109		Presence of kidney, pizzle eye, prepubic tendon, thymus gland, or hanging tender measuring 1.0 inch or more in one dimension and 0.2 inch or more in a second dimension (when measured at right angles to each other).
	208	Presence of kidney, pizzle eye, prepubic tendon, thymus gland, or hanging tender measuring less than 1.0 inch in one dimension and 0.2 inch or more in a second dimension (when measured at right angles to each other).
	209	Presence of calcified (scratchy) periosteum measuring 2.0 square inches or more.
	210	Presence of shank, clod, knuckle, or bottom (outside) round with tendinous end showing less than 75 percent lean tissue on a cross-sectional cut surface.
	211	Presence of dehydrated surface measuring 1.0 square inch or more.
	212	Presence of discolored meat (including blood discolored neck meat) measuring 1.0 square inch or more.
	213	Presence of exposed blood vessel measuring 1.0 inch or more in any dimension.
	214	Presence of cod, udder, kidney, or pelvic fat.

1/ Determination of wholesomeness and acceptability of product with respect to the presence of foreign material (e.g., glass, dirt, insect parts, hair, wood, metal) shall be made by a Meat and Poultry Inspection Operations employee.

2/ Evidence of freezing or defrosting or product not in excellent condition shall cause rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

4.5.1.3 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods, such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

4.5.3.1 Net weight inspection. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty tray pack cans and lids used in preparing the product and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average net weight is less than 106 ounces or if the net weight of any individual can is less than 104 ounces, the lot shall be rejected.

4.5.3.2 Product inspection. The sample size shall be as indicated by the double sampling plan specified in table III. The tray pack cans shall be selected at random from the lot. The tray pack cans shall be heated for 35 minutes in boiling water, opened, and inspected for the defects listed in table IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

TABLE III. Double sampling plan for product inspection 1/

Lot size (cans)	Sample size (cans)	Cumulative sample	Acceptance number	Rejection number
0 to 3,200	8	-	0	2
	8	16	1	2
3,201 to 35,000	13	-	0	3
	13	26	3	4

1/ a. If no defects are found in the first sample, the lot shall be accepted.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and, if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

TABLE IV. Product defects 1/ 2/

Category	Defect
Major	
101	Drained weight of beef pieces in a can is less than 56 ounces. 3/ 4/
102	Beef dry, tough, rubbery, or mushy.
103	Total weight of cartilage, opaque connective tissue, sections of tendons or ligaments, and glandular material, collectively, in a can is greater than 2 ounces.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

TABLE IV. Product defects 1/ 2/ - Continued

Category	Defect
Major	
104	Any individual can contains a bone piece measuring 0.3 inch or more in any dimension.
105	Sauce is lumpy.
106	Not a uniform mixture of beef and sauce.
107	Product shows evidence of excessive heating (materially darkened or scorched).

1/ The presence of foreign material (e.g., glass, dirt, insect parts, hair, wood, metal), foreign odor or flavor (e.g., burnt, scorched, moldy, rancid, sour, stale), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an Agricultural Marketing Service (AMS) agent.)

3/ To determine drained weight, the free liquid in the can shall be poured off and the remaining contents shall be poured into a flat bottom container. A minimum of three times the tray pack can's volume of 190° to 212°F water shall be added to the container so as to cover the contents. The contents and water shall be agitated so as to liquify rendered fat without breaking the beef pieces. The contents shall then be poured into a U.S. Standard 1/4-inch sieve in a manner that will distribute the product over the sieve without breaking the beef pieces. Sieve area shall be such that the distributed product does not completely cover all the openings of the sieve. The sieve shall be tilted at an approximate 45 degree angle and allowed to drain for 2 minutes before determining the drained weight by subtracting the sieve tare weight from the gross weight. The drained weight shall be reported to the nearest 0.1 ounce.

4/ The lot shall be rejected if the average drained weight is less than 60 ounces.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

4.5.3.3 Fat and salt content testing. Nine tray pack cans shall be selected at random from the lot and distributed as follows:

- Three for laboratory analysis.
- Three for submission to the contractor.
- Three for retention by the AMS agent as reserve samples.

The three tray packs for laboratory analyses shall be individually tested for fat and salt content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, chapter: Meat and Meat Products, Section: Meat, except that preparation of the samples shall be as follows. The three unopened cans shall be gently warmed in a water bath to melt fat adhering to the inside of the cans. The cans shall be opened and the entire contents of each can shall be separately blended in a Waring blender or equivalent. The test results shall be reported to the nearest 0.1 percent. Any test failure is a major defect. The lot shall be rejected if any of the following major defects occur:

a. The average fat content of the three tray packs is greater than 8.0 percent.

b. The fat content of any individual tray pack is greater than 10.0 percent.

c. The salt content of any individual tray pack is greater than 1.5 percent or less than 1.0 percent.

Analysis of reserve samples at the request of the contractor shall not be permitted unless the original laboratory analysis indicated that the involved lot will be rejected because of noncompliance with the fat or salt content requirement. When the reserve samples are analyzed, the analyses for both fat and salt shall be made and will be considered final. Unused reserve samples shall be returned to the contractor for inclusion in subsequent lots.

4.5.4 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the U.S. Standards for Condition of Food Containers except that inspection for labeling shall be as specified in 4.5.4.1.

4.5.4.1 Can label examination. Labels shall be examined for defects in accordance with MIL-L-1497 (see 5.4), except that for self-adhering labels the following additional defects shall apply:

Major: Label torn or scratched so as to obliterate any of the markings.

Minor: Air bubbles under label.
Label not properly adhered to can (i.e., label raised or peeled back from edges or corners).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

4.5.4.2 Label adhesive examination. When self-adhering labels are used, the adhesive shall be tested in accordance with ASTM D 3330.

4.5.5 Can closure examination. Can closure shall be examined visually and by teardowns in accordance with the can manufacturer's requirement and 21 CFR, Part 113, Subpart D or 9 CFR, Part 318, Subpart G, as applicable. Any nonconformance based on observation of can seam teardowns or on record of can seam teardowns is a major defect and shall be cause for rejection of any involved product.

4.5.6 Vacuum examination. Cans shall be allowed to cool to 75° ± 5°F, held for at least 24 hours after sealing, and then examined for vacuum retention. To examine, lay a straight edge in the center of the lid along the length of the tray pack. Both ends of the straight edge shall touch the lid at the inside edge of the double seam. There shall be a visible gap between the straight edge and the lid for the entire distance of the label panel. Using a shorter straight edge, the same procedure shall be used across the width, in the center of the tray pack can. When examining a ribbed lid, only lay the straight edge between the two center ribs along the length of the can. The inspection lot shall include only tray packs produced in a single shift on a single sealing machine. The sample size shall be 50 cans. Any nonconformance is a major defect and shall be cause for rejection of the lot.

4.5.7 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
Reinforced with other than nonmetallic strapping or tape.
Dimensions of pads not as specified.
Interior packing with fiberboard liner or pads not as specified.

Minor: Other required markings missing, incorrect, or illegible.
Arrangement or number of cans not as specified.

4.5.8 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIl-L-35078.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A or C, as specified (see 6.1).

Source: https://assist.dla.mil -- Downloaded: 202640-22T00:43Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. A size 1001 by 1206 by 200 tray pack can shall be filled with 106 ounces of the food product, sealed, and thermoprocessed as specified in 3.4 and 3.5. The base plate of the can shall be electrolytic chromium-coated steel and shall be of sufficient temper to protect the product during shipment and storage. The base plate weight of the body and end of each can shall be 90 pounds per base box. The entire inside area of the can shall be coated. Scratches or fractures shall not penetrate through the interior can coating. The interior can coating shall not peel or blister when in contact with the product. The interior can coating shall neither affect nor be affected by the packaged product. A certificate of conformance shall be furnished to certify compliance with the interior can coating requirements. The can shall be coated overall on the outside with a coating conforming to type I of TT-C-495.

5.1.1.1 When specified (see 6.1), the base plate of the can shall be electrolytic chromium-coated steel and shall be of sufficient temper to protect the product during shipment and storage. The base plate weight of the body and end of each can shall be 98 pounds per base box. The body design shall be reinforced on the bottom with six longitudinal beads or ribs 0.050 ± 0.010 inch deep. The beads shall be 9 inches by 3/4 inch in length and width and shall be equidistant in the center panel of the bottom. The end design shall be reinforced with eight longitudinal beads 0.018 ± 0.004 inch deep. The beads shall be 11 inches by 3/4 inch in length and width and shall be equidistant in the center panel of the end. The center four beads on the end design shall be interrupted to provide a 5-inch by 5-inch flat center panel for labeling. The apex of all these beads shall be outward. The interior and exterior can coating requirements shall be as specified in 5.1.1.

5.1.2 Level C. The product shall be preserved as specified in 5.1.1, except that cans with commercial exterior coating will be acceptable.

5.2 Packing. The product shall be packed in accordance with level A, B, or C, as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L or HSC-L with an HSC full depth cover, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads fabricated of grade V3c fiberboard. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box. Each box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament-reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

of load specified (see 6.1) except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). Flute direction of the box liner shall be vertical. The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of the same material as the box.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified, except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.4 Labeling. Each tray pack can shall be labeled in accordance with MIL-L-1497 and with the following:

- Official establishment number (e.g., est 38) or a three-letter code identifying the establishment
- Lot number 1/
- Production shift number 1/
- Retort identification number 1/
- Retort cook number 1/

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:43Z
Check the source to verify that this is the current version before use.

1/ The lot number shall be expressed as a four-digit Julian code. The first digit shall indicate the year of production and the next three digits shall indicate the day of the year (Example, March 19, 1987, would be coded as 7078). The Julian code shall represent the day the product was packaged and processed. Sub-lotting (when used) shall be represented by an alpha character immediately following the four-digit Julian code. Following the four-digit Julian code and the alpha character (when used), the other required code information shall be printed in the sequence as listed above.

Alternatively, a preprinted, self-adhering, 0.002-inch thick, clear polyester label printed with indelible black ink may be used. Self-adhering labels shall be applied after retorting. Pressure-sensitive adhesive shall require no preparation prior to application. Labels shall tack quickly and adhere without curling or breaking. The adhesive shall have a minimum adhesion of 60 ounces per inch width when examined as specified in 4.5.4.2. In addition, the name of the product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined as specified in 4.5.4 after preparation of product in accordance with heating instructions. Paper labels are not permitted. Cans shall show the following statements:

TO HEAT: Submerge unopened can in boiling water. Simmer gently 40 - 45 minutes. Avoid overheating (can shows evidence of bulging).

CAUTION: Use care when opening as pressure may have been generated within the can.

To heat in oven: Either punch several holes in lid of can or open can in usual manner leaving the loose lid in place. Place in a 350°F oven 35 - 40 minutes.

WARNING: Do not place unopened can in oven. This may cause the can to burst.

YIELD: Serves 18 portions of 2/3 cup each.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, when tray pack cans are fabricated from 90 pounds per base box, the following precautionary marking in capital letters larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT
OR MORE THAN TWO HIGH IN STORAGE,
UNLESS PALLET RACKS ARE USED.

6. NOTES

6.1 Ordering data. Acquistion documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1, 4.4, and 6.3).
c. Provisions for approved preproduction samples (see 3.6.1 and 6.3).
d. Level of preservation and packing required (see 5.1 and 5.2).
e. When tray pack cans are to be fabricated from 98 pounds per base box (see 5.1.1.1).
f. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on conditions known or expected to be encountered during shipment, handling and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 First article inspection. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Subject term (key word) listing.

Barbecue sauce
Beef
Canned foods
Combat field feeding
Thermostabilized
Tray pack

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

6.5 Changes from previous issue. Asterisks or vertical lines are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Review activities:

Army - MD, TS
Navy - MC
DP - SS

Preparing activity:

Army - GL

Project No. 8940-0605

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS. As a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US Army Natick Research, Development, and
Engineering Center
Natick, MA 01760-5014

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research, Development,
and Engineering Center
ATTN: STRNC-ES
Box 14A
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:43Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-44224A	Beef in Barbecue Sauce, Thermostabilized, Tray Pack

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil – Downloaded: 2026-02-22T00:43Z
Check the source to verify that this is the current version before use.