MIL-B-44225
23 June 1986
SUPERSEDING
C-B-002185(Army-GL)
March 31, 1983

MILITARY SPECIFICATION

BREAKFAST BAKE, THERMOSTABILIZED, TRAY PACK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers breakfast bake (French toast bake) thermostabilized in tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on the date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-C-495	-	Coatings, Exterior, for Tinned Food Cans
JJJ-S-30	-	Salad Oil, Vegetable
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8920

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:44Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification for

STANDARDS

MILITARY

MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-900 - Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks and Sugars Used in the Preparation of Thermostabilized Foods for the Armed Forces

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

OTHER GOVERNMENT DOCUMENTS

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

Regulations Governing the Inspection of Eggs and Egg Products (7 CFR Part 59)

(Application for copies should be addressed to the Poultry Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

U.S. Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:44Z
Check the source to verify that this is the current version before use.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Interim Primary Drinking Water Regulations

(Application for copies should be addressed to the Office of Drinking Water WH550, Environmental Protection Agency, Washington, DC 20460.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on the date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

NATIONAL ACADEMY OF SCIENCE

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for associated detail specifications, specification sheets, or MS standards), the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.4, 6.1, and 6.4).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent and or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:44Z
Check the source to verify that this is the current version before use.

3.2.1 Bread, white. Bread shall be commercial, soft crumb, enriched, white bread made by the continuous or conventional method. Other breads shall not be used. The bread shall be free from microbial deterioration such as mold, rope, sourness, musty odor, or any flavor or aroma not typical of soft crumb white bread. The commercial white bread used shall have a moisture content of not greater than 38.0 percent; protein content of not less than 8.0 percent; fat content of not less than 1.4 percent; and carbohydrate content of not less than 50.0 percent.

3.2.2 Water. Water used for formulations, ice making and washing shall conform to the National Interim Primary Drinking Water Regulations.

3.2.3 Cream, dry. The dry cream shall comply with FDA Standards of Identity (21 CFR) for dry cream, shall contain 70 to 75 percent by weight of milkfat, and shall contain no added nutritive sweeteners.

3.2.4 Eggs, whole, pasteurized. Whole eggs may be liquid or frozen and shall have been processed in accordance with the Regulations Governing the Inspection of Eggs and Egg Products (7 CFR Part 59). The whole eggs shall be egg whites and egg yolks in their natural proportions as broken directly from the shell as evidenced by a USDA Egg Products Inspection Certificate. The whole eggs shall contain no food additives and shall be in satisfactory condition, free from objectionable odors, such as musty, sour, or fruity. Liquid whole eggs shall be held at a temperature of 40°F or lower and shall be held for not more than 72 hours from the time of pasteurization until the start of formulation of the product in which they are used. Frozen whole eggs shall be held at 10°F or lower and used within 120 days. Frozen whole eggs shall be thawed and held at a temperature of 40°F or lower and shall be held for not more than 24 hours prior to use in the product.

3.2.5 Vegetable oil. Vegetable oil shall conform to type B of JJJ-S-30 and shall be cottonseed or corn oil or a combination thereof.

3.2.6 Sugar. Sugar shall be refined, sucrose, liquid or granulated cane or beet or a combination thereof. The sugar shall comply with the requirements of MIL-STD-900.

3.2.7 Salt. Salt shall be non-iodized, white, refined sodium chloride with or without anti-caking agents.

3.2.8 Flavoring, maple, imitation. The imitation maple flavoring shall be a double strength product possessing a color, flavor and odor characteristic of maple flavoring.

3.2.9 Lecithin. Lecithin shall comply with the Food Chemicals Codex.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:44Z
Check the source to verify that this is the current version before use.

3.3 Breakfast bake (French toast bake) preparation. The breakfast bake (French toast bake) shall be prepared from the following ingredients:

Ingredient	Percent by weight
Bread, white	20.40
Water	40.85
Cream, dry	1.00
Eggs, whole	27.85
Vegetable oil	2.00
Sugar	7.00
Salt	0.15
Maple flavoring, imitation	0.50
Lecithin	0.25

NOTE: The moisture content of the bread used in the formula shall be determined before combining with the above ingredients. If the moisture content is determined to be greater than 38 percent, that amount in excess shall be deducted from the percent water in the formulation. If the moisture content is less than 38 percent, adjust the formulation with the required amount of water.

The bread and half of the water shall be mixed to form a thick, smooth mass. The non-fat dry milk shall be rehydrated in the remaining water and gradually blended in with the bread mixture until a smooth, lump free mixture is formed. The remaining ingredients shall be added and mixed until the dry ingredients are dissolved and a uniform mixture is obtained. The temperature of the mixture shall not exceed 45°F at any time prior to filling into the cans. If the mixture is allowed to stand after mixing of the dry ingredients it shall be remixed before filling. In addition, the mixture shall be periodically stirred during can filling to prevent settling.

3.4 Tray pack filling and sealing. Each tray pack can (see 5.1.1) shall be filled with product so as to conform to the finished product requirements and to the following requirements.

a. Immediately after filling, each can shall be hermetically sealed under a vacuum of 5 to 8 inches of mercury as determined by presence of visible concavity of the can lid.

b. The filled and sealed tray pack cans shall be in the retort process within 1 hour after filling.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized by retorting until a sterilization value (F_o) of not less than 5 has been achieved. The filled and sealed thermoprocessed tray pack cans shall show no evidence of can swelling when tested for sterility as specified in 4.5.3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:44Z
Check the source to verify that this is the current version before use.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, dirt, insect parts, hair, wood, paper, paint, glass, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour, rancid, musty, or moldy.

c. There shall be no color foreign to the product.

d. The product shall have a tan surface with a uniform creamy-tan interior.

e. The product shall possess a slightly sweet maple flavor and aroma.

f. The product shall be uniform in appearance with a smooth surface and a moist, dense grainy custard interior and a dense, smooth, spongy texture.

g. The fat content of the finished product shall not exceed 9 percent.

h. The average net weight shall be 106 ounces.

i. No individual can shall contain less than 104 ounces of product.

3.6.1 Palatability. The finished product shall be equal to or better than the preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The product shall be prepared, processed, and packaged in establishments meeting the requirements of Title 21, Code of Federal Regulations, Para 110, "Current Good Manufacturing Practice in Manufacturing, Processing, Packaging or Holding of Human Foods", and the plant sanitation requirements of the appropriate Government inspection agency.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:44Z
Check the source to verify that this is the current version before use.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of supervision necessary to assure compliance with the requirements of this document.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.3 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this document and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this document or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be evident by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analysis, or other valid documents acceptable to the inspection agency. In addition, prior to use, each ingredient shall be examined organoleptically as necessary to determine con-formance to the condition requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:44Z
Check the source to verify that this is the current version before use.

4.5.3.1 Net weight inspection. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty tray pack cans and lids used in preparing the product and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average net weight is less than 106 ounces or if the net weight of any individual can is less than 104 ounces, the lot shall be rejected.

4.5.3.2 Product inspection. The sample size shall be as indicated by the double sampling plan specified by table I. The tray pack cans shall be selected at random from the lot. The tray pack cans shall be heated for at least 15 minutes in 140° to 150°F water, opened and inspected for the defects listed in table II.

TABLE I. Doubling sampling plan for product inspection 1/

Lot size (cans)	Sample size (No. of cans)	Cumulative sample	Acceptance number	Rejection number
0-3200	8	---	0	2
	8	16	1	2
3201-35000	13	---	0	3
	13	26	3	4

1/ a. If no defects are found in the first sample, the lot shall be accepted

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptable number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

TABLE II. Product defects 1/ 2/ 3/

Category	Defect
Major	
151	Product surface not tan, with a uniform creamy-tan interior.
152	Product does not possess a slightly sweet maple flavor and aroma.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:44Z
Check the source to verify that this is the current version before use.

TABLE II. Product defects 1/ 2/ 3/ (cont'd)

Category	Defect
Major	
153	Product not uniform in appearance and does not possess a smooth surface with a moist, dense grainy custard interior and a dense, smooth, spongy texture.

1/ The presence of foreign material (e.g., glass, dirt, insect parts, hair, wood, metal), foreign odor or flavor (e.g., burnt, scorched, moldy, rancid, sour, stale), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an Agricultural Marketing Service Agent (AMS)).

3/ The product shall be divided into ten approximately equal portions and examined for appearance and texture characteristics.

4.5.3.3 Fat content testing. Nine tray pack cans shall be selected at random from the lot and distributed as follows:

-Three for laboratory analysis
-Three for submission to the contractor
-Three for retention by the AMS agent as a reserve sample.

The three tray packs for laboratory analyses shall individually be tested for fat content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists: chapter: Cereal Foods, except that preparation of the samples shall be as follows. The three unopened cans shall be gently warmed in a water bath to melt fat adhering to the inside of the cans. The cans shall be opened and the entire contents of each can shall be separately blended in a Waring blender or equivalent. The lot shall be rejected if the fat content of any individual tray pack is greater than 9.0 percent. Report test results to nearest 0.1 percent. Analysis of reserve samples at the request of the contractor shall not be permitted unless the original laboratory analysis indicated that the involved lot will be rejected because of non-compliance with the fat content requirement. When the reserve samples are analyzed, the analysis for fat shall be made and will be considered final. Unused reserve samples shall be returned to the contractor for inclusion in subsequent lots.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:44Z
Check the source to verify that this is the current version before use.

4.5.3.4 Sterility testing. The sample size shall be one filled, sealed, and thermoprocessed tray pack can selected from each retort batch in the lot. The cans shall be tested for sterility by incubating the cans at 95°F plus or minus 2°F for 10 days. Any evidence of can swelling shall be considered a critical defect and cause rejection of the lot.

4.5.4 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the United States Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with MIL-L-1497 (see 5.4).

4.5.5 Can closure examination. Can closures shall be examined visually and by teardowns in accordance with CFR 21, Part 113, Subpart D and the can manufacturer's requirement.

4.5.6 Vacuum examination. Cans shall be examined 24 hours after sealing to determine vacuum retention. To examine, lay a straight edge from bead to bead and verify that the distance from the straight edge to the lid is greater at the middle of the can than near the bead.

4.5.7 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
Reinforced with other than nonmetallic strapping of tape.
Dimensions of pads not as specified.

Minor: Other required markings missing, incorrect or illegible.
Interior packing with fiberboard liner or pads not as specified.
Arrangement or number of cans not as specified.

4.5.8 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A or C as specified (see 6.1).

5.1.1 Level A. A size 1001 by 1206 by 200 tray pack can shall be filled with 106 ounces of the food product, sealed, and thermoprocessed as specified in 3.4 and 3.5. The base plate of the can shall be electrolytic chromium-coated steel and shall be of sufficient temper to protect the product during shipment and storage. The base plate weight of the body and end of each can shall be 90 pounds per base box. The entire inside area of the can shall be coated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:44Z
Check the source to verify that this is the current version before use.

Scratches or fractures shall not penetrate through the interior can coating. The interior can coating shall not peel or blister when in contact with the product. The interior can coating shall neither affect nor be affected by the packaged product. A certificate of conformance shall be furnished to certify compliance with the interior can coating requirements. The can shall be coated overall on the outside with a coating conforming to type I of TT-C-495.

5.1.2 Level C. The product shall be preserved as specified in 5.1.1, except that cans with commercial exterior coating will be acceptable.

5.2 Packing. The product shall be packed in accordance with level A, B, or C as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style HSC-L with a HSC full depth cover, grade V2s of PPP-B-636. The inside box dimensions shall be 12-3/4 inches in length by 10-1/2 inches in width by 8-1/2 inches in depth. The cans shall be packed flat, four in depth within the box, with two cans placed with covers down and two cans with covers up. The inside of each box shall be provided with a box liner and five fiberboard pads fabricated of grade V3c fiberboard. The dimensions of the fiberboard pads shall be 11-1/4 inches by 9-1/4 inches (± 1/8 inch) and the pads shall be placed between the cans and on the top and bottom of the stacked cans. Each box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1) except that the unit load shall consist of 48 boxes with 12 boxes per course and 4 courses per load with all courses having the same pattern so as to create columnar stacking. Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of the same material as the box.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:44Z
Check the source to verify that this is the current version before use.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified, except that the unit load shall consist of 48 boxes with 12 boxes per course and 4 courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping.

5.4 Labeling. Each tray pack can shall be labeled in accordance with MIL-L-1497. In addition, the name of product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined in accordance with 4.5.4 after submerging the can in boiling water for 30 minutes. Paper labels are not permitted. Cans shall show the following statements:

TO HEAT

a. To heat in water: Submerge sealed can in boiling water. Bring to boil, again and continue boiling for 40-45 minutes. Remove from water and open lid for serving.

CAUTION: Use care when opening as pressure may have been generated within the can.

b. To heat in oven: Either punch several holes in lid of tray can or open can in usual manner leaving the loose lid in place to prevent moisture loss. Place in a 350°F oven for approximately 35 to 40 minutes until contents reach an internal temperature of 165°F.

WARNING: Do not place closed can in oven, as heating will increase internal pressure which may cause the can to burst.

YIELD

Approximately 20 servings per tray and 5 ounces per serving.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract, shipping containers shall be marked in accordance with MIL-STD-129

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, the following precautionary marking in capital letters larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE.

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:44Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1, 4.4, and 6.4).
c. Provisions for approved preproduction samples (see 3.6 and 6.3).
d. Level of preservation and packing required (see 5.1 and 5.2).
e. Type and class of unit load when unit loading is required (see 5.2 and 5.3).

6.2 Appropriate level of pack. Based on conditions known or expected to be encountered during shipment, handling and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 First article inspection. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Preparing activity:

Army - GL

Project No. 8920-0477

Review activities:

Army - MD, TS
Navy - MC, MS
DP - SS

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:44Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:44Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-44225	Breakfast Bake, Thermostabilized, Tray Pack

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:44Z
Check the source to verify that this is the current version before use.