MIL-E-44200A
26 October 1988
SUPERSEDING
MIL-E-44200
15 January 1986

MILITARY SPECIFICATION

ESCALLOPED POTATOES WITH HAM, THERMOSTABILIZED, FOR MEAL, READY-TO-EAT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers thermostabilized escalloped potatoes with ham in flexible pouches for use as a component of the Meal, Ready-to-Eat, Individual.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATION

MILITARY

MIL-P-44073 - Packaging and Thermoprocessing of Foods in Flexible Pouches

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:33Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-900 - Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks, and Sugars Used in the Preparation of Thermo-stabilized Foods for the Armed Forces

(Copies of specifications, standards, and handbooks required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Copies may be obtained from the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

Meat and Poultry Inspection Regulations

(Copies may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

U.S. Standards for Grades of Butter

(Copies may be obtained from the Dairy Division, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2750, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Copies may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:33Z
Check the source to verify that this is the current version before use.

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Copies should be obtained from the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

AMERICAN DEHYDRATED ONION AND GARLIC ASSOCIATION (ADOGA)

Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products

(Copies should be obtained from the American Dehydrated Onion and Garlic Association, 650 California Street, Suite 800, San Francisco, CA 94108.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Copies should be obtained from the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Copies should be obtained from the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:33Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to the first article inspection (see 4.4, 6.1, and 6.2).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Water. Water used for formulation, blanching, and washing shall conform to the National Primary Drinking Water Regulations.

3.2.2 Ham, canned, or cooked. The ham shall be high commercial style. The ham shall not be labeled "water added," and shall not contain dextrose. The canned or cooked ham shall be maintained at an internal temperature of 28° to 40°F for a period of time not to exceed 60 days from date of pack until preparation of the finished product.

3.2.3 Potatoes, fresh. The potatoes shall be fresh, clean, sound, and of a white flesh variety suitable for canning. The maximum specific gravity for the potatoes shall be 1.075 with a reducing sugar content of not more than 2.0 percent on a dry weight basis.

3.2.4 Potatoes, dehydrofrozen, diced. Dehydrofrozen potatoes shall be firm, possess a good color and flavor and be of a white flesh variety suitable for canning. The maximum specific gravity for the potatoes shall be 1.075 with a reducing sugar content of not more than 2.0 percent on a dry-weight basis. The potatoes shall be mechanically diced to 3/8 inch cubes.

3.2.5 Shortening, vegetable, powdered. Powdered vegetable shortening shall consist of components which, when combined, will serve as a product whitening agent. The powdered shortening, when used as an ingredient in this product, shall withstand the specified thermoprocessing conditions without browning. A typical analysis of this powdered shortening follows:

Fat	75.00 percent	(±1.50 %)
Protein	5.50 percent	(±0.50 %)
Carbohydrates	15.00 percent	(±1.00 %)
Moisture	2.00 percent	Maximum

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:33Z
Check the source to verify that this is the current version before use.

3.2.6 Starch, food, modified, high opacity. High opacity starch shall be white, odorless, finely pulverized modified maize food starch for use in thermostabilzed foods. The modified starch shall demonstrate initial viscosity development in the temperature range of 140° to 170°F and a typical viscosity (be fully hydrated) at common retort temperatures. The modified starch shall resist breakdown at low pH, under shear stress. The cooked starch slurry shall be bland with essentially no cereal or starch taste and shall comply with MIL-STD-900.

3.2.7 Butter, lightly salted. Lightly salted butter shall be U.S. Grade A or better of the U.S. Standards for Grades of Butter.

3.2.8 Lecithin. Lecithin shall comply with the Food Chemicals Codex.

3.2.9 Onion powder. Onion powder shall be Fancy Grade of the Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products.

3.2.10 Pepper, white, ground. Ground white pepper shall be derived from the dried mature berries of Piper nigrum L. from which the outer covering or the outer and inner coverings have been removed. The ground pepper shall have a characteristic, penetrating odor, a hot biting pungent flavor, and a light color. The ground white pepper shall contain not less than 1.0 mL of volatile oil per 100 grams of ground white pepper and be of such size that not less than 95 percent shall pass through a U.S. Standard No. 40 sieve.

3.2.11 Celery seed, ground. Ground celery seed shall be derived from the seed of Apium graveolens L. and shall be light to rich brown in color and shall possess a characteristic celery odor and flavor with a warm, slightly bitter aftertaste. The ground celery seed shall contain not less than 2.0 mL of volatile oil per 100 grams of ground celery and be of such size that not less than 95 percent shall pass through a U.S. standard No. 35 sieve.

3.2.12 Starch, waxy maize, modified, filling and processing aid (see 6.3). Starch shall be white to off-white, odorless, finely pulverized powder suitable for use as a filling and processing aid in thermostabilized foods. When hydrated at temperatures of 165° to 200°F, the starch shall develop a paste. The initial viscosity of the paste shall be retained under conditions of moderate shear and prolonged holding times. During retorting at temperatures in excess of 200°F, the starch shall undergo extensive to complete breakdown of the initial viscosity. The starch shall be bland, shall demonstrate easy dispersibility, and shall comply with MIL-STD-900.

3.2.13 Preblended spice and seasoning mixture. Preblended spices and seasonings may be used. The spices and seasonings in the mixture shall comply with the requirements of this document. THe containers used for the spice and seasoning blend shall be labeled with each ingredient and the percentage of each ingredient in the blend. The ingredients shall be in the sampe proportions as specified in the ingredient formula.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:33Z
Check the source to verify that this is the current version before use.

3.3 Preparation and processing. Processing shall be on a continuous basis.

3.3.1 Preparation of ham. The ham shall be diced into 3/8 by 3/8 by 1/2 to 3/4 inch dices. The dices shall be blanched for a sufficient amount of time to comply with all finished product requirements. The broth shall be retained for use in the sauce preparation (see 3.3.4). If the blanched ham dices and ham broth are not immediately utilized in the product (see 3.3.4 and 3.3.5), the dices and broth shall be maintained separately at an internal temperature of 28° to 40°F for not more than 48 hours from the time of dicing to product preparation.

3.3.2 Preparation of potatoes.

3.3.2.1 Preparation of fresh potatoes. The fresh potatoes shall be thoroughly cleaned to remove the dark and extraneous material, peeled, trimmed, and thoroughly washed. The washed potatoes shall be mechanically diced into 3/8 inch cubes. The potato dices shall be blanched sufficiently to prevent discoloration and to remove excess air. The blanched potatoes shall be immediately cooled with cooling water to the initial temperature of the cooling water and thoroughly drained. The cooled, drained potato dices shall be handled in a manner to prevent discoloration prior to preparation, and filled into the pouches within 4 hours after blanching.

3.3.2.2 Preparation of dehydrofrozen potatoes. Dehydrofrozen potatoes shall be used without further preparation and handled in a manner to prevent discoloration prior to product preparation.

3.3.3 Filling and processing aid starch, preparation. When a filling and processing aid starch is used, a solution (slurry) shall be prepared with the filling and processing aid starch and part of the sauce formulation water in a concentration adequate to hold ingredients in suspension for uniform distribution during mixing and pumping of product.

3.3.4 Preparation of sauce. The sauce shall be formulated with the following ingredients:

Ingredient 1/	Percent by weight
Water and ham broth	89.43
Shortening, vegetable, powdered	4.00
Starch, food, modified, high opacity	3.50
Butter	2.00
Lecithin	0.25
Onion powder	0.75
Pepper, white, ground	0.06
Celery seed, ground	0.01

1/ The total amount of salt in the sauce formula shall be adjusted, as necessary, to produce a product that complies with the finished product salt requirements (see 3.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:33Z
Check the source to verify that this is the current version before use.

NOTE: The following sauce preparation procedures were used in the development of this product. Alternate procedures may be used provided finished product requirements are met. (When alternate procedures are used, the time and temperature requirements specified for the prepared sauce are still applicable.)

The sauce shall be prepared as follows:

a. A thin slurry shall be made with the starch, the powdered vegetable shortening, and part of the water.

b. The balance of the water and remaining ingredients shall be mixed together and heated to 180° to 190°F.

c. The starch slurry shall be added and the sauce vigorously stirred until the temperature reaches 150° to 170°F.

d. The volume of the sauce shall be adjusted with water to compensate for evaporation during heating and holding.

e. The sauce shall be filled within 4 hours after cooking. A filling and processing aid starch solution may be added in the amount required to facilitate uniform ingredient distribution in single-stage filling operations when dehydrofrozen potatoes are used. If a hot fill method is used, the prepared sauce shall be held in the temperature range of 150° to 180°F at all times prior to filling into the pouches. If a cold fill method is used, the prepared sauce shall be cooled immediately and held within a temperature range of 28° to 40°F at all times prior to filling into the pouches.

3.3.5 Product preparation. The product shall be formulated and prepared to comply with the finished product requirements (see 3.6 and 6.4).

3.4 Pouch filling and sealing. Each pouch (see 5.1) shall be filled with product to conform to the finished product requirements and to the following requirements:

a. Each pouch shall be filled and sealed in accordance with the pouch filling and sealing requirements specified for class 1 of MIL-P-44073.

b. A hot fill system is permitted if compatible with the single-stage or multi-stage filling and sealing method used.

c. The temperature of the ham, potatoes and sauce at time of filling shall be as specified (see 3.3.1, 3.3.2 and 3.3.4) for the applicable filling process used.

d. The ingredients may be filled into the pouch using either a single-stage or multi-stage filling operation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:33Z
Check the source to verify that this is the current version before use.

e. Each filled and sealed pouch shall be in the retort process within 2 hours after sealing.

3.5 Pouch thermoprocessing. The filled and sealed pouches shall be thermostabilized by retorting until a sterilization value (F_o) of not less than 6 has been achieved. The thermoprocessing operation shall be in compliance with the thermoprocessing requirements for class 1 of MIL-P-44073.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, dirt, insect parts, hair, wood, glass, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour, rancid, or moldy.

c. There shall be no color foreign to the product.

d. No individual pouch shall contain a bone piece measuring 0.3 inch or more in any dimension.

e. Total weight of skin, blood clots, bruised or discolored meat, cartilage, coarse connective tissue, section of tendons or ligments, and glandular material, collectively in any individual pouch shall be not more than 0.35 ounces.

f. The average net weight shall be not less than 8.0 ounces.

g. No individual pouch shall have a net weight of less than 7.5 ounces.

h. The drained weight of the ham dices in any individual pouch shall be not less than 2.0 ounces.

i. The average drained weight of the ham shall be not less than 2.5 ounces.

j. The drained weight of the potatoes in any individual pouch shall be not less than 1.5 ounces.

k. The average drained weight of the potatoes shall be not less than 2.0 ounces.

l. At least 75 percent of the ham shall be discernible dices.

m. Ham dice texture shall not be dry, rubbery, or mushy.

n. Potato dice texture shall not be hard, rubbery, fibrous, or mushy.

o. Sauce consistency shall be smooth, without lumps, and shall not be excessively thick or thin.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:33Z
Check the source to verify that this is the current version before use.

p. The average fat content of the finished product shall not be greater than 6.0 percent and no individual pouch shall have a fat content greater than 8.0 percent.

q. The salt content of the finished product in any individual pouch shall be not less than 0.5 percent nor greater than 1.2 percent.

r. The product shall show no evidence of excessive heating (materially darkened or scorched).

3.6.1 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The meat component and the finished product shall originate and be produced, processed, and stored in plants regularly operating under the Meat and Poultry Inspection Regulations of the U.S. Department of Agriculture.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection necessary to assure compliance with the requirements of this document.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this document and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this document or any appearance or palatability failure shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:33Z
Check the source to verify that this is the current version before use.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, and compliance be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods, such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, filling, sealing, and packaging requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation, or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Filled and sealed pouch inspection. Inspection of filled and sealed pouches shall be in accordance with the quality assurance provisions of MIL-P-44073.

4.5.4 Net weight inspection. The net weight of the filled and sealed pouches shall be determined by weighing each sample unit on a suitable scale tared with a representative empty pouch. Any individual net weight of less than 7.5 ounces shall be scored as a minor defect. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed pouch. The inspection level shall be S-3 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5. Results shall be reported to the nearest 0.1 ounce. In addition, the lot shall be rejected if the sample average net weight is less than 8.0 ounces.

4.5.5 Product and drained weight inspection.

4.5.5.1 Product inspection. The filled and sealed sample pouches shall be held for a minimum of 72 hours at room temperature (65° to 75°F) after completion of the thermoprocessing operation. The pouches shall be heated in 180° to 190°F water for 10 minutes, opened, and inspected. The lot size shall be expressed in pouches. The sample unit shall be the contents of one pouch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:33Z
Check the source to verify that this is the current version before use.

The sample size shall be as indicated by the sampling plan specified in table I. The contents shall be inspected for the defects indicated in table II.

TABLE I. Double sampling plan for product inspection 1/

Lot size (pouches)	Sample size (pouches)	Cumulative sample	Acceptance number	Rejection number
0 to 500,000	20	--	0	2
	20	40	1	2

1/ a. If no defects are found in the first sample, the lot shall be accepted.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second sample shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

TABLE II. Product defects 1/ 2/

Category	Defect
Major	
101	Presence of a bone piece measuring 0.3 inch or more in any dimension.
102	Total weight of skin, blood clots, bruised or discolored meat, cartilage, coarse connective tissue, section of tendons or ligments, and glandular material, collectively, in any individual pouch is more than 0.35 ounces.
103	Less than 75 percent of the ham consists of dicernible dices.
104	Texture of the ham dice is dry, rubbery or mushy.
105	Texture of the potato dice is hard, rubbery, fibrous, or mushy.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:33Z
Check the source to verify that this is the current version before use.

TABLE II. Product defects 1/ 2/ (cont'd)

Category	Defect
Major	
106	Sauce consistency is lumpy, not smooth, and is excessively thick or thin.
107	Product shows evidence of excess heating (materially darkened or scorched).

1/ The presence of foreign material (e.g. dirt, insect parts, hair, wood, glass, metal), foreign odor or flavor (e.g. burnt, scorched, moldy, rancid, sour, stale), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an Agricultural Marketing Service (AMS) agent.)

4.5.5.2 Drained weight inspection. The filled and sealed sample pouches shall be held for a minimum of 72 hours at room temperature (65° to 75°F) after completion of the thermoprocessing operation. The lot size shall be expressed in pouches. The sample unit shall be the contents of one pouch. The sample size shall be as indicated by the double sampling plan specified in table III. The drained weights shall be determined and inspected for the defects listed in table IV.

TABLE III. Double sampling plan for drained weight inspection 1/ 2/

Lot size (pouches)	Sample size (pouches)	Cumulative sample	Acceptance number	Rejection number
0 to 500,000	20	--	0	2
	20	40	1	2

1/ a. If no defects are found in the first sample, the lot shall be accepted.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:33Z
Check the source to verify that this is the current version before use.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

2/ To determine drained weight, the pouch contents shall be poured into a flat-bottom container. A minimum of three times the pouch's volume of 180° to 190°F water shall be added to the container so as to cover the contents. The contents and water shall be gently agitated so as to liquify rendered fat and to remove the sauce without breaking the ham dices or potatoes. The contents shall then be poured into a U.S. Standard 1/4 inch sieve in a manner that will distribute the product over the sieve without breaking the ham dices or potatoes. Sieve area shall be such that the distributed product does not completely cover all the openings of the sieve. The sieve shall be tilted at approximately a 45° angle and allowed to drain for 2 minutes. The drained weight of the ham dices and potatoes shall be determined individually and shall be reported to the nearest 0.1 ounce.

TABLE IV. Drained weight defects

Category	Defect
Major	
101	Drained weight of ham dices in a pouch is less than 2.0 ounces. 1/
102	Drained weight of potatoes in a pouch is less than 1.5 ounces. 2/

1/ If the sample average drained weight of the ham is less than 2.5 ounces, the lot shall be rejected.

2/ If the sample average drained weight of the potatoes is less than 2.0 ounces, the lot shall be rejected.

4.5.6 Fat and salt content testing. The unopened sample pouches shall be warmed in a water bath to melt fat adhering to the inside of the pouches. The sample pouches shall be opened and the entire contents of each pouch shall be separately blended in a Waring blender or equivalent. The fat and salt content of the product from each pouch in the sample shall be determined in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, Chapter: Meat and Meat Products. The test results shall be reported to the nearest 0.1 percent. Any result failing to

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:33Z
Check the source to verify that this is the current version before use.

conform to the fat or salt requirement in 3.6 shall be classified as a major defect. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed pouch. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 1.5.

4.5.7 Packaging inspection. Inspection of packaging shall be in accordance with the quality assurance provisions of MIL-P-44073.

5. PACKAGING

5.1 Packaging. Packaging shall be in accordance with the requirements of MIL-P-44073.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1, 4.4 and 6.2).
c. Provisions for approved preproduction samples (see 3.6.1 and 6.2).

6.2 First article. When a first article sample is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.3 Starch, waxy maize, modified, filling and processing aid. Shur-Fil ^{R} CS-500 starch, A.E. Staley Mfg. Co., Decatur, IL 62525 has been found to be satisfactory in holding ingredients in suspension for uniform distribution during mixing and pumping of product for single-stage filling operations.

6.4 Product preparation. Production tests have indicated that the following proportion of ingredients should produce a product which complies with the finished product requirements. Minor adjustments of the ingredient percentages by weight may be necessary in order to satisfy the different production systems.

a. When using fresh potatoes:

Ingredient	Percent by weight
Ham, diced, blanched	50.0
Potatoes, fresh, diced	25.0
Sauce	25.0

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:33Z
Check the source to verify that this is the current version before use.

b. When using dehydrofrozen potatoes:

Ingredient	Percent by weight
Ham, diced, blanched	50.0
Potatoes, dehydrofrozen, diced	12.5
Sauce	25.0
Water	12.5

6.5 Subject term (key word) listing.

Food Processing
Ham
Meal, Ready-To-Eat
Potatoes
Thermostabilized

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Review activities:

Army - MD, TS
Navy - MC, MS
DP - SS

Preparing activity:

Army - GL

Project No. 8940-0656

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:33Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-E-44200A	Escalloped Potatoes with Ham, Thermostabilized, For Meal, Ready-To-Eat

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE. NATICK/OP-1 Feb 86

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:33Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:33Z
Check the source to verify that this is the current version before use.