INCH-POUND

MIL-P-44206C
10 September 1993
SUPERSEDING
MIL-P-44206B
13 October 1988

MILITARY SPECIFICATION

POTATOES AU GRATIN, THERMOSTABILIZED, FOR MEAL, READY-TO-EAT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers thermostabilized potatoes au gratin in flexible pouches for use as a component of the Meal, Ready-to-Eat (MRE), Individual.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.1).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5018 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:35Z
Check the source to verify that this is the current version before use.

SPECIFICATION

MILITARY

MIL-P-44073 - Packaging and Thermoprocessing of Foods in Flexible Pouches

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

U.S. DEPARTMENT OF AGRICULTURE (USDA)

U.S. Standards for Grades of Cheddar Cheese (7 CFR Part 58)

(Copies are available from the Dairy Standardization Branch, Dairy Division, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2750, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations (7 CFR Part 58)
Dairy Plants Surveyed and Approved for USDA Grading Service
General Specifications for Dairy Plants Approved for USDA Inspection and Grading Service (7 CFR Part 58)

(Copies are available from the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, SW, Washington, DC 20460.)

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES (HHS), U.S. FOOD AND DRUG ADMINISTRATION (FDA)

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder (21 CFR Parts 1-199)

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

Source: https://assist.dla.mil -- Downloaded: 202640-22T00:35Z
Check the source to verify that this is the current version before use.

U.S. Standards of Identity for Margarine (21 CFR Part 166)

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.1).

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Application for copies should be addressed to the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

AMERICAN DEHYDRATED ONION AND GARLIC ASSOCIATION (ADOGA)

Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products

(Application for copies should be addressed to the American Dehydrated Onion and Garlic Association, One Maritime Plaza, 23rd Floor, San Francisco, CA 94111.)

AOAC INTERNATIONAL

Official Methods of Analysis of the AOAC

(Application for copies should be addressed to the AOAC International, 2200 Wilson Boulevard, Suite 400-CD, Arlington, VA 22201-3301.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to National Academy Press, 2101 Constitution Avenue, NW, Washington, DC 20418.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 202640-22T00:35Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified (see 6.1), a sample shall be subjected to first article inspection (see 6.2) in accordance with 4.4.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Potatoes, diced, dehydrofrozen. The diced, dehydrofrozen potatoes shall have been prepared from fresh, firm, potatoes which possess a good color and flavor and be of a white flesh variety suitable for canning. The maximum specific gravity for the fresh potatoes shall be 1.075 with a reducing sugar content of not more than 2.0 percent on a dry weight basis. The dehydrofrozen potatoes shall be of the latest season's pack. The fresh potatoes shall be mechanically diced with dicer settings at approximately 3/8 by 3/8 by 3/8 inch.

3.2.2 Cheese, cheddar, sharp, dehydrated, uncolored. Dehydrated cheddar cheese shall be derived from sharp, aged U.S. Grade A or better cheddar cheese. The cheddar cheese powder shall be manufactured in a USDA approved plant that meets the requirements contained in the General Specifications for Dairy Plants Approved for USDA Inspection and Grading Service (7 CFR Part 58). The dehydrated cheese shall be uncolored, uniform in composition and appearance, free from burnt specks and from lumps that do not fall apart under light finger pressure. The dehydrated cheese shall possess a characteristic flavor and odor. The dehydrated cheese shall contain not more than 4.0 percent moisture, 6.0 percent salt, and not less than 50.0 percent milkfat when calculated as milkfat in solids (fat on a dry basis).

3.2.3 Margarine. Margarine shall be of vegetable origin only and shall comply with the U.S. Standards of Identity for Margarine and shall possess a fine and pleasing flavor. The body shall be smooth, firm, and homogeneous. The margarine shall possess a uniform yellow color and may be salted or unsalted.

3.2.4 Shortening, vegetable, powdered. Powdered vegetable shortening shall consist of components which, when combined, will serve as a product whitening agent. The powdered shortening, when used as an ingredient in this product, shall withstand the specified thermoprocessing conditions without browning. A typical analysis of this powdered shortening follows:

Fat	75.00 percent (± 1.50%)	percent
Protein	5.50 percent (± 0.50%)	percent
Carbohydrates	15.00 percent (± 1.00%)	percent
Moisture	2.00 percent (Maximum)	

3.2.5 Salt. The salt shall be noniodized, white, refined, sodium chloride, with or without anticaking agents and shall comply with the purity standards for sodium chloride of the Food Chemicals Codex.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:35Z
Check the source to verify that this is the current version before use.

3.2.6 Starch, food, modified, high opacity. The high opacity starch shall be white, odorless, finely pulverized, modified waxy maize food starch for use in thermostabilized foods. The modified starch shall demonstrate initial viscosity development in the temperature range of 140°F to 170°F and be fully hydrated at common retort temperatures. The starch shall resist breakdown at low pH, under shear stress, and under conditions of cold storage. The cooked slurry prepared from the starch shall be bland with essentially no cereal or starch taste.

3.2.7 Onion powder. Onion powder shall be Fancy grade of the Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products.

3.2.8 Pepper, white, ground. Ground white pepper shall be derived from the dried mature berries of Piper nigrum L. from which the outer covering or the outer and inner coverings have been removed. The ground pepper shall have a characteristic, penetrating odor, a hot biting, pungent flavor, and a light color. The ground white pepper shall contain not less than 1.0 mL of volatile oil per 100 grams of ground white pepper and be of such size that not less than 95 percent shall pass through a U.S. Standard No. 40 sieve.

3.2.9 Preblended spice and seasoning mixture. Preblended spices and seasonings may be used. The spices and seasonings in the mixture shall comply with the requirements of this specification. The containers used for the spice and seasoning blend shall be labeled with each ingredient and the percentage of each ingredient in the blend. The ingredients shall be in the same proportions as specified in the ingredient formulation.

3.2.10 Water. Water used for formulation, rehydration, blanching, ice making, and washing shall conform to the National Primary Drinking Water Regulations.

3.2.11 Color, annatto, dry. Annatto color shall be a reddish-orange, water soluble powder of the extractive Annatto bixa Orellana. The powder shall contain not more than 10.0 percent moisture and 100 percent of the powder shall pass through a U.S. Standard No. 10 sieve. The total color (as percent Norbixin) shall be 15 percent. The dry annatto color shall have been held at a temperature of 45°F or lower during storage from date of pack to preparation of the potatoes au gratin. Refrigerated transportation from the annatto producer to user is not required.

3.2.12 Starch, waxy maize, modified (filling and processing aid). The starch shall be white to off-white, odorless, finely pulverized powder suitable for use as a filling and processing aid in thermostabilized foods. When hydrated at temperatures of 165°F to 200°F, the starch shall develop a paste. The initial viscosity of the paste shall be retained under conditions of moderate shear and prolonged holding times. During retorting at temperatures in excess of 200°F, the starch shall undergo extensive to complete breakdown of the initial viscosity. The starch shall be bland and shall demonstrate easy dispersability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:35Z
Check the source to verify that this is the current version before use.

3.2.13 Flavoring, cheddar cheese, natural. Natural cheddar cheese flavoring shall be of aged cheddar cheese and may be in paste or dry powder form. The natural chedar cheese flavoring may be enzyme modified cheddar cheese. The natural cheddar cheese flavoring shall not cause any browning in the finished product (see 6.3.1).

3.3 Preparation and processing. Processing shall be on a continuous basis.

3.3.1 Preparation of dehydrofrozen potatoes. The dehydrofrozen potato dices shall be blanched to approximately 1.5 times the frozen weight. The blanched potatoes shall be handled in such a manner as to prevent discoloration and shall be filled into the pouches within four hours after blanching.

NOTE: Alternatively, the dehydrofrozen potato dices may be blanched in the prepared sauce. The prepared sauce shall consist of additional water equal to 1.5 times the weight of the potatoes. Blanching shall be only to the extent necessary to ensure a uniform distribution for filling. The total batch weight shall be adjusted to compensate for water loss during heating and holding.

3.3.2 Sauce preparation. The sauce shall be formulated and prepared as follows:

Ingredients	Percent by weight
Water	79.463
Cheese, cheddar, sharp, dehydrated, uncolored	8.240
Margarine	4.120
Shortening, vegetable, powdered	3.640
Starch, food, modified, high opacity	2.110
Flavoring, cheddar cheese, natural	1.500
Salt 1/	0.520
Onion powder	0.340
Pepper, white, ground	0.060
Color, annatto, dry	0.007

1/ The total amount of salt in the sauce formula shall be adjusted, as necessary, to produce a product that complies with the finished product salt requirements (see 3.6).

NOTE: The following sauce preparation procedures were used in the development of this product. Alternative procedures may be used provided finished product requirements are met. (When alternative procedures are used, the time and temperature requirements specified for the prepared sauce are still applicable.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:35Z
Check the source to verify that this is the current version before use.

a. A slurry shall be made from the starch and part of the water.

b. The remaining ingredients shall be heated in a steam jacketed kettle to a temperature of 180°F to 190°F.

c. The starch slurry shall be added and stirred vigorously and continuously until the sauce reaches a temperature of 180°F to 190°F.

d. The volume of the final mixture shall be adjusted with water to compensate for evaporation loss during heating and holding.

e. The sauce shall be maintained in the temperature range of 150°F to 180°F and filled within four hours after preparation.

3.3.3 Filling and processing aid starch solution preparation. When a filling and processing aid starch is used, a solution (slurry) shall be prepared with the filling and processing aid starch and part of the sauce formulation water in a concentration adequate to hold ingredients in suspension for uniform distribution during mixing and pumping of product.

3.4 Pouch filling and sealing. Each pouch (see 5.1) shall be filled with product such as to conform to the finished product requirements and to the following requirements:

a. Each pouch shall be filled and sealed in accordance with the pouch filling and sealing requirements specified for class 2 of MIL-P-44073.

b. The temperature of the product at time of filling shall be 150°F to 180°F.

c. Each filled and sealed pouch shall be in the retort process within two hours after sealing.

3.5 Pouch thermoprocessing. The filled and sealed pouches shall be thermostabilized by retorting until a sterilization value (F_o) of not less than 6 has been achieved. The thermoprocessing operation shall be in compliance with the thermoprocessing requirements for class 2 of MIL-P-44073.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, dirt, insect parts, hair, wood, glass, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour, rancid, or moldy.

c. There shall be no color foreign to the product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:35Z
Check the source to verify that this is the current version before use.

d. No individual pouch shall contain less than 4.5 ounces of product.

e. The average net weight shall be not less than 5.0 ounces.

f. The texture of the potato dice shall not be mushy, hard, fibrous, or tough.

g. The potato dice shall be approximately uniform in size and shape.

h. The sauce consistency shall be smooth, without lumps, and shall not be excessively thick or thin.

i. The product shall show no evidence of excessive heating (materially darkened or scorched).

j. No individual pouch shall contain less than 2.0 ounces of drained potato dice.

k. The average drained weight shall be not less than 2.2 ounces or more than 3.2 ounces.

l. The salt content of the finished product in any individual pouch shall be not less than 0.5 percent nor greater than 1.0 percent.

3.6.1 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The product shall be prepared, processed, and packaged in establishments meeting the requirements of Title 21, Code of Federal Regulations, Part 110, "Current Good Manufacturing Practice in Manufacturing, Processing, Packaging or Holding Human Foods", and the plant sanitation requirements of the appropriate Government inspection agency.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The contractor shall ensure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection and supervision necessary to ensure compliance with the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:35Z
Check the source to verify that this is the current version before use.

4.3 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this document and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this document or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material examination. In accordance with 4.1, components and materials shall be examined in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, and compliance shall be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods, such as the standard methods described in the Official Methods of Analysis of the AOAC and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to preparation, processing, filling, sealing, and packaging requirements. Any nonconformance revealed by actual examination or by review of records of formulation or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Filled and sealed pouch inspection. Inspection of the filled and sealed pouches shall be in accordance with the quality assurance provisions of MIL-P-44073.

4.5.4 Net weight examination. The net weight of the filled and sealed pouches shall be determined by weighing each sample unit on a suitable scale tared with a representative empty pouch. Any individual net weight of less than 4.5 ounces shall be classified as a minor defect. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed pouch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:35Z
Check the source to verify that this is the current version before use.

The inspection level shall be S-3 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5. Results shall be reported to the nearest 0.1 ounce. In addition, the lot shall be rejected if the sample average net weight is less than 5.0 ounces.

4.5.5 Product and drained weight inspection.

4.5.5.1 Product inspection. The filled and sealed sample pouches shall be held for a minimum of 72 hours at room temperature (65°F to 75°F) after completion of the thermoprocessing operation. The pouches shall be heated in 180°F to 190°F water for 10 minutes, opened, and inspected. The lot size shall be expressed in pouches. The sample unit shall be the contents of one pouch. The sample size shall be as indicated by the sampling plan specified in table I. The contents shall be inspected for the defects indicated in table II.

TABLE I. Double sampling plan for product inspection 1/

Lot size (pouches)	Sample size (pouches)	Cumulative sample	Acceptance number	Rejection number
0 to 500,000	20	--	0	2
	20	40	1	2

1/ a. If no defects are found in the first sample, the lot shall be accepted.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second sample shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

TABLE II. Product defects 1/ 2/

Category	Defect
Major	
101	Potato texture mushy, hard, fibrous, or tough
102	Potato dice not approximately uniform in size and shape

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:35Z
Check the source to verify that this is the current version before use.

TABLE II. Product defects 1/ 2/ (cont'd)

Category	Defect
Major	
103	Sauce consistency lumpy or is excessively thick or thin
104	Product shows evidence of excessive heating (materially darkened or scorched)

1/ The presence of any foreign material (for example, dirt, insect parts, hair, wood, glass, or metal), foreign odor or flavor (for example, burnt, scorched, moldy, rancid, sour, stale), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot (see 3.6.1).

4.5.5.2 Drained weight inspection. The filled and sealed sample pouches shall be held for a minimum of 72 hours at room temperature (65°F to 75°F) after completion of the thermostabilization operation. The pouches shall be heated in 180°F to 190°F water for approximately 10 minutes, opened and inspected. The lot size shall be expressed in pouches. The sample unit shall be the contents of one pouch. The sample size shall be as indicated by the double sampling plan specified in table III. The drained weight shall be determined and inspected for the defects listed in table IV.

TABLE III. Double sampling plan for drained weight inspection 1/

Lot size (pouches)	Sample size (pouches)	Cumulative sample	Acceptance number	Rejection number
0 to 500,000	20	—	0	2
	20	40	1	2

1/ a. If no defects are found in the first sample, the lot shall be accepted.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:35Z
Check the source to verify that this is the current version before use.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second sample shall be combined, and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

TABLE IV. Drained weight defect 1/

Category	Defect
Major	
101	Drained weight of diced potatoes less than 2.0 ounces 2/

1/ To determine drained weight, the pouch contents shall be poured into a flat-bottom container. A minimum of three times the pouch's volume of 180°F to 190°F water shall be added to the container so as to cover the contents. The contents and water shall be gently agitated so as to separate sauce from potatoes. The contents shall then be poured into a U.S. Standard No. 1/4 inch sieve in a manner that will distribute the product over the sieve. The sieve area shall be such that the distributed product does not completely cover all the openings of the sieve. The sieve shall be tilted at approximately a 45° angle and allowed to drain for 2 minutes before determining the drained weight by subtracting the sieve tare weight from the gross weight. The drained weight shall be determined individually and shall be reported to the nearest 0.1 ounce.

2/ If the sample average drained weight is less than 2.2 ounces or more than 3.2 ounces, the lot shall be rejected.

4.5.6 Salt content testing. Eight filled and sealed pouches shall be selected at random from the lot. The product shall be tested for salt content in accordance with the Official Methods of Analysis of AOAC, method 935.47, except that preparation of the samples shall be as follows: The unopened pouches shall be gently warmed in a water bath to melt fat adhering to the inside of the pouches. The pouches shall be opened and the entire contents of each pouch shall be separately blended in a Waring Blendor or equivalent. The test results shall be reported to the nearest 0.1 percent. Any result failing to conform to the salt requirement in 3.6 shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.7 Packaging examination. Examination of packaging shall be in accordance with the quality assurance provisions of MIL-P-44073.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:35Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. Packaging shall be in accordance with the requirements of MIL-P-44073.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.4, and 6.2).
d. Provisions for approved preproduction samples (see 3.6.1 and 6.2).

6.2 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.3 Ingredient information.

6.3.1 Flavoring, cheddar cheese, natural. It has been found that "CHEDR SPRED III" manufactured by Chr. Hansen's Laboratory, Inc.; Enzyme Modified Cheddar Cheese Paste manufactured by Sanofi Bio-Industries; Natural Cheddar Cheese Flavor 094756 manufactured by F&C International, Inc.; and Natural Cheddar Cheese Flavor R7994 manufacutred by Haarman & Reimer meet the requirements of 3.2.13 and perform satisfactorily in this product.

6.4 Subject term (key word) listing.

Combat field feeding
Operational ration
Pouch food
Shelf stable

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:35Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Review activities:

Army - MD, QM
Navy - MC
DP - SS

Preparing activity:

Army - GL

(Project 8940-0743)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-P-44206C	1993 September 10

3. DOCUMENT TITLE

POTATOES AU GRATIN, THERMOSTABILIZED, FOR MEAL, READY-TO-EAT

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4501	256-4501
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-WT Natick, MA 01760-5018	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2020-10-22T00:35Z
Check the source to verify that this is the current version before use.