MIL-S-44215A(GL)
INTERIM AMENDMENT 1
1 May 1995

MILITARY SPECIFICATION

SWEATPANTS, PHYSICAL FITNESS UNIFORM (PFU)

This interim amendment is approved for use within the Department of the Army, and all Departments and Agencies of the Department of Defense, with MIL-S-44215A(GL), dated 23 February 1989.

PAGE 2

Para 2.1.1, under "Specifications" "Military", delete "MIL-T-43548 - Thread, Polyester Core: Cotton-, Rayon-, or Polyester-Covered", and add under "Specifications" "Federal", "A-A-50199 - Thread, Polyester Core: Cotton- or Polyester Covered".

PAGE 4

Para. 3.3.1, Line 3. After "rayon" add "or polyester".

Para. 3.3.1, Line 6. After "rayon" add "or polyester".

Para. 3.3.1, Line 17. Opposite "Weight, ounces per square yard", delete "8.2 ± 0.5" and substitute "8.45 ± .75".

Paragraph 3.3.1, Line 18. Opposite "Wales per inch", delete "21" and substitute "19".

PAGE 5

Para. 3.3.2, line 3. After "rayon" add "or polyester".

Para. 3.3.2, line 6. After "rayon" add "or polyester".

Para. 3.3.2, line 3. Opposite "Weight, ounces per square yard", delete "8.5 ± 0.5" and substitute "8.875 ± .875".

AMSC N/A FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:41Z
Check the source to verify that this is the current version before use.

PAGE 5

Para. 3.3.4, line 1. Delete "Gray 446" and substitute "Gray 466".

Para. 3.3.4.1, Colorfastness. Delete the paragraph in its entirety and substitute the following:

"3.3.4.1 Colorfastness. The finished cloth shall show fastness to laundering (after 3 cycles), and perspiration equal to or better than the standard sample or equal to or better than a rating of "good". The finished cloth shall show fastness to light (after 40 standard fading hours) equal to or better than a rating of "good". The finished cloth shall show fastness to crocking equal to or better than the standard sample or shall have an AATCC Chromatic Transferance Scale Rating of not lower than 3.5 when tested as specified in 4.4.1.2."

Para. 3.3.6, line 6. Under "Weight, ounces per linear yard", delete "0.046" and substitute "0.46 (minimum).

Para. 3.3.6, line 9. Opposite "Filling yarns per inch", delete "38 (+4)" and substitute "34 (minimum) 1/. At the end of the paragraph add the following footnote:

" 1/ When shuttleless looms are used, there will be 2 filling yarns pershed with a minimum of 68 filling yarns per inch."

Para. 3.3.7, line 2. Delete "MIL-T-43548" and substitute "A-A-50199".

PAGE 6

Para. 3.3.8, Drawcord. Delete the paragraph in its entirety and substitute the following:

"3.3.8 Drawcord. The drawcord shall be 1/4 inch diameter, 100 percent continuous filament texturized polyester yarn, hot knifed (or tips impregnated with cellulose acetate for a minimum of 1/2 inch) into lengths of 45-65 inches. The polyester shall be made with 150 denier 2-ply yarn consisting of 16 carriers having 6 ends per carrier and have a minimum breaking strength of 150 pounds. The drawcord shall be regular weave with no core. The drawcord shall be Light Gray DoD Standard Shade AV, C.A. 66064 and shall show "good" colorfastness to laundering".

Para. 3.3.11, last line. Delete "or medium".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:41Z
Check the source to verify that this is the current version before use.

PAGE 7

Para. 3.5.1.2, line 1. In the heading, after "Types", add "406,". At the end of the paragraph, add the following:

"Type 301 stitching may be used in repairing type 406 stitching.".

PAGE 8

Para. 3.7, TABLE I, Manufacturing Operations Requirements, Operation 1.c., line 1. Delete "same".

PAGES 9 and 10

Para. 3.7, TABLE I, Manufacturing Operations Requirements, Operation 4. Delete in its entirety and substitute:

"4. Seam rise, legs and gusset.				
a. Join center front seam.	504	SSa-1	10-14	50/2 50/2
b. Insert the label into the back seat seam 3/4 ± 1/2 inch below the seam of the waist, with the size visible (for alternate attachment of label size operation 5.b). Join center back seam.	504	SSa-1	10-14	50/2 50/2
c. Join both left and right leg seams from the bottom of the leg to the top where the gusset is to be joined.	504	SSa-1	10-14	50/2 50/2
d. Join the two ply gusset to to the left and right leg.	504	SSa-1	10-14	50/2 50/2
e. Insert the label into the back seat seam 3/4 ± 1/2 inch below the seam of the waist, with the size visible (for alternte attachment of label, see operation 5.b). Turn sweatpants right side out.				
f. Coverseam stitch all the seans."	406	SSb-2	8-12	50/2 50/2

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:41Z
Check the source to verify that this is the current version before use.

PAGE 12

Para. 3.8, TABLE II, Finished measurements (in inches). Delete all measurements for "Inseam C/" and substitute the following:

"29	30	31	32	33	+1, -1/2"

Para. 3.8, TABLE II, Finished measurements (in inches). Delete all measurements for "Outseam D/" and substitute the following:

"38-1/2	40	41-1/2	43	44-1/2	± 3/4"

Para. 3.8, TABLE II, Finished measurements (in inches). Delete all measurements for "Thigh (at gusset) I/" and substitute the following:

"13-1/4	14	14-3/4	15-1/2	16-1/4	± 1/2"

Para. 3.8, TABLE II, Finished measurements (in inches), Delete all measurements for "Crotch gusset width K/" and substitute the following:

"10	10	10	10	10	± 1/2"

Para. 3.8, TABLE II, Finished measurements (in inches), Delete all measurements for "Crotch gusset length L/" and substitute the following:

"2-1/4	2-1/4	2-1/4	2-1/4	± 1/2"

Para. 4.4.2, line 5. Delete "1.5" and "6.5" and substitute "1.0" and "4.0" respectively.

PAGE 18

Para. 4.4.3, line 6. Delete "4.0" and substitute "2.5".

Custodian:

Army - GL

Review activity:

Army - MD

Preparing activity:

DLA - CT

(Project No. 8415-A038)

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:41Z
Check the source to verify that this is the current version before use.