MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

DRIVER, FET, SWITCH, DIGITAL, KEY CODE GDP

This amendment forms a part of Military Specification MIL-M-28787/178B(EC), dated 27 April 1983, and is approved for use by the Naval Electronic Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 26

TABLE VIII: Delete and substitute new table VIII as printed on page 2 of this amendment.

Agent
DLA - ES

Preparing activity:
Navy - EC

(Project 5963-N634)

FSC 5963

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:29Z
Check the source to verify that this is the current version before use.

* TABLE VIII. Output crosstalk (low-level and high-level) test - Continued.

Test condition	Parameter	Connect				Initial limits 25°C ±5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	D to pin	Min	Max		
M9	OUT-9 Output crosstalk, low level	3,4,8,13, 17,18,23, 24,33,37, 38	29	Open	28	0	1	V	11,12
M10	OUT-10 "	3,4,8,13, 17,18,23, 24,28,37, 38	32	"	33	"	"	"	"
M11	OUT-11 "	3,4,8,13, 17,18,23, 24,28,33, 38	36	"	37	"	"	"	"
M12	OUT-12 "	3,4,8,13, 17,18,23, 24,28,33, 37	35	Open	38	"	"	"	"
N1	OUT-1 Output crosstalk, high level	4,8,13, 17,18,23, 24,28,33, 37,38	6	3	Open	"	800	mV	"
N2	OUT-2 "	3,8,13, 17,18,23, 24,28,33, 37,38	5	4	"	"	"	"	"
N3	OUT-3 "	3,4,13, 17,18,23, 24,28,33, 37,38	9	8	"	"	"	"	"
N4	OUT-4 "	3,4,8, 17,18,23, 24,28,33, 37,38	12	13	"	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 20260-20T16:29Z
Check the source to verify that this is the current version before use.