INCH-POUND

MIL-M-28787/196A(SH)
AMENDMENT 2
24 August 1990
SUPERSEDING
AMENDMENT 1
14 January 1985

*MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

RECEIVER, LINE, DIGITAL, KEY CODE BDM

This amendment forms a part of Military Specification MIL-M-28787/196A(SH), dated 14 January 1983, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

* TABLE I, Test conditions H1-H4 and H5-H8, Test type column: Delete "X" and substitute "S"

TABLE I, Test conditions K1-K8, Min columns: Delete "-0.70" (four places) and substitute "-0.40" (four places)

PAGE 8

* 4 4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through GG shall be performed in any order with the following exceptions. Test conditions A, B, C, D, E, F, G, H, and T are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D, E, F, G, H, or T are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, E, F, G, H, and T where applicable, followed by the remaining tests in the sequence."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:37Z
Check the source to verify that this is the current version before use.

TABLE XIII. Input threshold voltage (high to low) test.

Test condition	Parameter		Connect			Initial limits 25 ± 5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	Min	Max		
M1	1E	Input threshold voltage (high to low)	7	8	8	0.8	2 0	V	16
M2	2E	Input threshold voltage (high to low)	12	9	9	0 8	2.0	V	16
M3	3E	Input threshold voltage (high to low)	28	25	25	0 8	2.0	V	16
M4	4E	Input threshold voltage (high to low)	29	37	37	0.8	2.0	V	16

2

TABLE XIV. Input threshold voltage (low to high) test.

Test condition	Parameter		Connect			Initial limits 25 ± 5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	Min	Max		
N1	1E	Input threshold voltage (low to high)	7	8	8	0.6	2.0	V	16
N2	2E	Input threshold voltage (low to high)	12	9	9	0.6	2.0	V	16
N3	3E	Input threshold voltage (low to high)	28	25	25	0.6	2.0	V	16
N4	4E	Input threshold voltage (low to high)	29	37	37	0.6	2.0	V	16

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:37Z
Check the source to verify that this is the current version before use.

* 4.5.1, fifth line. Delete "H through FF" and substitute "J through S, U1–U8, V1–V8, W1–W8, X1–X8, Y1–Y12, Z1–Z12, FF".

* 4.5.3, third line and sixth line: Delete "H through FF" (two places) and substitute "J through S, U1–U8, V1–V8, W1–W8, X1–X8, Y1–Y12, Z1–Z12, FF" (two places).

PAGE 20

FIGURE 6, NOTE 3, add the following. "The test duration shall not exceed 5 seconds."

PAGE 33

TABLE XI, Test conditions K1 through K8, Min column. Delete "–0.70" and substitute "–0.40".

PAGE 37

TABLES XIII and XIV: Delete and substitute new tables XIII and XIV as printed on page 2 of this amendment

NOTE. The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment

Preparing activity:
Navy – SH

(Project 5963–N756)

Agent. NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:37Z
Check the source to verify that this is the current version before use.