INCH-POUND

MIL-M-28787/206A
AMENDMENT 1
31 March 1993

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

DRIVER, LAMP/RELAY, DIGITAL, KEY CODE FQB

This amendment forms a part of Military Specification MIL-M-28787/206A(EC), dated 23 August 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 5

TABLE I, Test conditions G1-G12, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions H1 and H2, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions J1-J12, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions K1 and K2, Test type column: Delete "X" and substitute "S".

PAGE 9

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through EE shall be performed in any order with the following exceptions. Test conditions A, B, C, D, E, F, G, H, J, and K are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D, E, F, G, H, J, or K are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, E, F, G, H, J, and K where applicable, followed by the remaining tests in the sequence."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:39Z
Check the source to verify that this is the current version before use.

4.5.1: Delete and substitute the following:

"4.5.1 Operating temperature tests. The operating temperature tests shall be conducted in accordance with MIL-M-28787. Before starting these tests, test conditions A through EE in table I shall be performed in the order specified in 4.4.2 using the initial limits at 25°C ambient. When electrical testing is called for at the end of each temperature stabilization period, test conditions L through AA and CC through EE shall be performed in the order specified in 4.4.2 using the initial limits for the applicable operating temperature. At all other times during the operating temperature tests, the module shall be operated in the test circuit shown on figure 2."

4.5.3: Delete and substitute the following:

"4.5.3 Life test. The life test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 2. Following the life test and while still at the maximum class temperature, electrical tests L through AA and CC through EE shall be performed in the order specified in 4.4.2 using the operating temperature end-of-life requirements in table I. Following the return of the module to 25 ± 5°C, electrical tests L through CC shall be performed in the order specified in 4.4.2 using the 25 ± 5°C ambient end-of-life requirements in table I."

PAGE 39

TABLE XIV: Delete and substitute new table XIV as printed on pages 3 and 4 of this amendment.

Custodians:
Army - ER
Navy - SH
Air Force - 85

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Preparing activity:
Navy - NW

(Project 5963-0178)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:39Z
Check the source to verify that this is the current version before use.

TABLE XIV. Output current (low-level) test.

Test cond	Parameter	Connect: A to pin	B to pin	C to pin	D to pin	E to pin	Initial limits 25 ± 5°C ambient: Min	Max	Unit	Test figure
N1	1D Output current, low level	11,15,12,6,9,24, 26,31,33,34,25	14	4	7	32	0	-4	μA	17
N2	2D	14,15,12,6,9,24, 26,31,33,34,25	11	16						
N3	3D	14,11,12,6,9,24, 26,31,33,34,25	15	19						
N4	4D	14,11,15,6,9,24, 26,31,33,34,25	12	2						
N5	5D	14,11,15,12,9,24, 26,31,33,34,25	6	3						
N6	6D	14,11,15,12,6,24, 26,31,33,34,25	9	17						
N7	7D	14,11,15,12,6,9, 26,31,33,34,25	24	23						
N8	8D	14,11,15,12,6,9, 24,31,33,34,25	26	38						
N9	9D	14,11,15,12,6,9, 24,26,33,34,25	31	37						
N10	10D Output current, low level	14,11,15,12,6,9, 24,26,31,34,25	33	39	7	32	0	-4	μA	17

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:39Z
Check the source to verify that this is the current version before use.

TABLE XIV. Output current (low-level) test - Continued.

Test cond	Parameter	Connect					Initial limits 25 ± 5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	D to pin	E to pin	Min	Max		
N11	11D Output current, low level	14,11,15,12,6,9, 24,26,31,33,25	34	22	7	32	0	-4	μA	17
N12	12D	14,11,15,12,6,9, 24,26,31,33,34	25	29	7	32				
N13	1D	7,14,11,15,12,6, 9,24,26,31,33,34, 25	Open	4	Open	Open				
N14	7D Output current, low level	32,14,11,15,12,6, 9,24,26,31,33,34, 25	Open	23	Open	Open	0	-4	μA	17

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:39Z
Check the source to verify that this is the current version before use.