
INCH-POUND
MIL-C-39010/9B
4 January 1994
SUPERSEDING
MIL-C-39010/9A
1 March 1985

MILITARY SPECIFICATION SHEET

COILS, FIXED, RADIOFREQUENCY, MOLDED, MICROMINIATURE (IRON CORE), ESTABLISHED RELIABILITY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-39010.



Ltr	Dimensions are in inches with metric equivalents (mm) in parentheses	
	Minimum	Maximum
A	.085 (2.16)	.105 (2.67)
B	.240 (6.10)	260 (6.60)
C	1.250 (31.75)	1.626 (41.30)
D	0185 (0 470)	0215 (0.546)

NOTES:
1. Dimensions are in inches
2. Metric equivalents are given for information only

FIGURE 1 Dimensions and configuration

(B) denotes changes.

AMSC N/A
FSC 5950

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 202610-21T16:32Z
Check the source to verify that this is the current version before use.

REQUIREMENTS.

Design, construction, and physical dimensions: See figure 1

Material Iron core

(B) Weight 0.01 ounce maximum.

Operating temperature range -55°C to +105°C.

Dielectric withstanding voltage Method 301 of MIL-STD-202; test voltage of 1,000 V rms.

Barometric pressure. Method 105, test condition C, of MIL-STD-202, 70,000 feet with a test voltage of 300 V rms.

Electrical characteristics: See tables I and II.

Inductance. See table I.

Inductance tolerance See table I.

Q values. See table I

Self-resonant frequency See table I

DC resistance. See table I.

Temperature rise. 15°C

Terminal pull. 5 pounds.

(B) Part or Identifying Number (PIN) M39010/09 (dash number from table I).

(B) Supersession data This specification supersedes MS75084 dated 4 September 1985.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:32Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics (initial) and dash numbers.

Dash number 1/	Inductance µH	Inductance tolerance ± percent	Q minimum	Test frequency (MHz)	Self-resonant frequency minimum (MHz)	DC resistance (25°C) maximum (ohms)	Rated dc current (mA) 2/
A1R1**	1.1	5	25	7.9	150	.18	590
A1R2**	1.2	5, 10	25	7.9	150	.18	590
A1R3**	1.3	5	25	7.9	140	.22	535
A1R5**	1.5	5, 10	28	7.9	140	.22	535
A1R6**	1.6	5	28	7.9	125	.30	455
A1R8**	1.8	5, 10	30	7.9	125	.30	455
A2R0**	2.0	5	30	7.9	115	.40	395
A2R2**	2.2	5, 10	30	7.9	115	40	395
A2R4**	2.4	5	30	7.9	100	.55	335
A2R7**	2.7	5, 10	37	7.9	100	55	335
A3R0**	3 0	5	37	7 9	90	.85	270
A3R3**	3 3	5, 10	45	7 9	90	.85	270
A3R6**	3 6	5	45	7.9	80	1.00	250
A3R9**	3 9	5, 10	45	7.9	80	1.00	250
A4R3**	4 3	5	45	7.9	75	1.20	230
A4R7**	4 7	5, 10	45	7.9	75	1 20	230
A5R1**	5 1	5	45	7 9	65	1.80	185
A5R6**	5.6	5, 10	50	7.9	65	1.80	185
A6R2**	6.2	5	50	7.9	60	2 00	175
A6R8**	6 8	5, 10	50	7 9	60	2 00	175
A7R5**	7 5	5	50	7.9	55	2.70	155
A8R2**	8.2	5, 10	55	7.9	55	2.70	155
A9R1**	9 1	5	55	7.9	50	3 70	130
A100**	10 0	5, 10	55	7.9	50	3 70	130
A110**	11.0	5	45	2 5	40	2.70	130
A120**	12 0	5, 10	45	2.5	40	2 70	155
A130**	13 0	5	40	2 5	35	2.80	150
A150**	15 0	5, 10	40	2 5	35	2 80	150
A160**	16 0	5	40	2.5	30	3.10	145
A180**	18 0	5, 10	50	2.5	30	3 10	145
A200**	20.0	5	50	2.5	25	3.30	140
A220**	22.0	5, 10	50	2 5	25	3 30	140
A240**	24 0	5	50	2 5	20	3 50	135
A270**	27.0	5, 10	50	2 5	20	3.50	135

1/ The complete dash number will include two additional letters (indicated by **) The first additional letter will indicate the inductance tolerance and the second additional letter will indicate the failure rate symbol (e g , M, P, R, S) and will be added to the end of the dash number

2/ The rated dc current is based on 90°C ambient temperature with a 15°C rise.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:32Z
Check the source to verify that this is the current version before use.

(B) TABLE II. Electrical characteristics (final). 1/

Inspection group	Allowable variation from initial measurement		Allowable percent from specified minimum value in electrical characteristics (initial) table	
	Inductance (percent)	DC resistance	Self-resonant frequency	Q
Qualification inspection				
Group II	±2	---	---	-10
Group IV	±5	±(3% +.001 ohm)	2/	-10
Group V	±5	±(2% +.001 ohm)	2/	-15
Quality conformance inspection Group B				
Subgroup 1	±5	±(2% + 001 ohm)	2/	-15
Subgroup 3	±2	---	---	-10
Subgroup 4	±5	±(3% + 001 ohm)	2/	-10

1/ Test fixture allowance of +.01 µH shall be added to all change in inductance limits ±(_ percent +.01 µH).

2/ The self-resonant frequency shall be not less than the value specified in table I

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Army - AR, ME, MI
Navy - AS, CG, MC, OS, SH
Air Force - 17, 19, 99
DLA - ES

Preparing activity
Army - ER

Agent
DLA - ES

(Project 5950-0831-08)

Source: https://assist.dla.mil -- Downloaded: 202610-21T16:32Z
Check the source to verify that this is the current version before use.