MIL-I-15650E(SH)
27 July 1979
SUPERSEDING
MIL-I-15650D(SHIPS)
17 April 1970
(See 6.5)

MILITARY SPECIFICATION

INCINERATORS, SHIPBOARD USE

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers incinerators of 500 pounds per hour capacity for shipboard use.

1.2 Classification. Incinerators shall be of the following types, as specified (see 6.2):

Type I - Weight and size restricted (see 3.9).
Type II - Weight and size not restricted (see 3.9).

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

FEDERAL
PP-B-171 - Bearings, Ball, Annular (General Purpose).
PP-B-185 - Bearings, Roller, Cylindrical; and Bearings, Roller, Self-Aligning.
PP-B-187 - Bearings, Roller, Tapered.
TT-P-645 - Primer, Paint, Zinc-Chromate, Alkyd Type.

MILITARY
MIL-E-917 - Electric Power Equipment, Basic Requirements for (Naval Shipboard Use).
MIL-S-1222 - Studs, Bolts, Hex Cap Screws and Nuts.
MIL-C-2212 - Controllers, Electric Motor, A.C. or D.C. and Associated Switching Devices, Naval Shipboard.
MIL-I-2819 - Insulation Block, Thermal.
MIL-Q-9858 - Quality Program Requirements.
MIL-P-15024 - Plates, Tags and Bands for Identification of Equipment.
MIL-P-15024/5 - Plates, Identification.
MIL-B-15382 - Bolt, Firebrick Anchor.
MIL-B-15606 - Bricks, Refractory, Naval Boiler Furnace Lining Quality.
MIL-B-16008 - Brick, Insulating, High Temperature, Fire Clay.
MIL-B-16305 - Brick, Refractory, Insulating.
MIL-M-17060 - Motor, 60 Hertz, Alternating Current, Integral HP (Shipboard Use).

STANDARDS

FEDERAL
FED-STD-595 - Colors.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Naval Sea Systems Command, SEA 3112, Department of the Navy, Washington, DC 20362 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4540

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:22Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-108 - Definitions of and Basic Requirements for Enclosures for Electric and Electronic Equipment.
MIL-STD-167-1 - Mechanical Vibrations of Shipboard Equipment (Type I - Environmental and Type II - Internally Excited.
MIL-STD-278 - Fabrication Welding and Inspection; and Casting Inspection and Repair for Machinery, Piping and Pressure Vessels in Ships of the United States Navy.
MIL-STD-769 - Thermal Insulation Requirements For Machinery and Piping.
MIL-STD-882 - Systems Safety Program Requirements.
DOD-STD-1399, Section 300 - Electric Power, Alternating Current (Metric).

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)
ASME Boiler and Pressure Code.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th St., New York, NY 10018.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC. AGENT
National Motor Freight Classification.

(Application for copies should be addressed to the National Motor Freight Traffic Association, Inc., ATA TRAFFIC Dept., 1616 "P" Street, N.W., Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE AGENT
Uniform Freight Classification Ratings, Rules, and Regulations.

(Application for copies should be addressed to the Uniform Classification Committee Agent, Tariff Publication Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Qualification. Incinerators furnished under this specification shall be products which are qualified for listing on the applicable qualified products list at the time set for opening of bids (see 4.2 and 6.3).

3.2 Materials.

3.2.1 Metals. Furnace doors, ashpit doors, and fire bed grates shall be constructed of cast iron. The other metal parts shall be fabricated of materials suitable for operating conditions and temperatures. Carbon steel shall be used for operating temperatures up to 775°F. Metal parts which are exposed to operating temperatures in excess of 775°F shall be fabricated of materials selected in accordance with design parameters permitted by the ASME Boiler and Pressure Vessel Code.

3.2.2 Refractory and insulating materials. The combustion chamber shall be lined, as required, with the material shown in table I. Incinerator combustion chamber refractories and insulating materials shall comprise only those shapes and dimensions carried in the Naval supply system. The refractories and insulating material shall be of a quality, arranged to withstand the effects of the heat combustion and the normal mechanical and thermal shock incident to Naval shipboard operation for a minimum of 10,000 hours without major deterioration, spalling, or crumbling. Anchor bolts, where used shall be furnished in accordance with MIL-B-15382.

Source: https://assist.dla.mil -- Downloaded: 202640-18T06:22Z
Check the source to verify that this is the currentversion before use.

TABLE I. Refractory and insulation materials.

Material	Specification
Firebrick	MIL-B-15606, grade B
Thermal insulating brick	MIL-I-16008
Refractory insulating brick	MIL-B-16305, class B
Insulating block	MIL-I-2819, class 3

3.2.2.1 Lagging. The incinerator shall be insulated and lagged, if and where necessary, to bring temperature within that specified in 3.6.

3.2.3 Bolts and threads. The bolts and threads shall conform to MIL-S-1222.

3.2.4 Recovered materials. Unless otherwise specified herein, all equipment, material, and articles incorporated in the products covered by this specification shall be new and shall be fabricated using materials produced from recovered materials to the maximum extent practicable without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products is allowed under this specification unless otherwise specifically specified.

3.2.5 Prohibited materials. Incinerators furnished under this specification shall contain no asbestos, mercury, or cadmium plating, or materials containing asbestos, mercury or cadmium plating. A certificate of compliance shall be provided at the time of qualification.

3.3 General requirements. Unless otherwise specified in the contract or order (see 6.2.1), the incinerator shall be furnished complete with fans and with the necessary connecting air ducts, and foundation plate or support if required. The arrangement of the unit shall provide easy access for examination and repair of all internal parts, such as the spark arrester, with the unit installed in its intended shipboard incinerator room. The incinerator shall be supplied in either the completely-assembled or knocked-down condition at the prerogative of the shipbuilder (see 6.2.1). If knocked down, the size of each piece shall be capable of passing through a 26 inch x 66 inch or a 30 inch x 60 inch opening provided in the ship for the room when completely finished.

3.4 Design requirements. The incinerator shall provide a suction in the furnace during all rates of operation, thereby permitting operation in an open compartment (not pressurized). The incinerator shall burn the rated capacity of trash (see 3.9) when installed in a compartment open to atmospheric pressure, with a possible back pressure of 3 inch water gage at 70°F imposed by the incinerator exhaust stack, and shall operate without the emission of sparks or flyash from the gas outlet, and without the egress of smoke or flame through either the fire door, when opened for firing, or any other opening in the incinerator. Except for the periods indicated herein, the emission of smoke from the stack outlet, during operation of the unit, will not be acceptable. Some smoking will be tolerated when it occurs in the interim period between the start of firing from a cold state to the time when equilibrium temperature conditions exist through the walls of the combustion chamber; also, during the raking of the fire bed and for a short period subsequent to feeding of a new supply of trash (see 4.4.1.3 and 4.4.1.4).

3.4.1 Grating. Air flow (open) area through the furnace grates shall not exceed 40 percent of total furnace (grating) area to prevent trash from dropping through the grates before being completely incinerated. Maximum width of any grating opening shall not exceed 1-1/8 (narrowest dimension) inches.

3.4.2 Furnace door. Design of furnace door shall be such that when closed it retains an effective, tight seal under shipboard conditions up to a maximum 10 degree pitch and a 45 degree roll.

3.4.3 Bearings. Bearings for rotating parts shall be in accordance with FF-B-171, FF-B-185, or FF-B-187.

3.4.4 Lubrication. Sliding parts not permanently lubricated shall be provided with a readily accessible means for lubrication.

Source: https://assist.dla.mil -- Downloaded: 20261O-18T06:22Z
Check the source to verify that this is the current version before use.

3.4.5 Welding. Welding shall conform to the requirements of MIL-STD-278.

3.4.6 Safety. The incinerator design shall be analyzed in accordance with MIL-STD-882. Moving parts, parts subject to high temperature, or electrically energized shall be insulated, fully enclosed, or properly guarded to prevent hazards to operating personnel. Access covers shall be lockable or removable by hand tools only. Safety devices shall be designed so that they cannot be easily circumvented.

3.4.7 Enclosure for electrical circuitry. Control devices or electric circuitry that will be exposed during cleaning of the incinerator shall be spraytight in accordance with MIL-STD-108.

3.5 Fans. Unless otherwise specified (see 6.2.1) fan(s) shall be furnished directly mounted on the incinerator or mounted to a structural base, (for the purpose of providing draft for combustion, intercasing air cooling, and cool exhaust gases) to meet the design and operational requirements of this specification. The requirements for the fan motor voltage shall be as specified (see 6.2.1). Gaskets and washers shall be provided for the flanges and bolting to preclude metal-to-metal between the fans and the incinerator. Gaskets shall not be made of asbestos.

3.6 Surface temperatures. Except for clean-out doors and doors leading into the furnace and ashpit areas, no exposed surface of the incinerator shall exceed a temperature of 150°F when the unit is operating at full rated capacity in a 70°F ambient atmosphere. The incinerator shall be provided on all sides with a double casing having intercasing air cooling (see 3.5) to reduce temperatures to the limit specified. If necessary, asbestos-free lagging may be used (see 3.2.2.1), in accordance with MIL-STD-769.

3.6.1 Stack outlet temperatures. Incinerator exhaust gas outlet temperature shall not exceed 650°F for both types.

3.7 Spark arrester. A spark arresting device shall be included as an integral part of the unit. The use of water to arrest sparks will not be permitted. The incinerator shall be capable of operation at its rated capacity without spark or flyash (see 3.4). The material from which the spark arrester is fabricated shall depend upon operating temperatures encountered with the particular unit. Metal material shall be as delineated in 3.2.1.

3.8 Electrical and control requirements. Electrical and control requirements shall be in accordance with MIL-E-917 and MIL-C-2212, respectively, for design, materials, and construction of electrical and control items.

3.8.1 Electrical power supply. Unit shall operate on type I power in accordance with DOD-STD-1399, section 300. Power required shall be 440-volt, 3-phase, 60-Hertz (Hz).

3.8.2 Motors. Motors shall be a.c. in accordance with MIL-M-17060. Motors shall be 3-phase. The motor classification shall be service C. Motors shall be totally enclosed fan-cooled (TEFC).

3.9 Characteristics. Incinerators, completely assembled, including spark arrester, all appendages such as fans, air ducts, and the necessary straight run of exhaust outlet, shall meet the characteristics specified in table II.

TABLE II. Characteristics.

	Type I	Type II
Burning capacity	500 pounds of trash per hour	500 pounds of trash per hour
Mass	12,000 pounds max	Over 12,000 pounds
Box volume	880 cubic feet, max	Over 880 cubic feet
Dimensions:		
Width and length	Approximately equal	-------
Height (excluding 4 to 5 inches high foundation)	6 ft, 9 in, max	Over 6 ft, 9 in

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:22Z
Check the source to verify that this is the current version before use.

3.9.1 Arrangement. The arrangement of the incinerator for firing (right-hand, left-hand, or end fired), and the location of the firing door with relation to the exhaust outlet shall be as specified (see 6.2.1).

3.10 Vibration. Components shall be capable of meeting, and be installed in accordance with type I requirements of MIL-STD-167-1.

3.11 Operating instructions. Instructions outlining the proper operating procedure for operating the incinerator shall be furnished in the form of a rigid placard of fireproof and waterproof material suitable for mounting on a bulkhead in the incinerator compartment.

3.12 Tools. A set of tools consisting of a rake and hoe for the handling and leveling of fires and cleaning the fire bed and ashpit shall be furnished with each unit.

3.13 Identification plates. Identification plates and other designating markings shall be in accordance with MIL-P-15024 and MIL-P-15024/5, type H normal service plates. These plates shall be installed on and furnished as part of the incinerator and of the fans when supplied. The plates shall be located in a readily accessible position on outer casing or housing where they can be read at all times without danger to personnel. Data marked on identification plates shall include the following:

(a) Manufacturer's name.
(b) Applicable specification and type.
(c) Manufacturer's contract or serial number.
(d) Arrangement (see 3.9.1).
(e) Statement "Free of asbestos, mercury, and cadmium plating".

3.14 Painting. All metal parts of the incinerator, except the fan and cast iron grates, shall be given two coats of zinc chromate primer conforming to TT-P-645, to be followed by two coats of haze gray paint conforming to color number 26270 in accordance with FED-STD-595.

3.15 Manuals. The contractor shall prepare technical manuals in accordance with the data ordering document included in the contract or order (see 6.2.2).

3.16 Drawings. In addition to the drawing content required by the data ordering document (see 6.2.2), the following features shall be included:

(a) List of material.
(b) Overall dimensions shall be indicated for assemblies and subassemblies.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality program. The contractor shall provide and maintain a quality program acceptable to the Government for supplies and services covered by this specification. The quality program shall be in accordance with MIL-Q-9858 (see 6.2.1).

4.2 Qualification tests. Qualification tests shall be conducted at a laboratory satisfactory to NAVSEA. Qualification tests shall consist of the examination of 4.3 and the tests specified in 4.4.

4.3 Examination. Each incinerator offered for delivery shall be subjected to examination to determine compliance with the requirements of this specification that do not involve tests. Examination shall be conducted as specified in table III.

Source: https://assist.dla.mil -- Downloaded: 202610-18T06:22Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of defects.

Categories	Defects
Critical:	None defined
Major:	
101	Incinerator not complete; component parts missing; not in accordance with drawings.
102	Component parts not new: evidence of reclaimed, used, or salvaged components.
103	Evidence of use of unauthorized materials or repairs.
104	Incinerator not of type specified.
105	Furnace doors, ashpit doors, and fire bed grates not constructed of cast iron.
106	Refractory and insulating materials as specified for lining combustion chamber.
107	Insulation and lagging for incinerator missing.
108	Bolts and threads nonconforming.
109	Incinerator not supplied in "knocked down" condition; fans not supplied when required; piece dimensions outside, nonconforming.
110	Fans when required, nonconforming to specification.
111	Fan motor voltage not as specified.
112	Insulating gaskets and washers missing from flanges and bolting.
113	Spark arrester of proper type not provided.
114	Rake and hoe not provided.
115	Parts not free of moisture, dirt, oil, grease, chips.
Minor:	
201	Operating instruction plates not provided; plates not fire and water proof.
202	Technical manual not furnished.

4.4 Tests.

4.4.1 Smoking.

4.4.1.1 During daylight hours, the incinerator shall be lighted off using a 20-25 pound load of trash consisting of paper, wood, cardboard, and cloth. As soon as the trash in the unit is burning freely, new loads of identical size and of the same composition shall be inserted as frequently as firing conditions permit, until the fire bed is built up to, and maintained at the design level. For test purposes, the height of stack installed at the incinerator's exhaust gas outlet flange shall not exceed 7 feet; furthermore, the stack outlet shall be shielded with a rain hood only and contain no mesh screen or Liverpool hood. Provision shall be made for imposing a maximum of 3 inches of water stack resistance (back pressure) at the unit's exhaust outlet. In addition, the incinerator exhaust gas outlet pipe shall be run within an outer steel pipe separated from the inner pipe by a 2 inch annular air space. This air space shall be arranged to allow for circulation of the cooling air from between the incinerator double casing (see 3.6) to the weather outlet. Unit must be adjusted to burn the rated capacity of trash without smoking or sparking with one air inlet setting for all operation. Two separate settings of the various air adjustments on the unit, one for daytime and one for nighttime operation, will not be permitted.

4.4.1.2 By the time equilibrium temperature conditions exist through the combustion chamber walls, all smoking from the stack outlet shall have ceased.

4.4.1.3 With the fire bed at the design level, and burning freely, it shall be vigorously raked and smoking conditions noted. If smoke is emitted from the stack outlet, its duration shall be shortlived, not to exceed a period of 60 seconds.

4.4.1.4 The duration of smoking, subsequent to the addition of new loads of trash (charging), raking and ashpit clean-out shall not exceed a period of 60 seconds.

Source: https://assist.dla.mil -- Downloaded: 202610-18T06:22Z
Check the source to verify that this is the current version before use.

4.4.2 Sparking.

4.4.2.1 The incinerator shall be operated at night for this phase of the test.

4.4.2.2 Under all or any condition of operation whatsoever, no sparks or embers shall be emitted from the stack outlet.

4.4.3 Capacity. After the fire bed in the incinerator has been built up to the design level, and is burning freely, a time log shall be maintained, and after each 3-minute interval, approximately 25 pounds of trash, made up as specified in 4.4.1.1, shall be loaded into the unit. The mass of the individual loadings shall be varied, as necessary, to maintain the fire bed at a constant level. The incinerator shall be operated continuously for a period of 8 hours and shall meet the 500 pounds capacity (see 3.9).

4.4.3.1 Ash and residue. During the qualification operational tests, the frequency and number of times that the ashpit is cleaned out shall be recorded. All ash and residue removed shall be carefully weighed. The weight shall not exceed 3 percent of the total mass of material incinerated.

4.4.4 Electrical enclosures. Enclosures for electrical circuitry or equipment shall be subjected to the test of MIL-STD-108 for enclosures designated spraytight to assure conformity with 3.4.7.

4.4.5 Temperatures. During full capacity operation of the incinerator, temperature measurements shall be made of the various internal and external metal portions of the unit. The temperature of any metal portion shall not be excessive to the point where deterioration of the metal can be expected (see 3.2.1). Surface temperatures shall be in conformance with the limitations specified (see 3.6).

4.4.6 Hours of operation and final examination. At the conclusion of the tests specified in 4.4.1 through 4.4.5 the incinerator shall continue to be operated, as necessary, so that a minimum total of 60 hours of continuous or intermittant operation at full rated capacity, is logged. The incinerator shall then be dismantled and all internal parts examined. The examination shall show that the test operation has had no deleterious effects on any of the incinerator parts.

4.4.7 Possible test failures. Possible test failures are defined as follows:

(a) Smoking test - Evidence of smoking from stack outlet.
(b) Sparking test - Evidence of sparks and embers emitting from stack outlet.
(c) Capacity test - Incinerator not capable of burning specified poundage of trash per hour or ash and residue collected in the ashpit in excess of 3 percent by mass of material burned.
(d) Temperature test:
    (1) Temperature of exposed surfaces of incinerator exceed allowable temperature limits (see 3.6).
    (2) Evidence of deterioration of metal parts due to excessive temperature.
(e) Hours of operation and final inspection test - Evidence of warping and deterioration of exposed parts; refractory and insulating brick loose or falling out.

5. PACKAGING

(The preparation for delivery requirements specified herein apply only for direct Government acquisitions. For the extent of applicability of the preparation for delivery requirements of referenced documents listed in section 2, see 6.8.)

5.1 Preservation-packaging level C.

5.1.1 Disassembly. When specified (see 3.3 and 6.2.1), incinerators furnished in a knocked down condition shall be disassembled the minimum necessary to safeguard parts vulnerable to damage, pilferage and loss. The extent of further disassembly shall be confined to the removal of protruding parts such as stacks and other components that would otherwise increase cubage; however, disassembly shall be limited to those parts that can be removed and reinstalled without special tools or skill. Removed hardware shall be reinstalled in mating parts and secured to prevent their loss. Removed parts and mating parts shall be match marked or tagged to facilitate reassembly. Matchmarks and printed tags shall be waterproofed.

Source: https://assist.dla.mil -- Downloaded: 202610-18T06:22Z
Check the source to verify that this is the current version before use.

5.1.2 Openings. Openings that will permit entrance of water shall be closed and sealed with water-resistant barrier materials, secured in place with water-resistant tape. Wood or fiberboard blanks may be used for large openings where barrier materials are subject to puncture.

5.1.3 Refractories.

5.1.3.1 Installed linings. Linings that remain installed in the basic units shall be protected with blocking and cushioning as necessary to prevent the linings from loosening.

5.1.3.2 Linings not installed. Refractory linings, including brick, block, and shapes required for installation shall be packaged in close-fitting wood or wood cleated plywood or wirebound boxes normally used by industry for shipping purposes. To prevent damage to the linings, linings shall be separated from other linings and the inside faces of the boxes by cushioning with sheets of corrugated fiberboard material. The gross weight of each box shall not exceed 500 pounds. Boxes exceeding 50 pounds shall be modified by the installation of 2 inch by 3 inch wood skids. The boxes shall be shipped without over-packing (see 5.2) at the same time as the basic unit for which intended.

5.1.4 Electrical equipment. Fans, motors, control boxes, or other electrical units shall be covered or wrapped with waterproof barrier material and secured with water-resistant tape. Exposed ends of wiring shall be sealed with water-resistant tape. Lengths of electric cable and wire shall be coiled to not less than 10 times their diameter and the coils secured with tape as specified herein.

5.2 Packing level C. Incinerators, preserved-packaged as specified in 5.1 shall be packed in a manner acceptable to the common carrier and which will insure safe delivery at destination in a satisfactory condition at the lowest applicable rate. Incinerators shall be furnished on wood skids to permit acceptance by standard handling equipment. Containers, packing, or method of shipment shall comply with Uniform Freight or National Motor Freight Classification Rules or Regulations or other carrier rules as applicable to the mode of transporation. Linings packaged in boxes as specified in 5.1.3.2 do not require overpacking for shipment.

5.3 Marking. Unless otherwise specified (see 6.2.1), interior (when provided) and exterior packs shall, as a minimum, be marked as follows by any means which provides legibility and durability:

(a) National Stock Number (NSN) or part number when NSN is not available.
(b) Noun nomenclature.
(c) Quantity and unit of issue.
(d) Contract, purchase order, or delivery order number.
(e) Additional markings as may be required by the contract.
(f) Exterior shipping containers shall be marked with the appropriate address and caution marking except for full carloads of full truckloads to a single Continental United States (CONUS) consignee.
(g) One copy of the shipping documents and contract or order documentation shall be attached to the outside in an envelope or placed inside the container.

6. NOTES

6.1 Intended use. Incinerators are intended for the disposition of combustible trash accumulated on board ships.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type required (see 1.2).
(c) Whether fans are required and, if required, the fan motor voltage (see 3.3, 3.5, and 5.1.1).
(d) If incinerator is supplied in assembled or knocked-down condition (see 3.3).
(e) Assembly arrangement required (see 3.9.1).
(f) Quality assurance requirements (see 4.2).
(g) Marking required (see 5.3).

Source: https://assist.dla.mil -- Downloaded: 202610-18T06:22Z
Check the source to verify that this is the currentversion before use.

6.2.2 Data requirements. When this specification is used in a contract which invokes the provision of the "Requirements for Data" of the Defense Acquisition Regulation (DAR), the data identified below, which are required to be developed by the contractor, as specified on an approved Data Item Description (DD Form 1664), and which are required to be delivered to be delivered to the Government, should be selected and specified on the approved Contract Data Requirement List (DD Form 1423) and incorporated in the contract. When the provisions of the "Requirements for Data" of the DAR are not invoked in a contract, the data required to be developed by the contractor and required to be delivered to the Government should be selected from the list below and specified in the contract.

Paragraph	Data requirements	Applicable DID	Option
3.15	Manual, technical, standard, basic issue	DI-M-2044	Type I of MIL-M-15071
3.16	Drawings, engineering and associated lists	DI-E-7031	Level 3 Design activity designation - By contractor Drawing No. - By contractor Delivery of hard copy - To contracting activity Drawing revisions - One print in accordance with type II, class 4 of MIL-D-5480

(Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.)

6.2.2.1 The data requirements of 6.2.2 and any task in section 3, 4, or 5 of the specification required to be performed to meet a data requirement may be waived by the contracting/acquisition activity upon certification by the offeror that identical data were submitted by the offeror and accepted by the Government under a previous contract for identical item acquired to this specification. This does not apply to specific data which may be required for each contract regardless of whether an identical item has been supplied previously (for example, test reports).

6.3 With respect to products requiring qualification, awards will be made only for products which are at the time set for opening of bids, qualified for inclusion in applicable Qualified Products List QPL-15650 whether or not such products have actually been so listed by that date. The attention of the contractors is called to this requirement, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. The activity responsible for the Qualified Products List is the Naval Sea Systems Command, SEA 3112, Department of the Navy, Washington, DC 20362, and information pertaining to qualification of products may be obtained from that activity. Application for Qualification tests shall be made in accordance with "Provisions Governing Qualification SD-6" (see 6.3.1).

6.3.1 Copies of "Provisions Governing Qualification SD-6" may be obtained upon application to Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

6.4 Sub-contracted material and parts. The preparation for delivery requirements of referenced documents listed in section 2 do not apply when material and parts are acquired by the contractor for incorporation into the equipment and lose their separate identity when the equipment is shipped.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Preparing activity:
Navy - SH
(Project 4540-N064)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:22Z
Check the source to verify that this is the current version before use.