INCH-POUND
MIL-L-15596G
AMENDMENT 1
31 January 1991

MILITARY SPECIFICATION

LOCKS, COMBINATION FOR GENERAL SERVICES ADMINISTRATION APPROVED SECURITY CONTAINERS, VAULT DOORS, AND SAFE LOCKERS

This amendment forms a part of MIL-L-15596G, dated 17 June 1988, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 6

3.3.1.1: Delete and substitute:

"3.3.1.1 Dissimilar metals. Dissimilar metals, as defined in MIL-STD-889, must either be plated or compatible to prevent operationally destructive corrosion."

PAGE 12

4.5.2.1: Delete and substitute:

"4.5.2.1 Security. The lock in the locked condition shall have the dial turned at 600 rpm for a break-in period of not less than 8 hours, turned 4 hours in clockwise and 4 hours in counterclockwise direction. After the break-in period, an attempt shall be made to manipulate the lock, including the use of commercially available electronic equipment. The lock shall resist manipulation for 20 man-hours. Forced entry shall be resisted for 10 minutes. The ending torque shall be checked when finished and before proceeding to 4.5.2.2 to determine conformance to 3.5. The lock shall be checked for normal functioning after the 8 hour break-in period."

4.5.2.5: Delete this paragraph in its entirety.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:20Z
Check the source to verify that this is the current version before use.

4.5.2.6.2: Delete and substitute:

"4.5.2.6.2 Aging-stress distortion. The synthetics shall not warp to the extent that the intended function is impaired when the material is aged for 7 days in a circulating-air oven conforming to ASTM D2436 with temperature maintained at 163.4°F (73°C). Exhaust ports of the oven shall be adjusted to achieve 200 or more complete fresh-air changes per hour. A substantial amount of fresh air is to be admitted continuously throughout the 7 day aging period. At least 6 representative samples shall be tested. Following the 7 day aging, the samples are removed, cooled at room temperature, and then checked for performance of the intended function by conducting the operation and wheel slippage test of 4.5.2.2 and 4.5.2.4."

Custodians:
Army - ME
Navy - YD
Air Force - 99

Review activities:
Army - AR, GL
DLA - IS

User activities:
Army - CE
Navy - MC SH

Preparing activity:
Navy - YD

(Project 5340-2036)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:20Z
Check the source to verify that this is the current version before use.