MILITARY SPECIFICATION

PANELS, SOUND POWERED TELEPHONE (TYPE IC/A)

1. SCOPE

1.1 Scope.- This specification covers sound powered telephone switchboard panels, panel tops and panel bases for use with the sound powered telephone system in Naval ships.

1.2 Classification.- The panels shall be of the following types as specified (see 6.1).

Type IC/A1 - (with 30 line cutout switches)
Type IC/A5 - (with 4 S1JR 5 switches)
Type IC/A10 - (with 4 S1JR 10 switches)

The panel tops and panel bases shall be of but one type as described hereinafter.

2. APPLICABLE SPECIFICATIONS, OTHER PUBLICATIONS AND DRAWINGS

2.1 Specifications.- The following specifications, of the issue in effect on the date of invitation for bids, forma part of this specification:

Military Specification
MIL-I-983 - Interior Communication Equipment; General Specification for.

Navy Department Specification
General Specifications for Inspection of Materials.

(Army.- Copies of specifications should be obtained from the procuring agency or as directed by that agency. Both the title and identifying number or symbol should be stipulated when requesting copies.)

(Navy.- Copies of Military and and Navy Department specifications may be obtained upon application to the Bureau of Supplies and Accounts, Navy Department, Washington 25, D.C., except that activities of the Armed Forces should make application to the Commanding Officer, Naval Supply Center, Norfolk 11, Va. Both the title and identifying number or symbol should be stipulated when requesting copies.

(Air Force.- Copies of Military specifications may be obtained upon application to the Commanding General, Air Materiel Command, Wright-Patterson Air Force Base, Dayton, Ohio. Both the title and identifying number or symbol should be stipulated when requesting copies.)

(Marine Corps.- Copies of Military specifications may be obtained upon application to the Quartermaster General, Headquarters U.S. Marine Corps, Navy Department, Washington 25, D. C. or the Depot Quartermaster, Marine Corps Depot of Supplies, 1100 South Broad Street, Philadelphia 46, Pa. Both the title and identifying number or symbol should be stipulated when requesting copies.)

Source: https://assist.dla.mil -- Downloaded: 202610-18T06:19Z
Check the source to verify that this is the current version before use.

2.2 Drawings.- The following drawing, of the issue in effect on date of invitation for bids, forms a part of this specification:

Bureau of Ships Drawing
9000-S6501-74012 - Sound Powered Telephone Panels, Panel Tops and Panel Bases-Type IC/A

(Copies of Bureau of Ships Drawings may be obtained only upon application to the Bureau of Ships, Navy Department, Washington 25, D. C. Both the title and the identifying number or symbol should be stipulated when requesting copies.)

3. REQUIREMENTS

3.1 Qualification.- The sound powered telephone panels, panel tops and panel bases furnished under this specification shall be of a brand which has been tested and successfully passed the qualification tests specified in section 4 (see 6.2).

3.2 General.- The panels, panel tops and panel bases, shall be in accordance with Drawing 9000-S6504-74012 and the requirements of Specification MIL-I-983 listed below in addition to the requirements outlined hereinafter. Whenever a requirement of Specification MIL-I-983 conflicts with a requirement of this specification, the requirement of this specification shall govern:

Materials, general
Stressed or vital parts
Unstressed or non vital parts
Wood
Magnesium
Aluminum
Brass and bronze
Iron and steel
Protection against corrosion
(salt spray test not required)
Plastics
Inflammable materials
Toxic compounds
Lubricants
Electrical parts, general
Fungus inert materials
Restriction of materials
Electric Tapes
Accessibility
Minimum sheet thickness
Through bolting
Cover bolts
Temperature and humidity
(storage requirements only)
Threaded parts
Locking devices
Washers
Interchangeability and standardization
Shock, Vibration and Inclination
(vital equipment)
Painting
Designation and marking
Design for production
Rounded corners and edges
Internal unit protection
Drilled and tapped holes
Welding
Clearances
Grounds
Soldering
Mounting of parts
Terminal strips, connectors and terminals
Wiring
Workmanship
General information

3.2.1 Contact Resistance.- The contact resistance of the line cutout switches shall not exceed 0.015 ohms when measured in accordance with 4.3.3.

3.2.2 Accelerated Life tests.- The sound powered telephone panels shall be capable of withstanding, without mechanical or electrical damage the accelerated life test described in 4.3.1.

Source: https://assist.dla.mil -- Downloaded: 202610-18T06:19Z
Check the source to verify that this is the current version before use.

4. SAMPLING, INSPECTION AND TEST PROCEDURES

4.1 Qualification tests at a Government laboratory.- Qualification tests shall be conducted at a Government laboratory designated by the Bureau of Ships. These tests shall consist of the tests specified in 4.3.1.

4.2 Sampling procedures and tests to be required.- The sampling procedures for the various tests to be performed on the equipment shall be as follows · (The attention of the manufacturer is invited to the paragraphs of Specification MIL-I-983 covering general information on these tests such as cost, where conducted, failures, test conditions etc.):

4.2.1 Qualification.- One panel of each type covered in this specification shall be subjected to the qualification tests listed below. These tests shall be performed, in general, in the order listed.

Test	Requirement Paragraph	Test Procedure
General Inspection	3.2	(see 4.3.4)
Temperature	3.2	(see 4.3.2)
Dielectric Strength	3.2	(see Specification MIL-I-983)
Insulation Resistance	3.2	(see Specification MIL-I-983)
Accelerated Life Test	3.2.2	(see 4.3.1)
Contact resistance	3.2.1	(see 4.3.3)
Vibration (for vital equipment)	3.2	(see Specification MIL-I-983)
Shock	3.2	(see Specification MIL-I-983)

4.2.2 Contract suitability.- One panel from each production run of each type covered on the contract or order shall be subjected to the contract suitability tests described below. These tests shall be performed, in general, in the order listed.

Test	Requirement Paragraph	Test Procedure
General Inspection	3.2	(see 4.3.4)
Temperature	3.2	(see 4.3.2)
Dielectric Strength	3.2	(see Specification MIL-I-983)
Insulation Resistance	3.2	(see Specification MIL-I-983)
Accelerated Life Test	3.2.2	(see 4.3.1)
Contact Resistance	3.2.1	(see 4.3.3)
Vibration (for vital equipment)	3.2	(see Specification MIL-I-983)
Shock	3.2	(see Specification MIL-I-983)

4.2.3 Inspection tests at place of manufacture.- All panels covered in the contract or order shall be subjected to the inspection tests at the place of manufacture described below. These tests shall be performed, in general, in the order listed.

Test	Requirement Paragraph	Test Procedure
General Inspection	3.2	(see 4.3.4)
Dielectric Strength	3.2	(see Specification MIL-I-983)
Insulation Resistance	3.2	(see Specification MIL-I-983)
Contact Resistance	3.2	(see 4.3.3)

4.3 Test Procedures -

4.3.1 Accelerated Life Test -

4.3.1.1 The panel doors shall be opened and closed 100 times.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:19Z
Check the source to verify that this is the current version before use.

4.3.1.2 Two line cutout switches on the panel type IC/A1 shall be subjected to 10,000 make and break cycles at a rate not greater than 30 cycles per minute. The contact resistance shall be measured at the end of this test.

4.3.2 Temperature cycling.- The panels shall be subjected to the temperature cycle outlined in Specification MIL-I-983 except for the measurement of temperature rise.

4.3.3 Contact Resistance.- The contact resistance through a stationary contact and a moving contact that form part of the same circuit, shall be measured with an ohm meter with a 1.5 volt supply. The Government inspector shall select sample contacts in accordance with table I.

Table I - Sampling for Inspection

Lot quantity number of contacts	Sample number of contacts
	8
10 to 25	12
26 to 50	18
51 to 100	24
101 to 200	32
201 to 300	40
301 to 500	50
501 to 800	60
801 to 1300	90
1301 to 3200	150
3201 to 8000	

4.3.4 General Inspection.- The general inspection shall be conducted in accordance with Specification MIL-I-983. No operating test is required.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing and marking.- Each sound powered telephone panel, panel top, panel base shall be preserved, packaged, packed and marked in accordance with Specification MIL-I-983. Domestic or overseas shipment shall be as specified (see 6.1).

6. NOTES

6.1 Ordering data.- Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Type of panels required (see 1.2)
(c) Whether the subject commodity is to be prepared for domestic or overseas shipment (see 5.1).

6.2 In the procurement of products requiring qualification the right is reserved to reject bids on products that have not been subjected to the required tests and found satisfactory for inclusion on the Navy Qualified Products List. The attention of suppliers is called to this requirement, and manufacturers are urged to communicate with the Bureau of Ships, Navy Department, Washington 25, D. C., and arrange to have the products that they propose to offer to the Armed Services, tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products covered by this specification may be obtained from the Chief of the Bureau of Ships, Navy Department, Washington 25, D. C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:19Z
Check the source to verify that this is the current version before use.

Notice.- When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:19Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD, FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE C-8979

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:19Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDER
NAVAL SHIP ENGINEERING CENTER
ATTN: CODE 6604.3B
WASHINGTON, D.C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:19Z
Check the source to verify that this is the current version before use.