MIL-STD-1329C

15 July 1988

SUPERSEDING
MIL-STD-1329B
30 JUN 1976

MILITARY STANDARD

SWITCHES, RF COAXIAL, SELECTION OF

AMSC N/A

FSC 5985

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF DEFENSE
Washington, DC 20301

Switches, RF Coaxial, Selection of

1. This military standard is approved for use by all Departments and Agencies of the Department of Defense.

2. Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Space and Naval Warfare Systems Command, ATTN: SPAWAR 003-121, Department of the Navy, Washington, DC 20363-5100, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

CONTENTS

			Page
Paragraph	1.	SCOPE	1
	1.1	Scope	1
	1.2	Purpose	1
	2.	REFERENCED DOCUMENTS	1
	2.1	Government documents	1
	2.1.1	Specifications	1
	3.	DEFINITIONS	1
	4.	GENERAL REQUIREMENTS	1
	4.1	Selection of coaxial switches	1
	4.2	Criteria for selection	1
	4.3	Application and use	1
	4.4	Detailed requirements for coaxial switches	2
	5.	DETAILED REQUIREMENTS	2
	6.	NOTES	2
	6.1	Changes from previous issue	2
Table	I.	Standard coaxial switches with series N connectors	2
	II.	Standard coaxial switches with series BNC connectors	3
	III.	Standard coaxial switches with series SMA connectors	3
	IV.	Standard coaxial switches with series TNC connectors	4
	V.	Cross-reference of type to part number	4

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Scope. This standard provides a list of standard coaxial switches for use in military applications.

1.2 Purpose. The purpose of this standard is to:

a. Provide the equipment designer with a list of coaxial switches considered standard for military applications.

b. Restrict the number of coaxial switch types used in military equipment in order to provide effective logistic support of field equipment.

c. Establish criteria pertinent to choice, application, and use of coaxial switches in military equipment.

2. REFERENCED DOCUMENTS

2.1 Government documents.

2.1.1 Specifications. The following specifications form a part of this standard to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-S-3928 - Switches, Radio Frequency Transmission Line (Coaxial), General Specification For.
MIL-S-24067 - Switches, Coaxial, Radio Frequency Transmission Line, (For Use With Electronic Countermeasures Equipment), General Specification.
MIL-S-25879 - Switch, Radio Frequency Transmission Line SA-521A/A.

(Copies of the specifications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

3. DEFINITIONS

3.1 The terms used in this standard are commonly encountered in coaxial switch engineering practice.

4. GENERAL REQUIREMENTS

4.1 Selection of coaxial switches. Coaxial switches to be used in military applications shall be selected from those listed in tables I through IV. Cross-reference of type to part number is shown in table V.

4.2 Criteria for selection. The criteria for the selection of coaxial switches for inclusion in this standard are:

a. The coaxial switches shall be considered by representatives of the Military Departments the best available type for current application.

b. Availability of the coaxial switches shall be reasonably certain.

c. The coaxial switches shall have an approved military specification.

4.3 Application and use. Coaxial switches used in military applications shall be representative of manufactured lots possessing acceptable material and physical and electrical characteristics and shall in no manner degrade the operational characteristics of the equipment in which used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

4.4 Detailed requirements for coaxial switches. The detailed requirements for coaxial switches listed in this standard are covered by the applicable MIL-S-3928 or MIL-S-24067 specification sheets, or MIL-S-25879.

5. DETAILED REQUIREMENTS Not applicable.

6. NOTES

6.1 Changes from previous issue. Vertical lines or asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

TABLE I. Standard coaxial switches with series N connectors.

Part number	Configuration	Type actuator	Operating voltage (nominal)	Position indicating circuit	Type actuator connector
M3928/7-02	1P2T	Manual	---	None	---
M3928/7-06	1P6T	Manual	---	None	---
M3928/7-09	1P2T	Solenoid	110 dc	None	6-32NC-2A
M3928/7-11	1P3T	Solenoid	110 dc	None	MS3456-14S-2S 1/
M3928/7-12	1P3T	Manual	---	None	---
M3928/7-14	1P2T	Manual	---	None	---
M3928/7-15	1P6T	Manual	---	None	---
M3928/7-16	1P4T	Manual	---	None	---
M3928/7-17	1P2T	Solenoid	26 dc	None	6-32NC-2A
M3928/7-18	1P2T	Solenoid	26 dc	None	6-32NC-2A
M3928/7-19	1P2T	Solenoid	110 dc	None	6-32NC-2A
M3928/7-20	1P2T	Solenoid	28 dc	None	6-32NC-2A
M3928/7-22	1P4T	Manual	---	None	---
M3928/7-24	1P4T	Solenoid	28 dc	None	6-32NC-2A
M3928/7-25	TR	Solenoid	28 dc	None	MS83723--13R1006N
M3928/7-26	TR	Solenoid	28 dc	None	MS83723-13R1006N
M3928/9-04	2P2T	Manual	---	None	---
M3928/9-05	1P2T	Manual	---	None	---
M3928/9-13	TR	Manual	---	None	---
M3928/9-14	1P3T	Manual	---	None	---
M3928/9-15	1P6T	Manual	---	None	---
M3928/9-17	TR	Motor	28 dc	Yes	MS3452W-12-10S 1/
M3928/10-01	1P2T	Solenoid	110 dc	None	Solder terminals
M3928/10-02	1P2T	Solenoid	28 dc	None	Solder terminals
M3928/10-03	1P2T	Solenoid	115 dc	None	Solder terminals
M3928/10-04	1P2T	Solenoid	28 dc	None	Solder terminals
M3928/10-05	1P2T	Solenoid	28 dc	Yes	Solder terminals
M3928/10-06	1P2T	Solenoid	28 dc	None	MS27484T8-F98S 1/
M3928/10-07	TR	Solenoid	28 dc	None	MS27484T8-F98S 1/
M3928/10-08	TR	Solenoid	28 dc	Yes	MS3113H10-6P
M3928/10-11	TR	Solenoid	28 dc	None	---
M3928/10-12	1P2T	Solenoid	28 dc		Solder terminals
M24067/1-001	1P2T	Solenoid	28 dc	Yes	MS3102R-14S-6P
2-001 (MIL-S-25849)	2P2T	Solenoid	28 dc	Yes	MS3102R-14S-5P
SA-521A/A	1P2T	Solenoid	28 V dc	None	MS3106-10SL-3S 1/

1/ Mates with.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

TABLE II. Standard coaxial switches with series BNC connectors.

Part number M3928/	Configuration	Type actuator	Operating voltage (nominal)	Position indicating circuit	Type actuator connector
7-10	1P2T	Solenoid	26 dc	None	6-32NC-2A
7-13	1P6T	Manual	---	None	---
7-23	1P2T	Solenoid	115 ac	None	6-32NC-2A
8-01	TR	Solenoid	28 dc	None	Solder terminals
8-03	1P2T	Solenoid	28 dc	None	Solder terminals
8-05	1P2T	Solenoid	115 ac	None	Solder terminals
8-07	1P2T	Solenoid	110 dc	None	Solder terminals
8-18	1P2T	Solenoid	28 dc	None	Solder terminals
8-19	1P2T	Solenoid	28 dc	None	Solder terminals
8-20	1P2T	Solenoid	28 dc	None	Solder terminals
8-21	1P6T	Manual	---	None	---
8-22	1P4T	Solenoid	28 dc	None	---

TABLE III. Standard coaxial switches with series SMA connectors.

Part number M3928/	Configuration	Type actuator	Operating voltage (nominal)	Position indicating circuit	Type actuator connector
15-01	1P2T	Solenoid	28 dc	None	Solder terminals
15-02	1P2T	Solenoid	28 dc	None	Solder terminals
15-03	1P2T	Solenoid	28 dc	None	Solder terminals
15-04	1P2T	Solenoid	28 dc	Yes	Solder terminals
15-05	1P2T	Solenoid	28 dc	Yes	Solder terminals
15-07	1P2T	Solenoid	28 dc	None	Solder terminals
15-08	1P2T	Solenoid	28 dc	Yes	Solder terminals
16-01	1P3T	Solenoid	28 dc	Yes	MS3114E-12-10P
17-01	1P4T	Solenoid	28 dc	Yes	M8372311-H1210N
17-02	1P4T	Solenoid	28 dc	None	RTK07-8-7P (Deutch) or equivalent
17-03	1P4T	Solenoid	28 dc	None	Solder terminals
18-01	1P6T	Solenoid	28 dc	None	RTK07-8-7P (Deutch) or equivalent
18-02	1P6T	Solenoid	28 dc	None	Solder terminals
18-03	1P6T	Solenoid	28 dc	None	Solder terminals
18-04	1P6T	Solenoid	28 dc	None	Solder terminals
18-05	1P6T	Solenoid	28 dc	None	MS3112E-14-18PN
18-06	1P6T	Solenoid	28 dc	Yes	MS3112E-14-15P
18-07	1P6T	Solenoid	28 dc	Yes	Solder terminals
18-08	1P6T	Solenoid	28 dc	None	Solder terminals
19-02	TR	Solenoid	28 dc	None	Solder terminals
19-03	TR	Solenoid	28 dc	Yes	Solder terminals
19-04	TR	Solenoid	28 dc	None	Solder terminals
19-05	TR	Solenoid	28 dc	Yes	Solder terminals
19-06	TR	Solenoid	115 ac	Yes	MS3113H10-6P
25-01	1P5T	Solenoid	26 dc	None	Solder terminals

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

TABLE IV. Standard coaxial switches with series TNC connectors.

Part number M3928/	Configuration	Type actuator	Operating voltage (nominal)	Position indicating circuit	Type actuator connectors
12-01	1P2T	Solenoid	28 dc	Yes	MS27478-Y8D6P
13-01 1/	1P2T	Solenoid	28 dc	Yes	Solder terminals
14-01	TR	Solenoid	28 dc	Yes	MS27466-T9B6P
20-02	1P2T	Solenoid	28 dc	None	Solder terminals
20-03	1P2T	Solenoid	28 dc	None	MS3113-8-2P
20-04	1P2T	Solenoid	28 dc	Yes	Solder terminals
20-05	1P2T	Solenoid	28 dc	Yes	Solder terminals
20-06	1P2T	Solenoid	28 dc	None	MS3116E-8-3S 2/
20-07	1P2T	Solenoid	28 dc	None	Solder terminals
20-08	1P2T	Solenoid	28 dc	Yes	Solder terminals
21-01	TR	Solenoid	28 dc	Yes	Solder terminals
21-02	TR	Solenoid	28 dc	Yes	Solder terminals
21-03	TR	Solenoid	28 dc	Yes	Solder terminals
23-01	2P2T	Solenoid	28 dc	None	Solder terminals

1/ Center connector (common) is series SC.

2/ Mates with.

TABLE V. Cross-reference of type to part number.

Part number M3928/	Type SA-( )/U	Part number M3928/	Type SA-( )/U
7-09	1328	8-03	1350
7-10	1329	8-05	1352
7-11	1330	8-07	1354
7-12	1331	9-13	1345
7-13	1332	9-14	1346
7-14	273	9-15	1347
7-15	275	10-01	1360
7-16	274	10-02	1361
8-01	1348	10-03	1362

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Navy - EC
Army - ER
Air Force - 85

Review activities:
Army - MI
Navy - SH
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AV
Navy - AS, CG, MC, OS
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5985-1018)

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

Defense Electronics Supply Center
Dayton, OH 45444-5000

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 Alexandria, VA

POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Commander
Defense Electronics Supply Center
ATTN: DESC-ES
1507 Wilmington Pike
Dayton, OH 45444-5276

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-STD-1329C	SWITCHES, RF COAXIAL, SELECTION OF

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.