MILITARY SPECIFICATION

HEAD ASSEMBLY, TANK PERISCOPE: 10513392

This amendment forms a part of Military Specification MIL-H-60153(MU) dated 10 February 1965.

Paragraph 3.8: Delete paragraph and substitute:

"3.8 Resolution.- Resolution shall be 9.0 seconds of arc or less when observing with a telescope of at least 50 power. The entrance pupil of the telescope shall be not less than 7.0 inches. Resolution shall be observed at one focus setting of the telescope."

Paragraphs 3.9 and 3.10: Delete paragraphs.

Paragraph 4.2.2, Table I: Delete characteristics 112 and 113.

Paragraph 4.3.2: Delete paragraph and substitute the following:

"4.3.2 Environmental.- Three head assemblies shall be selected at random as samples from each 50 produced, or from each month's production, whichever occurs first. The samples shall not be selected from those which have previously been vibrated in Table I. They shall be subjected to the following sequence of tests to determine compliance with their respective requirements:

	CONTROL TESTS	REQUIREMENTS	TEST PROCEDURES
303.	Storage temperatures (-80° and $+160^{\circ}F$)	3.3.1	4.5.1
304.	Operating temperatures (-40° and $+150^{\circ}F$)	3.3.2	4.5.2
305.	Vibration* (60° to $90^{\circ}F$)	3.4	4.5.4

*Subsequent to being vibrated the head assembly shall be subjected to the tests of 4.5.5 to 4.5.13 inclusive to determine overall compliance with 3.4.

Paragraph 4.5.9, last sentence: Delete and substitute "Resolution shall be within the value specified in 3.8 as determined by observing through the exit aperture of Window 8215997 with auxiliary telescope."

Paragraphs 4.5.10 and 4.5.11: Delete paragraphs.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A454Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:12Z
Check the source to verify that this is the current version before use.