MIL-C-46982B(AR)
AMENDMENT 2
19 November 1982
SUPERSEDING
AMENDMENT 1
22 September 1981

MILITARY SPECIFICATION

CARTRIDGE, 4.2 INCH, HE M329A1
W/SUPPLEMENTARY CHARGE, W/FUZE
PD, M557, LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-C-46982B(MU), dated 10 January 1969, and is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Add the following preamble underneath the title:

"This specification is approved by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense."

PAGE 4

3.3.2: Delete the second sentence in its entirety and substitute the following:

"Cavities in the base of the fuze well shall not be cause for rejection provided the sum of the areas of the cavities is not greater than 80 percent of the area of the fuze well base and no individual point extends more than 1/4 inch below the maximum depth of fuze well permitted by the drawing, and provided no point extends above the flat surface on which the liner would rest."

3.4.1.3.2, Table II, under "Max Lot Standard Deviation": Delete "26" and substitute "30".

PAGE 5

3.4.2: Add the following after the last sentence:

"Separation of the cartridge container extension outside the gun bore is not considered a safety hazard."

FSC 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:28Z
Check the source to verify that this is the current version before use.

PAGE 8

4.2.2.1: Add critical defect 2 as follows:

"2. Unsolidified pool of paint in bottom of shell cavity ... Visual 01004."

4.2.2.2:

Critical: Delete "None defined" and substitute the following:

"1. Liners external surface not coated 360 degrees for entire length with silicone soft film ... Visual 02008."

Delete Minor defect in its entirety.

4.2.2.3, Categories:

Critical: Delete "None defined: and substitute the following:

"1. Liner missing ... Visual 03008."

Major defect 101: Delete Code No. "03005" and substitute Code No. "03007."

Minor defect 201: Delete in its entirety.

Minor defect 202: Delete "missing or."

PAGE 10

4.2.2.5: Add Minor defect 203 as follows:

"203. Supplementary charge spacer missing (if loading unfuzed cartridges) ... Visual 05005."

PAGE 15

Add new paragraph 4.2.3.3.2 as follows:

"4.2.3.3.2, Caked explosive in threads - Minor defect, Code No. 02009. The sampling plan for this defect shall be a CSP-2 plan in accordance with MIL-STD-1235 with an AQL of 0.65 percent, inspection level II. The projectile shall be inspected visually for this defect prior to assembly of the liner."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:28Z
Check the source to verify that this is the current version before use.

Add new paragraph 4.2.3.3.3 as follows:

"4.2.3.3.3, Liner removable by hand - Minor defect, Code No. 03001. The sampling plan for this defect shall be a CSP-2 plan in accordance with MIL-STD-1235 with AQL of 0.65 percent, inspection level II. The projectile shall be inspected manually for this defect."

PAGE 18

4.3.2, Proving Ground Test: Add the following statement:

"See Acceptance Test Procedure CR-VAR, Artillery Complete Rounds, dtd 2 August 1965 and Suppl. CR-4.2 M-1, Cartridge 4.2 Inch, HE, M329A1 with Fuze, PD, M557 and Cartridge, 4.2 Inch, Smoke, WP, M328A1, with Fuze, PD, M521, dtd 15 August 1968."

* Add the following sentence:

"The mortar tube at the beginning of the test shall have fired less than 4,000 rounds."

4.3.2.1:

Line 1: Delete the first sentence and substitute the following:

"The cartridges for this test shall be divided into two equal groups with the fuzes set superquick."

Line 8: Add the following statement after "standard.":

"Rounds shall be at a temperature of $70^{o}F \pm 5^{o}F$ when fired. Sufficient warmer rounds shall be fired to attain the approximate gun tube temperature that will be maintained during the entire firing. A steady rate of fire shall be maintained throughout any series of firings; if for any reason there is a break in the firing of any series, sufficient warmer rounds shall be fired to attain the original approximate gun tube temperature before firing is resumed."

4.3.2.3: Delete "Refiring" and substitute "Test Validity."

PAGE 22

Add new paragraph 6.9 as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:28Z
Check the source to verify that this is the current version before use.

"6.9 Proving Ground Test Summary

Test	First 3 consecutive Lot Samples	Subsequent Lot Samples
Security Acceptance criteria see 4.2.3.5.2 observation for	20 Mpts breakup, prematures (photographic coverage)	13
Functioning	Chg 7 40 Chg 41 40	25 25
Acceptance criteria see 4.2.3.5.1 observation for	Misfires, Rng Std Dev, short rds less than 80% average range, duds, MPTS breakup, premature."	

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-A532)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:28Z
Check the source to verify that this is the current version before use.