MIL-C-46995C (AR)
AMENDMENT 1
24 August 1981

MILITARY SPECIFICATION

CARTRIDGE, 81MM, HE, M374
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIl-C-46995C (MU), dated 4 April 1969.

PAGE 1

Add the following preamble underneath the title:

"This specification is approved by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense."

Delete "M374" and substitute "M374A1 and M374A2" wherever the M374 designation appears in the specification.

Delete "8881026" and substitute "8881026 and 9240950" wherever it appears in the specification.

Delete "M71A1E1" and substitute "M71A2" wherever the M71A1E1 designation appears in the specification.

PAGE 5

3.7, line 2: Delete "Shall not break upon application of ten pounds minimum load but shall break upon application of twenty-five pounds maximum load" and substitute "shall not break upon application of ten pounds minimum load but shall break upon application of forty pounds maximum load."

PAGE 8

4.2.2.2, Major Defect 101: Delete in its entirety.

PAGE 10

4.2.2.6: Add new Major Defect 104 as follows:

"104. Shell, increments bind on inside diameter of container... Visual/Manual 06004."

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No: 1315-A445

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:31Z
Check the source to verify that this is the current version before use.