MILITARY SPECIFICATION

DETONATOR, STAB, M19A2
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-D-46462B (MU), dated 22 March 1965.

PAGE 5

4.2.1b: Delete and substitute as follows: "4.2.1b Lead azide of the same type from not more than two lots produced by the same manufacturer in accordance with the same spcecification and same specification revision and which have subsequently been subjected to uniformly controlled drying and operating conditions at the loading plant."

PAGE 8

4.2.3.4.1: Delete and substitute as follows: "4.2.3.4.1 Sensitivity (see 3.5.1) - Major defect - Code No. 02009. - A sample of three hundred and fifteen (315) detonators shall be randomly selected from each lot. If three (3) or more detonators fail to comply with the specified requirements, the lot shall be rejected. If one or two defectives occur, a second sample of 315 detonators shall be selected and tested. If, in the combined first and second sample, a total of four (4) or more defectives occur, the lot shall be rejected. The test shall be performed as specified in 4.3.4.1, using test equipment as specified in 4.2.4."

Custodian:
Army - AR

Preparing Activity:
Army - AR

Project No: 1375-A199

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:01Z
Check the source to verify that this is the current version before use.