MIL-I-46437B
20 May 1970
SUPERSEDING
MIL-I-0046437A(MU)
26 May 1969
MIL-I-46437
30 October 1961

MILITARY SPECIFICATION

IGNITER, DOCUMENT DESTROYER,

INCENDIARY, M25

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of igniter.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

QQ-S-781	-	Steel Strapping, Flat.
TT-W-572	-	Wood Preservative, Water Repellent.
PPP-B-601	-	Box, Wood, Cleated-Plywood.
PPP-B-621	-	Box, Wood, Nailed and Lock-Corner.
PPP-B-636	-	Box, Fiberboard.
PPP-C-843	-	Cushioning, Material, Cellulosic.
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes.
PPP-P-291	-	Paperboard, Wrapping, Cushioning.

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-B-2427 - Boxes, Ammunition Packing, Wood, Nailed.
MIL-B-46506 - Boxes, Ammunition Packing, Wood, Wirebound.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1168 - Lot Numbering of Ammunition.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

DL4-6-123 - Igniter, Document Destroyer, Incendiary, M25.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL4-6-123 or on the subsidiary drawings shall conform to the specifications listed thereon or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the igniter shall conform to the specifications and drawings listed on Drawing DL4-6-123 and subsidiary drawings.

3.2 Assembly. The igniter shall be assembled in accordance with Drawing C4-6-123 (see 6.3).

3.2.1 Incendiary mixture. The igniter body shall be filled with 23 + 2 grams of incendiary mixture conforming to Drawing B143-13-4 (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

3.2.2 Matchhead mixture. The matchhead mixture conforming to Drawing B143-11-1 shall be mixed with water to form a plastic mix. While in the plastic state, approximately 3-1/2 grams of the mixture shall be spread on the partition in layer form in the shallow portion of the body (Drawing C4-1-8) and the disk (Drawing A4-1-7) pressed on top of the mixture to extrude the plastic mixture through the 3/8 inch diameter hole to form a button above the matchhead disc and two crescent shaped extrusions at the sides while leaving a layer of the mixture of substantially the same thickness below the disc. The completed matchhead assembly shall be dried to a constant weight. (See 6.3.)

3.3 Igniter adapter. The six holes in the adapter, Drawing B4-6-124, shall remain clear and unobstructed, except for the tape specified on Drawing C4-6-123.

3.4 First fire pellets. The pellets made from the mixture conforming to Drawing B143-9-2 shall weigh 0.72 to 0.79 grams and shall be consolidated at a pressure of 30,000 ± 1000 pounds per square inch (see 6.3).

3.5 Leakage. The incendiary mixture shall not leak from the body assembly when tested as specified in 4.4.4.1.

3.6 Functioning. The igniter, excluding the metal parts, shall completely burn when tested as specified in 4.4.4.2.

3.7 Preproduction. Prior to the start of regular production, a preproduction lot of igniters shall be produced in accordance with this specification for examination and tests (see 4.3).

3.8 Workmanship. The igniter shall be free of foreign matter (oil, grease or dirt) and damage such as cracks, dents, or deformation which could affect its intended use.

4. QUALITY ASSURNACE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections.

(a) Preproduction inspection (see 4.3)

(b) Quality conformance inspection (see 4.4)

4.3 Preproduction inspection.

4.3.1 Lot. A preproduction lot of 200 igniters shall be manufactured using the same methods, materials, equipment and processes as will be used during regular production.

4.3.2 Sampling.

4.3.2.1 For examination and nondestructive test. The preproduction lot shall be randomly sampled in accordance with table I. The sampling of body assemblies for the leakage test (4.4.4.1) shall be done prior to the application of the matchhead mixture.

4.3.2.2 For destructive test. The preproduction lot shall be randomly sampled in accordance with table I.

4.3.3 Inspection procedure.

4.3.3.1 For examination and nondestructive test. Inspection shall be performed in accordance with table I.

4.3.3.2 For destructive test. Inspection shall be performed in accordance with table I.

Table I. Sampling, inspection and acceptance/rejection criteria

Sample	Requirement	Inspection	Accept	Reject
*30	------	4.4.3.3	0	1
60	3.5	4.4.4.1	0	1
*30	3.6	4.4.4.2	0	1

*Igniters complying with 4.4.3.3 shall be tested in accordance with 4.4.4.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

4.3.4 Acceptance/rejection criteria. The preproduction lot of igniters shall comply with table I to be acceptable. The supplier shall obtain written approval from the contracting officer prior to proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. Each lot shall be identified and controlled in accordance with MIL-STD-1168. No more than one lot of fuzes shall be represented in any one lot of igniters.

4.4.2 Sampling.

4.4.2.1 For examination and nondestructive test.

(a) Classification of defects. Sampling shall be conducted in accordance with MIL-STD-105.

(b) Leakage. Thirty body assemblies shall be taken at random from each lot subsequent to sealing of the incendiary mixture chamber but prior to the application of the matchhead mixture.

4.4.2.2 For destructive test. Thirty igniters shall be taken at random from each lot.

4.4.3 Inspection procedure.

4.4.3.1 For examination and nondestructive test.

(a) Classification of defects. The sample igniters and the level A preparation for delivery shall be examined in accordance with the classification of defects and MIL-STD-105.

(b) Leakage. The sample body assemblies shall be tested in accordance with 4.4.4.1. The acceptance number is zero.

4.4.3.2 For destructive test. The sample igniters shall be tested in accordance with 4.4.4.2. The acceptance number is zero.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

4.4.3.3 Classification of defects.

(a) Igniter, document destroyer, incendiary, M25 (Drawing C4-6-123).

Categories		Defects
Critical:		
1		Safety pin not spread
Major:	AQL	1.0 percent defective
101		Component missing or incorrectly assembled
102		Adapter holes open
103		Gasket missing or inadequate
104		Cement missing
105		Marking missing or illegible
106		Fuze torque incorrect
107		Workmanship (3.8)

(b) Preparation for delivery (section 5).

Categories		Defects
Critical:		None defined
Major:	AQL	4.0 percent defective
101		Packaging incorrect
102		Container incorrect
103		Contents loose
104		Closure incorrect
105		Quantity incorrect
106		Container or package damaged (torn, punctured, crushed or wracked)
107		Marking missing or illegible
*108		Safety pin spread incorrect
*109		Pull ring location incorrect

*Check prior to closing can (Drawing C4-6-125).

4.4.4 Tests. Tests shall be conducted as follows:

4.4.4.1 Leakage. Place the filled body in an oven in a horizontal position for a period of 4 + 1/2 hours at a temperature of 150° + 5° F. At the end of this period, visually inspect the assembly for evidence of leakage (see 6.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

4.4.4.2 Functioning. Submerge the igniter in water, having a temperature of 0° to 10° F above the temperature of the igniter, to a minimum depth of 6 inches for 30 + 5 minutes. At the end of the soak period, the igniter shall be dried by wiping and functioned within 1 hour. Remove the tape, grasp the igniter so that the handle is secured in the palm of one hand and pull the safety pin with other hand. Place igniter on a clay or ceramic surface, protected from drafts, and release handle.

5. PREPARATION FOR DELIVERY

5.1 Packaging, level A. The igniter shall be wrapped in cushioning material conforming to PPP-C-843 and single faced paperboard, type III, style 1 of PPP-P-291. The igniter shall then be placed in a full tear-out top can in accordance with Drawing C4-6-125 and closed and sealed in accordance with the can specification. (See 6.4.)

5.2 Packing. Level shall be as specified (see 6.2).

5.2.1 Level A. Eighty igniters, packaged as specified in 5.1, shall be packed in two tiers, each tier having five rows of eight igniters each, in a PPP-B-601, overseas type, style I or J, PPP-B-621, class 2, style 4 or 4-1/2; of MIL-B-46506, type I, class 2, shipping container. The interior dimensions of the container shall be approximately 28-1/8 by 17-1/8 by 12-3/8 inches. Interlocking fiberboard partitions fabricated from grade W5c of PPP-F-320, 6 inches in height, and having 40 cells each measuring 3-3/8 inches across the openings, shall be used to separate the igniters in each tier. Fiberboard separators, fabricated from the same material as the interlocking partitions, shall separate the load from the shipping container and each tier. Closure of the container shall conform to the requirements specified in the appendix to the applicable box specification, using strapping conforming to type 1 or 4, class B, of QQ-S-781. The shipping container and all wood parts thereof shall be fully immersed for a minimum of 3 minutes, in a water repellent, wood preservative, conforming to Composition A of TT-W-572. Prior to packing the igniters in the treated shipping container, the preservative shall be dry as evidenced by the wood preservative test specified in MIL-B-2427.

5.2.2 Level C. Eighty igniters, packaged as specified in 5.1, shall be packed as specified in 5.2.1, except the shipping container shall conform to style FOL-L, grade W5c of PPP-B-636. Closure of the container shall conform to the requirements in the appendix to PPP-B-636.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages shall be marked in accordance with MIL-STD-129. The shipping containers shall be marked in accordance with Drawing D4-6-127. Sufficient drying time shall be allowed after application of the wood preservative to insure that all marking shall be clear, legible and permanent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

5.4 Palletization. Unless otherwise specified in the contract or order, shipping containers shall be palletized in accordance with Drawing D4-6-126.

6. NOTES

6.1 Intended use. This item is intended as an ignition element for the M3 document destroyer.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Level of packing required.
(c) Preproduction.

(1) Time allowed for supplier submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the supplier whether or not to proceed with production.

6.3 Caution. Suppliers are hereby notified to take all necessary precaution to protect personnel while loading, assembling and testing igniters due to the hazard of fire and explosion.

6.4 Packaging. The following procedure has been found to satisfactorily package the igniter: Wrap the igniter as centered in width of item 1(Drawing C4-6-125) by rolling lengthwise, then roll successively in each of the two 12-inch paperboard strips separated approximately 1/4 inch end-from-end and with corregations lengthwise of igniter and facing inward. Roll pack tightly enough to slip freely into can. Assemble lid and plastic protective cover.

6.5 Leakage. Leakage may be determined more readily when the sample ignites are placed, with adequate spacing, on a layer of absorbent paper (blotting paper or paper towel) and gently weighted to hold them in contact with the absorbing paper.

Custodians:

Army - MU
Navy - OS
Air Force - 70

Preparing activity:

Army - MU(EA)

Project No. 1375-1008

Review activities:

Navy - OS
Air Force - 70

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.