MIL-C-26805G(USAF)
AMENDMENT 2
10 March 1982

SUPERSEDING
AMENDMENT 1
10 September 1975

MILITARY SPECIFICATION

COMPRESSOR UNITS, AIR/GAS, GENERAL REQUIREMENTS FOR

This amendment forms a part of Military Specification MIL-C-26805G(USAF) dated 10 September 1975, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2: Under Type III, Class 1 delete "Gasoline engine" and substitute "Diesel engine".

PAGE 2

Under SPECIFICATIONS, Federal add; "GG-G-76-Gage, Pressure and Vacuum, Dial Indicating (for Air, Steam, Water, Ammonia, Chloro-fluoro Hydrogen Gases, and Compressed Gases)".

add; "TT-C-490-Cleaning Method and Pretreatment of Ferrous Surfaces for Organic Coatings".

Under Military add; "MIL-T-5624 Turbine fuel, Aviation, Grades JP-4 and and JP-5".

Delete "MIL-G-8402 - Gages, Pressure, Dial Indicating, General Specification for

Delete "MIL-H-8795 - Hose Assemblies, Rubber, Hydraulic, Fuel and Oil Resistant"

Delete "MIL-E-11275 - Engines, Gasoline, Industrial Type, General Specification for".

PAGE 3

Delete "MIL-E-11276 - Engines, Diesel, Industrial, Medium and High Speed, General Specification for".

Add: "MIL-P-23377 - Primer Coating, Epoxy Polyamide, Chemical and Solvent Resistant."

Add: "MIL-H-38390 - Hose Assembly, Tetraflouroethylene, Pneumatic, High Pressure."

Add: "MIL-H-26666 - Hose Assembly, Pneumatic, High Pressure."

FSC 4310

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:23Z
Check the source to verify that this is the current version before use.

MIL-C-26805G(USAF)
AMENDMENT 2
10 March 1982

SUPERSEDING
AMENDMENT 1
10 September 1975

MILITARY SPECIFICATION

COMPRESSOR UNITS, AIR/GAS, GENERAL REQUIREMENTS FOR

This amendment forms a part of Military Specification MIL-C-26805G(USAF) dated 10 September 1975, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2: Under Type III, Class 1 delete "Gasoline engine" and substitute "Diesel engine".

PAGE 2

Under SPECIFICATIONS, Federal add; "GG-G-76-Gage, Pressure and Vacuum, Dial Indicating (for Air, Steam, Water, Ammonia, Chloro-fluoro Hydrogen Gases, and Compressed Gases)".

add; "TT-C-490-Cleaning Method and Pretreatment of Ferrous Surfaces for Organic Coatings".

Under Military add; "MIL-T-5624 Turbine fuel, Aviation, Grades JP-4 and and JP-5".

Delete "MIL-G-8402 - Gages, Pressure, Dial Indicating, General Specification for

Delete "MIL-H-8795 - Hose Assemblies, Rubber, Hydraulic, Fuel and Oil Resistant"

Delete "MIL-E-11275 - Engines, Gasoline, Industrial Type, General Specification for".

PAGE 3

Delete "MIL-E-11276 - Engines, Diesel, Industrial, Medium and High Speed, General Specification for".

Add: "MIL-P-23377 - Primer Coating, Epoxy Polyamide, Chemical and Solvent Resistant."

Add: "MIL-H-38390 - Hose Assembly, Tetraflouroethylene, Pneumatic, High Pressure."

Add: "MIL-H-26666 - Hose Assembly, Pneumatic, High Pressure."

FSC 4310

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:23Z
Check the source to verify that this is the current version before use.

PAGE 9

3.4.8.1.2 - Delete in its entirety.

3.4.8.1.3 - Delete in its entirety.

3.4.8.1.4 - Delete in its entirety

3.4.8.1.5 - Delete in its entirety.

3.4.8.1.6 - In the first sentence after "VV-F-800" add "or jet fuel, JP-4 or JP-5, conforming to MIL-T-5624."

PAGE 10

3.4.8.1.11.1 - Delete in its entirety and substitute "3.4.8.1.11.1 Storage batteries. Commercial batteries may be furnished provided they meet or exceed the minimum capacity ampere - hour rating as specified in MIL-B-11188. Batteries shall be shipped charged and dry without electrolyte.

PAGE 11

3.4.8.1.11.3 - Delete in its entirety and substitute "3.4.8.1.11.3 Charging generator/alternator. The charging system shall be as specified in MIL-STD-1410."

PAGE 16

3.4.12 - Delete in its entirety and substitute "3.4.12 Pressure gages. Pressure gages shall be in accordance with Federal Specification GG-G-76."

3.4.14.2 - Delete "or other hoisting attachments shall be provided on" and substitute "shall be provided or other arrangements shall be made for hoisting or removing".

PAGE 17

3.4.15.2.4 - Delete in it entirety and substitute "3.4.15.2.4 Air hose. A 50-foot length of 5/16 inch nominal inside diameter air hose conforming to SAE100R6 shall be provided. The hose shall be equipped with end fittings in accordance with MIL-A-5070."

Add new paragraph "3.4.15.2.4.1 Hose reels. A live hose reel shall be provided to accomodate stowage of the servicing hose. The reel shall be located in a position that will afford protection to the reel from inadvertent damage from other vehicles, stationary objects, etc. The reel shall be equipped with a spring drive for automatic hose retrieval and the drive spring tension shall be adjustable. The reel shall be equipped with a mechanism to assure a positive latch or unlatch with each pull of the hose and shall maintain any desired working length of hose. The reel shall be designed to operate over the temperature range of -65°F to +160°F."

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:23Z
Check the source to verify that this is the current version before use.

3.4.15.2.5 - Add to the beginning of the paragraph -"The receiver shall be designed, constructed, and stamped in accordance with the ASME Boiler and Pressure Vessel Code, Section VIII."

PAGE 19

3.4.15.3.1.3 - Delete "Type II" and substitute "Type III".

3.4.15.3.4 - Delete "MIL-H-8795" and substitute "MIL-H-38390 or MIL-H-26666". Delete "69E35397-5" and substitute "7347114-10".

PAGE 20

3.4.15.3.4.1 - Delete in its entirety and substitute "3.4.15.3.4.1 Hose reel. Hose reel/s conforming to paragraph 3.4.15.2.4.1 shall be provided."

3.4.15.3.9 - In the last sentence delete "MIL-G-8402" and substitute "Federal Specification GG-G-76."

PAGE 22

3.9.1 - Delete in its entirety and substitute "3.9.1 Cleaning, Surface Preparation and Painting. Type I, Type II Class 1, and Type III Class 1 compressors shall be finished as follows:

a. Cleaning, and surface preparation. Prior to painting, ferrous metal surfaces shall be blasted to remove all mill scale, products of corrosion, dirt, casting sand, slag or other foreign substances. Surfaces such as machined parts and sheet metal thinner than 0.0625 inch (16 gage US Standard) shall not be blasted. However, prior to blasting the surface shall be cleaned to insure that the surface is free of all oil, grease, dirt, or any other material that will contaminate the surface. Oil and grease contamination resulting from fabrication, machining, or handling subsequent to cleaning shall be completely removed by methods described in Federal Specificaton TT-C-490.

b. Priming. Prime with one coat of epoxy primer conforming to MIL-P-23377 to 0.7 to 1.0 Mil-inch (dry film) thickness. Allow primer to dry a a minimum of 45 minutes and no longer than 16 hours prior to top coating.

c. Top coating. Top coat with two coats of polyurethane paint conforming to MIL-C-83286, color (as specified in paragraph 6.2 (s)) per FED-STD-595, to a total thickness of 2.0 to 2.5 mils. Environmental controls shall be 60°F to 90°F and 40% to 80% relative humidity.

d. Total thickness. The total thickness of the primer and top coat shall be between 2.7 and 3.5 mils.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:23Z
Check the source to verify that this is the current version before use.

PREVIOUS

e. Decal. A decal shall be affixed to an interior surface of a door indicating the paint system applied and the date applied.

Example: Primer - MIL-P-23377 - 1 coat
Top Coat - MIL-C-83286 - 2 coats
Date Applied - Jan 1983

All other types and classes of compressors covered by this specification shall be cleaned and finished in accordance with the manufacturer's standard commercial practice. The finish color to be as specified in paragraph 6.2(s) per FED-STD-595."

PAGE 23

3.10.9 - In the title delete "cartridge holders" and substitute "dehydrator cartridges" and add "(Type III Only)".

PAGE 27

4.5.2.1 - Delete "4.7.7.1.3" and substitute "4.7.7.1.1".

PAGE 37

Add new paragraph "4.7.21 Hose Reel Environmental Performance Test. With the maximum operating pressure of the compressor unit applied to the inlet connection to the reel and the outlet of the hose or reel plugged, the reel shall be subjected to 1,000 cycles (complete unreeling and retrieval of the hose) at each of the following ambient temperatures; -65° ± 5°F, 70° ± 15°F, and + 160 ± 5°F. Any malfunction of the reel to perform as intended shall be cause for rejection . This test applies to the preproduction unit only."

6.2 (c) - Delete "Gasoline" and substitute "Diesel".

6.2 (g) - Delete in its entirety.

PAGE 38

6.2 (s) - Delete in its entirety and substitute "6.2(s)- Color No. per FED-STD-595".

6.2 (t) -Delete in its entirety.

Custodian:
Air Force - 99

Preparing Activity:
Air Force - 99

Project Number:
4310-F087

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:23Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:23Z
Check the source to verify that this is the current version before use.