INCH - POUND

MIL-DTL-26764C
23 November 2018
SUPERSEDING
MIL-L-26764B
04 March 1970

DETAIL SPECIFICATION

LIGHT, MARKER, AIRPORT APPROACH, HIGH INTENSITY, TYPE MB-2

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1 SCOPE

1.1 Scope. This specification covers one type of high intensity, airport approach, marker light, designated Type MB-2.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government Documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

SPECIFICATIONS

MILITARY

MIL- DTL-7989 - Covers, Light-Transmitting, for Aeronautical Lights, General Specification for

Comments, suggestions, or questions on this document should be addressed to DLA Troop Support - Industrial Hardware Division (ATTN: Code FHTE), 700 Robbins Avenue, Philadelphia, PA 19111-5096 or email trpsptspecspa@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:11Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MS24489 - Filter, Marker Light, Airport Approach, Glass
MIL-STD-130 - Identification Marking of U.S. Military Property
MIL-STD-889 - Dissimilar Metals

(Copies of these documents are available online at http://quicksearch.dla.mil.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract

FEDERAL AVIATION ADMINISTRATION:

SPECIFICATIONS

L-823 - Plug and Receptacle Cable Connectors
FAA-982 - PAR:56 Lamp Holder

DRAWINGS

D-4761-1 - PAR-56 Lamp Holder, General Assembly
D-4761-2 - PAR-56 Lamp Holder, Parts Details
D-4761-3 - PAR-56 Lamp Holder, Parts Details

(Copies of these documents are available online at https://www.faa.gov).

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

ASTM INTERNATIONAL

ASTM B633 Zinc on Iron and Steel, Electrodeposited Coatings of

(Copies of these documents are available from http://www.astm.org.)

American Society for Quality (ASQ):

ANSI/ASQ Z1.4 - Sampling Procedures and Tables for Inspection by Attributes.

(Copies of this document are available online from http://asq.org.

SAE International

SAE-AMS-STD-595 - Colors, color 12197

SAE-AS25050 - Colors, Aeronautical Lights and Lighting Equipment, General Requirements for

(Copies of this document are available online from http://www.sae.org)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:11Z
Check the source to verify that this is the current version before use.

ASME (AMERICAN SOCIETY OF MECHANICAL ENGINEERS)

ASME-Y14.100 - Engineering Drawing and Related Documentation Practices

(Copies of these documents are available from https://www.asme.org)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein (except for related specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2.

3.2 Use of commercial parts. Bolts, nuts, washers, cotter pins, lock rings and similar fastening devices used for assembly, may be selected from commercial sources, provided military or other standard parts are not specified by this specification or associated standards. If such commercial parts are used, they shall possess suitable properties and shall be replaceable by military standard parts without alteration, and provided the corresponding military standard part numbers are referenced in the parts list and, if practicable, on the contractor's drawings.

3.3 Materials.

3.3.1 Fungus-proof materials. Materials that are nutrients for fungi shall not be used where it is practicable to avoid them. When used and not hermetically sealed, they shall be treated with a fungicidal agent acceptable to the procuring activity. However, if they will be used in a hermetically sealed enclosure, fungicidal treatment will not be necessary.

3.3.2 Metals. Metals shall be of the corrosion-resistant type or treated to resist corrosion caused by fuels, salt spray, or atmospheric conditions as may be encountered in storage or normal service. The use of dissimilar metals shall be avoided whenever practicable. Dissimilar metals are defined in MIL-STD-889.

3.3.3 Bolts, screws, and nuts. Bolts, screws, and nuts shall be of corrosion resistant metal or shall be treated to prevent corrosion or seizing which would cause difficulty in removal for servicing and maintenance.

3.4 Design and construction. The light shall be designed and constructed in accordance with Drawings D-4761-1, D-4761-2, D-4761-3, and FAA-982, with the exceptions and additions specified herein.

3.4.1 Optional design. Slightly different details of design other than those specified may be permitted, provided the difference does not affect the performance or interchangeability of the lights, and provided the design change is approved by the procuring activity.

3.4.2 Design conditions. The light shall be designed for continuous outdoor operation under all weather conditions. It shall be so designed and constructed that no parts will work loose in service. It shall be constructed to withstand the strains, jars, vibrations and other conditions incident to shipping, storage, installation, and service.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:11Z
Check the source to verify that this is the current version before use.

3.4.3 Adjustment and repairs.· The light shall be so constructed that adjustments and repairs can be easily made by personnel of operating units and overhaul bases without the use of special tools.

3.5 Performance.

3.5.1 Assembly. When tested as specified in 4.4.2, the light shall be properly assembled and shall conform to the design and construction specified.

3.5.2 Operation. There shall be no evidence of smoking, charring, softening or other damage to any component when tested as specified in 4.4.3.

3.5.3 Lamp position. When tested as specified in 4.4.4, the aiming of the light shall correspond to the markings on the protractor scale.

3,6 Components. The major components of the light shall consist of the housing shell, ring, support and holder, terminal block, clips, connectors, and cord.

3.6.1 Lamp. The light shall be designed for use with a PAR-56, 500-watt, 20-amp, two-contact, mogul end-prong base, sealed beam lamp. There shall be approximately 1-inch space between the lamp and the filter. Unless otherwise specified, lamps shall not be furnished with the light (see 6.2).

3.6.1.1 Lamp-holding clips. At least three 18-8 stainless steel pressure clips shall be provided to hold the lamp to the index ring. The clips shall be in accordance with Drawing D-4761-3. They shall be so constructed that they will not cut into the la.mp and will permit the lamp to be readily clipped and held in place. Screws, nuts, and washers shall be furnished with the clips.

3.6.2 Filters. The filters shall be in accordance with MIL-DTL-7989 and MS24489 and shall be capable of being mounted as specified in FAA-982. Unless otherwise specified, the light shall not be provided with a filter (see 6.2).

3.6.2.1 Filter color. When filters are required, they shall be provided in aviation colors specified, conforming to type I of SAE-AS25050 and grade in accordance with MS24489 (see 6.2).

3.6.2.2 Filter clips and screws. The clips and screws for holding the filter shall be supplied with the light.

3.6.3 Mounting hardware. The screws, nuts, bolts, washers, etc., used for assembly of the adjustable mount and for connecting it to the shell shall be of 18-8 stainless steel. One setscrew .375 (3/8)-16 by .750 (3/4) inch used in the mount shown on Drawing D-4761-1 shall have a round point to permit adjustment of the light.

3.6.4 Cord. A two-conductor No. 12 AWG, type SJO rubber or synthetic rubber cord shall be connected to the terminal block of each light. The length of the cord with plug shall be 72 ±2 inches. The cord shall be threaded through the mounting support so that the cord and its connector are inside the mounting support.

3.6.4.1 Cord plug. The plug shall be two pole, 600V, 20 amp in accordance with type Ia of L-823 and shall be molded to the lower end of the cord.

3.6.5 Squeeze connectors. The squeeze connectors shall be in accordance with, or equal to, the connector specified on Drawing D4761-1. Each connector shall be complete with aluminum or steel locknut. If steel locknut is furnished, it shall be zinc plated .0005 inch thick in accordance with type II, class 2 of ASTM B633

3.6.6 Terminal block. The terminal block shall conform to the terminal block requirements specified in FAA-982.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:11Z
Check the source to verify that this is the current version before use.

3.7 Part numbering of interchangeable parts. All parts having the same manufacturer's part number shall be functionally and dimensionally interchangeable. The item identification and part number requirements of ASME Y14.100 shall govern the manufacturer's part numbers and changes thereto.

3.8 Finish. All aluminum parts, except the inside of the support, shall be finished with one base coat and one finish coat of orange paint, color 12197, conforming to SAE-AMS-STD-595. All paints and finishes used in the light shall be suitable for the ·operating temperatures involved and shall not cause parts of the assembly to adhere to each other.

3.9 Identification of product. Equipment, assemblies, and parts shall be marked for identification in accordance with MIL-STD-130.

3.10 Workmanship. The light, including all parts and accessories, shall be fabricated and finished in a thoroughly workmanlike manner. Particular attention shall be given to freedom from blemishes and defects, marking of parts and assemblies, thoroughness of soldering, cementing, welding, brazing, painting, wiring, and riveting, alignment of parts, and tightness of assembled screws and nuts.

3.11 Cleaning. The light shall be thoroughly cleaned, and loose, spattered or excess solder, metal chips, and other foreign material removed during and after final assembly.

4. VERIFICATION

4.1 Classification of tests. The inspection and testing of the light shall be classified as follows:

a. First article testing. (See 4.2)
b. Conformance tests (See 4.3)

4.2 First article testing (see 6.2)

4.2.1 Test sample. The test sample shall consist of one light, one lamp, and one filter representative of the production equipment.

4.2.2 First article tests. The first article tests shall consist of all tests described under 4.4.

4.3 Conformance tests. For the purpose of conformance testing, a lot shall consist of all lights submitted for acceptance at one time. Quality conformance tests shall consist of group I and II tests.

4.3.1 Group I tests. Sampling for group I testing shall be conducted in accordance with ANSI/ASQ Z1.4, inspection level II. The AQL shall be 0. This test shall consist of the examination of product as specified in 4.4.1.

4.3.2 Group II tests. Sampling for group II testing shall be conducted in accordance with ASQ Z1.4, inspection level S-3. The AQL shall be 0. These tests shall consist of the assembly test (4.4.2) and the operation test (4.4.3).

4.4 Test methods.

4.4.1 Examination of product. Each light shall be examined to determine conformance to this specification with respect to materials, workmanship, and marking (see 3.3, 3.9, and 3.10).

4.4.2 Assembly. The light shall be tested with the specified lamp and tilter to determine that the design and construction is satisfactory. When assembled, there shall be approximately a 1-inch space between the la.mp and the filter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:11Z
Check the source to verify that this is the current version before use.

4.4.3 Operation. The light shall be operated for 24 hours at room temperature (approximately 25°c) positioned so the beam is approximately horizontal. It shall be equipped with a 20-amp 500-watt lamp and green filter properly installed. Twenty amperes shall be supplied to the lamp for the 24-hour test period.

4.4.4 Lamp position. The light, complete with lamp and filter, shall be tested to ascertain that the lamp and filter which will be used are correctly positioned and aimed. The protractor scale on the light shall be checked to determine that the aiming of the light is as indicated on the scale.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The Type MB-2 lights are intended for use in airport approach lights.

6.2 Ordering data. Ordering data.

a. Title, number, and date of this specification
b. When filters are to be provided and the color required (see 3.6.2 and 3.6.2.1)
c. Whether lamps are to be furnished with the lights (see 3.6.1)
d. Packaging (see 5.1)

6.3 Subject term (key word) listing.

1. Corrosion-resistant
2. Fungus-proof
3. Lamp
4. Lampholder

6.4 Changes from previous issues. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Navy - AS
Air Force - 99

Review activities:
DLA - GS

Preparing Activity:
DLA - CQ

(Project 6210-2018-001)

NOTE: The activities listed above were interested in this document as of the date of document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:11Z
Check the source to verify that this is the current version before use.