INCH-POUND

MIL-G-26869D
21 April 1989
SUPERSEDING
MIL-G-26869C
21 March 1980

MILITARY SPECIFICATION

# GROOVING MACHINE, SHEET METAL, FLOOR MOUNTING TYPE, POWER OPERATED, ELECTRIC MOTOR DRIVEN

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification covers one size sheet metal grooving machine of the floor mounting type with equipment and accessories specified herein.

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-M-18058 - Machinery, Metal and Woodworking, Packaging of.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSG, 2163 Airways Blvd. Memphis, Tennessee 38114-5051, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of of this document or by letter.

AMSC N/A FSC 3441

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:28Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-H28 - Screw Thread Standards for Federal Services.

(Unless otherwise indicated, copies of Federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center , (ATTN: NPODS) 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

CODE OF FEDERAL REGULATIONS (CFR)

U. S. DEPARTMENT OF LABOR, OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR 1910 - Occupational Safety and Health Standards.

(Application for copies should be addressed to the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402-0001.)

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contract activity.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI B11.7 - Cold Headers and Cold Formers - Safety Requirements for the Construction, Care, and Use. (DOD adopted)

(Application for copies should be addressed to the American National Standards Institute, ATTN: Sales Dept., 1430 Broadway, New York, NY 10018-3363. )

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA 79 - Electrical Standard for Industrial Machinery. (DOD Adopted)

(Application for copies should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269-9101.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:28Z
Check the source to verify that this is the current version before use.

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

## 3. REQUIREMENTS

3.1 First article. When specified (see 6.2), one complete machine shall be subjected to first article inspection (see 6.3) in accordance with 4.4.

3.2 Design. The machine shall be new (not a prototype) and one of the manufacturer s current production models capable of operations in accordance with the requirements herein. The machine shall include all components, parts, and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be readily accessible for adjustment, replacement, or repair. The machine shall be power operated, designed to perform sheet metal forming operations through the use of a powered head on a carriage, which rolls the specified shapes, by the application of mechanical pressure on the workpiece.

3.2.1 Measuring and indicating device calibration. Measuring and indicating devices shall be graduated in inch-pound (see 6.4.1), metric (see 6.4.2), or dual (inch-pound and metric) units as specified by the procuring activity (see 6.2). Regardless of the measurement system used, all measuring and indicating devices on the machine shall be graduated in the same system.

3.2.1.1 Dials. Dials shall be permanently and legibly engraved or etched on a nonglare background with graduations that can be read from the operator’s normal position.

3.2.2 Reclaimed materials. The machine may contain reclaimed materials to the maximum extent Possib le provided such materials will not jeopardize the intended use, performance, or design life of the machine. Reclaimed materials shall have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted-to mean that the ‘use of used, rebuilt, or remanufactured products are allowed under this specification.

3.2.3 Energy efficiency. The machine and its components that directly consume energy in normal operation shall be designed and constructed for energy efficiency in accordance with the developments available within the industry.

3.2.4 Controls. All mechanical, hydraulic, and pneumatic operating controls shall be located convenient to the operator’s work station(s).



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:28Z
Check the source to verify that this is the current version before use.

3.2.5 Safety and health requirements. All parts, components, mechanisms, and assemblies furnished on the machine, whether or not specifically required herein, shall conform with all requirements of 29 CFR 1910 and ANSI B11.7. If a conflict arises between 29 CFR 1910 and B11.7, 29 CFR 1910 shall apply. Additional safety and health requirements shall be as specified in detail (see 6.2). Covers, guards, or other safety devices normally furnished as standard on the manufacturer's commercial machine supplied to the commercial market shall be provided for the point of operation and all other parts of the machine that present safety hazards. Additional guarding dependent on workpiece size and configuration shall be provided when specified and fully described by the procuring activity (see 6.2).

3.2.6 Mercury restriction. The machine shall not contain mercury or mercury compounds nor be exposed to free mercury during manufacture.

3.2.7 Asbestos restriction. Asbestos and materials containing asbestos shall not be used on or in the machine.

3.2.8 Environmental protection. During the manufacture, operation, service, transportation, or storage of the machine, and its components, materials hazardous to the ecological system as prohibited by Federal, state, or local statutes in effect at the point of installation on the date of the contract shall not be used or emitted.

3.2.9 Lubrication. Means shall be provided to ensure lubrication for all moving parts. Recirculating lubrication systems shall include a cleanable or replaceable filter. Each lubricant reservoir shall have means for determining fluid level. All oil holes, grease fittings, and filler caps shall be accessible.

3.2.10 Interchangeability. To provide for replacement of worn parts, all parts shall be manufactured to definite dimensions and tolerances that will permit installation of replacement parts without modification of the part or machine.

3.3 Construction. The machine shall be constructed of parts which are new, without defects, and free of repairs. The structure shall withstand all forces encountered during operation of the machine to its maximum rating and capacity without permanent distortion.

3.3.1 Castings and forgings. All castings and forgings shall be free of defects, scale, and mismatching. No processes such as welding, peening, plugging, or filling with solder or paste shall be used for reclaiming any defective part. Such processes may be used only for enhancing surface finish and appearance.

3.3.2 Fastening devices. All fasteners shall be installed to prevent change of tightness. Fastening devices subject to removal or adjustment shall not be permanently installed.

3.3.3 Surfaces. All surfaces shall be clean and free of harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:28Z
Check the source to verify that this is the current version before use.

specified herein, the condition and finish of all surfaces shall be in accordance with the manufacturer's commercial practice.

3.3.4 Welding, brazing, or soldering. Welding, brazing, or soldering shall be employed only where specified in the original design. None of these operations shall be employed as a repair measure for any defective part.

3.3.5 Painting. Unless otherwise specified (see 6.2), the machine shall be painted in accordance with the manufacturer's commercial practice and color.

3.3.6 Threads. All threaded parts used on the machine and its related attachments and accessories shall conform to FED-STD-H28 and the applicable "Detailed Standard" section referenced therein.

3.3.7 Gears. All gears shall be constructed from a material suitable for the intended purpose. All drive gears shall have the hardness, surface finish, and toughness that will enable the gear train to transmit full rated torque of the drive motor without gear damage, failure, or premature deterioration and wear.

3.4 Components. The machine shall consist of not less than a pedestal and base assembly, frame, horn, carriage, rolls, and electrical System.

3.4.1 Pedestal and base assembly. The pedestal and base assembly shall support the frame, horn, and the powered carriage. The base shall have not less than three mounting holes for securing the base to the foundation.

3.4.2 Frame. The frame shall support and direct the powered carriage along the ways and guides. The outer end of the frame shall be constructed with a mechanical latch for providing support to the outer end of the horn, and also include features that allow easy mounting and removal of workplaces.

3.4.3 Horn. The horn shall have both flat and grooved longitudinal working surfaces. The horn shall revolve and lock in position, to the desired working surface, positioned properly under the carriage. Workpiece positioning on the horn shall be adjustable by a movable stop.

3.4.4 Carriage. The carriage shall be mounted on the frame. An electric motor driven mechanism shall provide forward and reverse carriage motions, at speeds of not less than 70 feet per minute. Adjustable stops shall halt the forward carriage motion, and the carriage motion shall be reversed by a manual control.

3.4.5 Rolls. Rolls shall be supported by the carriage with a means for adjusting rolling pressure, on the workpiece. Rolling action shall start with one roller contacting the workpiece on the outward travel, and another alternately, on the inward or return stroke. Rolls shall be designed to accomplish lock seaming on both single and Pittsburg seams. Three (3) grooved and two (2) flat rolls for single lock seaming, and two (2) closing rolls for Pittsburgh lock seams shall be provided with each grooving machine.

3.4.6 Electrical system. The electrical system shall be wired to conform to NFPA 79. Unless otherwise specified (see 6.2), each machine shall be wired to draw all of its electrical power from a single 230/460-volt, 3-phase,



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:28Z
Check the source to verify that this is the current version before use.

60-Hertz (Hz) circuit. Unless otherwise specified (see 6.2), the machine shall be initially wired for operation on 460 volts.

3.4.7 Motors. Motors shall be rated for continuous duty and shall have ball or roller bearings of the sealed and permanently lubricated type. Unless otherwise specified (see 6.2), each motor shall have a dripproof enclosure.

3.4.8 Worklight. When specified (see 6.2), a worklight shall be provided. The light shall have a protective shield, an on-off switch and shall be adjustable to reflect maximum light on the work area. If a built in lighting system is provided, the adjustable light described above shall not be required.

3.4.9 Hour meter. When specified (see 6.2), the machine shall be equipped with an hour meter. The hour meter shall be installed to display accumulated operating time of the main drive motor. The meter shall be of the nonresetting type and shall have a range of 0 to 9,999 hours in increments of not greater than 1 hour. The meter shall be sealed to prevent the entrance of dust and moisture and shall be mounted to withstand shock and vibration generated by the machine.

3.5 Performance. The machine shall be power operated, capable of performing sheet metal forming operations of grooving, seaming, flattening, and offsetting. This includes both inside and outside seams of both the cylindrical and rectangular shaped sheet metal pipe and ductwork, on which the edges are prefolded for single lock and Pittsburg type seams. The machine shall be capable of performing the forming operations on workplaces up to a length of 48 inches, but not in excess of 60 inches; also a thickness range of 18 to 22, U. S. standard gage, of galvanized, and mild steel with a tensile strength of at least 50,000 pounds per square inch. The minimum inside diameter of cylindrical work shall be 4 inches, and a minimum inside dimension of 3-1/8 inches, for rectangular or square work. The machine shall be capable of performing these operations without damage to the tooling, permanent deformation of machine components, or damage to the workpiece.

3.5.1 Additional performance requirements. Performance features required in addition to, or in lieu of, the requirements herein shall be as specified and fully described (see 6.2).

3.6 Standard equipment. All standard equipment normally provided with the manufacturer’s commercial machine shall be furnished.

3.7 Optional equipment. Optional equipment shall be furnished as specified and fully described (see 6.2).

3.8 Repair parts. Required repair parts shall be furnished as specified (see 6.2).

3.9 Marking on instruments, control panels, charts, and plates. All words on instruments, control panels, charts, and plates shall be in the English language. Characters shall be permanently marked in boldface on a contrasting background. All plates shall be corrosion resistant.



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:28Z
Check the source to verify that this is the current version before use.

3.9.1 Lubrication plate. When specified (see 6.2), a lubrication plate or chart shall be attached to each machine. If a chart is furnished, it shall be placed in a transparent plastic folder, or permanently sealed between clear plastic sheets. Unless otherwise specified (see 6.2), the information provided on the chart or plate shall be as listed below:

Points of lubricant application
Type of lubricant
Servicing interval
Military or Federal specification for each lubricant (if applicable)

3.9.2 Nameplate. A nameplate shall be securely attached to each machine. Unless otherwise specified (see 6.2), the nameplate shall contain the information listed below:

Nomenclature
Manufacturer's name
Manufacturer's model designation
Manufacturer's serial number
Power input (volts, total amps, phase, frequency)
Amp rating of largest motor
Short circuit/over-current protection rating
Contract number or order number
National stock number or plant equipment code
Date of manufacture

3.10 Workmanship. Workmanship of the machine and its accessories shall meet all requirements specified herein and shall be of a quality equal to that prevailing among manufacturers producing equipment of the type covered by this specification.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:28Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a, First article inspection (see 4.4).

b. Quality conformance inspection (see 4.5).

4.3 Inspection conditions. Unless otherwise specified (see 6.2), all inspections shall be performed in accordance with the test conditions specified in 4.7.1.

4.4 First article inspection. When a first article inspection is required, it shall be applied to the first article submitted in accordance with 3.1. Unless otherwise specified (see 6.2), first article inspection shall consist of the examination in 4.6 and all tests in 4.7. The machine shall pass the examination and all tests to be accepted.

4.5 Quality conformance inspection. Quality conformance inspection shall be applied to each item prior to being offered for acceptance under the contract. Unless otherwise specified (see 6.2), quality conformance inspection shall consist of the examination in 4.6, the tests in 4.7, and the inspection in 4.8. The machine shall pass the examination, all tests, and the inspection to be accepted.

4.6 Examination. The machine shall be examined to determine compliance with all requirements of this specification.

4.7 Tests.

4.7.1 Test conditions. All tests shall be performed in an indoor facility with ambient conditions of $41^0$ to $104^0$ Fahrenheit (F), and 20 percent to 95 percent relative humidity.

4.7.2 Operational test. Each machine shall be operated at no load for not less than 30 minutes. Proper operation of all controls, motors, adjusting mechanisms, and accessories shall be verified during the trial period.

4.7.3 Performance tests. The grooving machine shall be tested to determine compliance with 3.5. Complete grooving operations shall be performed on the type steel workplaces of not less than 50,000 P.S.I., tensile strength. The resulting seams, inside and outside, shall be smooth and firmly folded along their entire length. All performance tests shall be completed without making any adjustments to or performing any maintenance on the machine.

4.8 Packaging inspection. Packaging of each item shall be inspected to determine compliance with the requirements of section 5.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-18058.



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:28Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. Grooving machines covered herein are intended for use in sheet metal shops, to perform finishing operations on longitudinal seams of sheet metal cylinders and rectangular ductwork.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Issue of DODISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).

c. First article, if required (see 3.1).

d. Specify system of units for measuring and indicating devices (see 3.2.1).

e. Additional safety and health requirements, if required (see 3.2.5).

f. Specify configuration of additional point-of-operation guarding, if required (see 3.2.5).

g. Painting, if different (see 3.3.5.).

h. Electrical system, if different (see 3.4.6).

i. Initial input voltage, if different (see 3.4.6).

j. Motors, if different (see 3.4.7).

k. Worklight, if required (see 3.4.8).

l. Hour meter, if required (see 3.4.9).

m. Additional performance features, if required (see 3.5.1).

n. Specify and fully describe optional equipment, if required (see 3.7).

0. Specify applicable repair parts, if required (see 3.8).

P. Lubrication plate, if required (see 3.9.1).

q. Specify information to be provided on lubrication plate, if different (see 3.9.1).



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:28Z
Check the source to verify that this is the current version before use.

r. Nameplate, if different (see 3.9.2).

s. Inspection conditions, if different (see 4.3).

t. First article inspection, if different (see 4.4).

u. Quality conformance inspection, if different (4.5).

6.2.1 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DIDs) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DIDs are tailored to reflect the requirements of the specification acquisition. To ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 27.475-1. exempts the requirement for a DD Form 1423.

| Reference Paragraph | DID Number | DID Title | Suggested Tailoring |
|---|---|---|---|
| . | . | . | . |
| . | . | . | . |
| . | . | . | . |

The above DIDs were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DIDs are cited on the DO Form 1423.

6.2.2 Technical data. All technical data furnished should be written in the English language.

6.3 First article. When first article inspection is required, the contracting officer should provide specific guidance to offerors whether the item(s) should be a preproduction sample, a first article sample, a first production item, a sample, a standard production item from the contractor's current inventory (see 3.1), and the number of items to be tested. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Definitions.

6.4.1 Inch-pound units. Inch-pound units are a system of measures based on the yard and pound commonly used in the United States of America and defined by the National Bureau of Standards. Inch-pound units having the same names in other countries may differ in magnitude.



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:28Z
Check the source to verify that this is the current version before use.

6.4.2 Metric units. Metric units are a system of basic measures defined by the International System of Units based on "Le Systeme International d'Unites (SI)," of the International Bureau of Weights and Measures. These units are described in ASTM E 380 and IEEE 268 (MIL-STD-961).

6.5 Measurement system. In this specification, all measurements, dimensions, sizes, and capacities are given in inch-pound units. These measurements may be converted to metric units through the use of the conversion factors and methods specified in FED-STD-376.

6.6 Changes from previous issues. Marginal notations are not used in this revision to identity changes with respect to the previous issue due to the extensiveness of the changes.

6.7 Safety and health requirements. The 29 CFR 1910 limits only the total hazard level (noise, radiation, electromagnetic emissions, noxious vapors, air contaminants and heat) of the environment in which a machine will operate. It does not limit the hazard level of individual machines in an" operating environment. The procuring activity should analyze the existing hazard level in the proposed operating environment and specify additional requirements necessary to integrate this new machine into its future environment.

6.8 Training. Training required by the procuring activity should be provided as specified in the contract.

6.9 Warranty. Warranty requirements should be as specified by the procuring activity in the contract.

6.10 Inspection location. The contractor should identify in his response to the solicitation the location where Inspection and tests are to be performed.

6.11 Subject term (keyword) listing:

Flange
Forming
Grooving
Seams
Sheet metal

Custodians:
Army - AL
Air Force - 99

Review activity:
Air Force - 84

User activities:
Army - AR
Navy - YD

Preparing activity:
DLA - IP

Project (3441-0139)



Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:28Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:28Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| IIL-G-26869D | GROOVING MACHINE, SHEET METAL, FLOOR MOUNTING TYPE, POWER OPERATED, ELECTRIC MOTOR DRIVEN |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR<br>☐ USER<br>☐ MANUFACTURER<br>☐ OTHER *(Specify)*: _____ |
| b. ADDRESS *(Street, City, State, ZIP Code)* | |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording.

c. Reason/Rationale for Recommendation:

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:28Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE:* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEFENSE LOGISTICS AGENCY
Commander
Defense Industrial Plant Equipment Center
ATTN: DIPEC-SSG
Memphis, TN 38114-5051

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 4966 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Commander
Defense Industrial Plant Equipment Center
ATTN: DIPEC-SSG
Memphis, TN 38114-5051

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:28Z
Check the source to verify that this is the current version before use.