MIL-H-26827(USAF)
AMENDMENT 1
1 April 1958

MILITARY SPECIFICATION

HANDSET-HEADSET H-108( )/U
AND CORD CX-1245( )/U (7 FT 6 IN)

This amendment forms a part of Military Specification MIL-H-26827(USAF) dated 9 August 1956.

Page 1, paragraph 1.1: Delete and substitute:
"1.1 This specification covers one type of handset-headset designated Handset-Headset H-108( )/U, hereinafter referred to as "the handset-headset" and two cords designated Cord CX-1245( )/U (7 Feet (ft) 6 Inches (in)) and Cord CX-4396( )/U (3 ft 0 in), hereinafter referred to by their respective nomenclatures."

Page 2, paragraph 2.1: After the list of "STANDARDS Military" add "DRAWINGS

Air Force

56E12858 Cushion, Airfoam MX-2088/U Assembly Of"

Page 2, paragraph 3.3: Delete and substitute:
"3.3 COMPONENTS.- The handset-headset and cords shall consist of the following:

Item	Quantity	Description	Requirement
1	1 each	Handset-Headset H-108( )/U	3.7.1
2	1 each	Cord CX-1245( )/U (7 ft 6 in) or	3.7.2
3	1 each	Cord CX-4396( )/U (3 ft 0 in)	3.7.3"

Page 8, Add the following paragraph:
"3.6.9 SWITCH BAR COVER.- The switch bar cover shall be polyurethane rubber or equal."

Page 8, paragraph 3.7.1.1: Delete and substitute:
"3.7.1.1 HEADBAND ASSEMBLY.- The headband shall be made of spring wire covered with a material which shall give a maximum degree of traction. The headband shall accommodate two ear cushions similar to Ear Cushion MX-2088/U, Hyperlon type in accordance with drawing 56E12858. One ear cushion shall cover the receiver housing, the other ear cushion shall have an opening through the center. Attachment of the headband assembly to the headset shall permit a 360-degree rotation around the receiver (earphone end)."

FSC
5965
5995

THE REPUBLICAN PRESS, Hamilton, Ohio
June 29, 1958 500

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:24Z
Check the source to verify that this is the current version before use.

Page 9, Add the following paragraph:
"3.7.3 CORD CX-4396( )/U (3 Ft 0 In).- The cord assembly shall consist of three -conductor, tinsel cord, in accordance with MIL-C-3849, terminated at one end in Plug RJ-068 in accordance with MIL-P-642. The other end shall terminate in a three-conductor polarized plug suitable for mating with Connecticut Telephone and Electric Corporation plug type 12154 or equal attached to Headset H-108( )/U. Color coding to the plug shall be as follows:

a. Tip (black) of Plug RJ-068 to one side of the transmitter.

b. Ring (red) of Plug RJ-068 to the other side of the transmitter and to one side of the receiver. This conductor shall be common to one side of the transmitter and one side of the receiver.

c. Sleeve (white) of Plug RJ-068 to the other side of the receiver."

Page 10, paragraph 4.3.1: Delete and substitute:
"4.3.1 PREPRODUCTION TEST SAMPLES.- The following items as specified in the contract will be tested for design approval by the procuring activity, or when so specified in the contract, at the contractors' plant under the supervision of the procuring activity:

a. 12 each Handset-Headset H-108( )/U
b. 8 each Receiver elements
c. 8 each Microphone elements
d. 4 each Cord CX-1245( )/U (7 ft 6 in)
e. 4 each Cord CX-4396( )/U (3 ft 0 in)"

Page 19, paragraph 6.1: Delete the last sentence and substitute:
"Cord CX-1245( )/U (7 ft 6 in) or Cord CX-4396( )/U (3 ft 0 in) are intended to be used to connect the operator's handset -headset to the telephone equipment."

Page 19, paragraph 6.2: Add the following:
"e. Whether Cord CX-1245( )/U (7 ft 6 in) or Cord CX-4396( )/U (3 ft 0 in) will be provided with Handset-Headset H-108( )/U."

Page 19, paragraph 6.4, line 2: After "Cord CX-1245( )/U (7 ft 6 in)", add "or Cord CX-4396( )/U (3 ft 0 in)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:24Z
Check the source to verify that this is the current version before use.