MIL-P-26795B(USAF)
AMENDMENT 2
22 December 1964
Superseding
AMENDMENT 1
22 June 1964

MILITARY SPECIFICATION

PUMP, ROTARY, POWER DRIVEN, 20 GPM CAP., TWO WHEELED HAND CART, TYPE MC-1

This amendment forms a part of Military Specification MIL-P-26795B(USAF) dated 11 September 1963.

Pages 1 and 2, paragraph 2.1:

(1) Federal specifications: Add: "0-F-555 Foam-Forming Liquids, Concentrated Fire Extinguishing, Mechanical".

(2) Military specifications: Delete "JAN-P-100," "MIL-B-138," "JAN-C-266," "MIL-T-9107," "MIL-M-26512," and "MIL-I-26600".

(3) Military standards: Add:

"MIL-STD-826	Electromagnetic Interference Test Requirements and Test Methods
"MIL-STD-831	Test Reports, Preparation of".

Page 4, paragraph 3.5.3: Delete and substitute:

"3.5.3 Maintainability.- The pumping unit shall be designed and constructed as specified herein and to provide the following:

a. Minimum number of parts consistent with reliability and performance specified herein.

b. Minimum amount of training and time necessary for assembly, disassembly, location of trouble sources, and maintenance including servicing. Where practical, parts and components shall be located or positioned for rapid and simple inspection and recognition of excessive wear or potential failure

c. Permit adjustments, servicing, replacement of parts and components, and other maintenance with minimum disturbance to other equipment parts or components. Parts and components shall be located for ample and rapid access unless performance or reliability will be appreciably degraded by the accessible location. In performing maintenance, if engineering reasoning or data determines that physical or visual interference between items cannot be avoided, the item predicted to require the most maintenance shall be located for best accessibility

FSC 4320

Source: https://assist.dla.mil -- Downloaded: 20260-20T10:22Z
Check the source to verify that this is the current version before use.

information of a general or explanatory nature that may be helpful, but ... (THIS section contains

d. Permit maintenance with general-purpose tools and equipment normally available commercially. Use of special-purpose tools and equipment shall be subject to approval by the procuring activity

e. Minimum number of tools required for maintenance by design practices such as reducing the variety of bolt head sizes to the practicable minimum

f. Foolproofness - Where improper installation of an item could cause malfunction of the item or the equipment in which it is installed, an unsymmetrical mounting means shall be provided where practical. That mounting shall allow the item to be installed only in its proper operating position. If an unsymmetrical mounting means is not practical, the item shall be so mounted that its proper operating position can be readily and visibly determined by service maintenance personnel."

Page 5, paragraph 3.6, item a(1): Delete "(JAN-C-266)" and substitute "(O-F-555)".

Page 6, paragraph 3.8.2, item a: Delete "5100-S5-16" and substitute "510008-S5-16". Item b: Delete "JAN-C-266" and substitute "O-F-555".

Page 6, paragraph 3.10.1: Delete and substitute:

"3.10.1 Power cable.-The pumping unit shall be provided with a 20-foot, 2 No. 10 AWG electric cable conforming to MIL-C-3432, class HD, or commercial type SO, and having a MS24217 connector head molded to the cable."

Page 6, paragraph 3.10.2, first sentence: Delete and substitute "The motor shall be controlled by a double-pole, single-throw momentary contact, normally off-switch mounted at the end of a 15-foot, No. 10 AWG conductor, electric cable conforming to MIL-C-3432, class HD, or commercial type SO."

Page 7, paragraph 3.13: Delete "MIL-I-26600, class IV." and substitute "MIL-STD-826."

Page 7, paragraph 3.15, line 3: Delete "215 pounds." and substitute "225 pounds."

Page 8, paragraph 4.3.1: Delete "JAN-C-266" and substitute "O-F-555".

Page 9, paragraph 4.4.2: Delete "MIL-T-9107" and substitute "MIL-STD-831".

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:22Z
Check the source to verify that this is the current version before use.

Page 13, paragraph 4.6.10: Delete "for class IV equipment in MIL-I-26600." and substitute "in MIL-STD-826, method 1001, class T."

Page 13, paragraph 4.6.12: Delete and substitute:

"4.6.12 Maintainability evaluation.-The pumping unit shall be inspected and evaluated from the standpoint of ease of maintenance, servicing, and operation. Particular attention shall be given maintenance with a minimum number of common tools, servicing, and operation by personnel wearing heavy gloves, and provisions made to prevent accumulation of dirt, snow, ice, et cetera, that may hinder servicing and operation."

Page 13, paragraph 5.2.1, line 3: Delete ", or MIL-B-138".

Page 14, paragraph 5.3: Delete.

Page 15: Delete "ASD".

Custodian:
Air Force - 11

Preparing activity:
Air Force - 11

Reviewers:
Air Force - 11, 69

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:22Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:22Z
Check the source to verify that this is the current version before use.