NOT MEASUREMENT SENSITIVE

MIL-D-3943/56C
24 June 1994
SUPERSEDING
MIL-D-3943/56B
31 March 1987

MILITARY SPECIFICATION SHEET


DECORATION, MERITORIOUS SERVICE AWARD, DEFENSE CONTRACT AUDIT AGENCY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-D-3943.



OBVERSE





REVERSE

MATERIAL: Red Brass

FINISH: Nickel Plated, Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 15.

DIMENSIONS:

HEIGHT (Including Lug): 2 inches (5.08 cm) (REF)
DIAMETER: 1-21/32 inches (4.21 cm) (REF)
THICKNESS (At Center): 0.225 inch ± 0.010 inch (0.572 cm ± 0.025 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T23:10Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated.

3. Decoration set shall consist of a regular size medal, a service ribbon and a lapel button all packaged in a presentation case conforming to MIL-C-14633, Type VIII, Style 6 with a Class 1 or 1A pad.

4. The ribbon for the pendant drape and service ribbon shall conform to MIL-R-11589/160.

5. The lapel button shall conform to MIL-L-11484/203.

Custodians:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0763)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T23:10Z
Check the source to verify that this is the current version before use.