INCH-POUND


MIL-DTL-3928/10F
28 January 2013
SUPERSEDING
MIL-DTL-3928/10E
15 August 2001

DETAIL SPECIFICATION SHEET


SWITCHES, RADIO-FREQUENCY TRANSMISSION LINE (COAXIAL) (ELECTRICALLY OPERATED) CLASS 1

This specification is approved for use by all Departments and Agencies of the Department of Defense.

Requirements for acquiring the switch described herein shall consist of this specification and MIL-DTL-3928.



Position 1. (De-energized or failsafe position), C connects to NC connector.
Position 2. (Energized position), C connects to NO connector.




Dimensions									
Letter	Inches		Millimeters		Letter	Inches		Millimeters	
	Max	Min	Max	Min		Max	Min	Max	Min
A	2.03	1.97	51.6	50.0	J	1.510	1.490	38.35	37.85
B	1.135	1.115	28.83	28.32	K	.792	.772	20.12	19.61
C	.112-40 UNC-2B dia		2.84-40 UNC-2B dia		L	.604	.584	15.34	14.83
D	.697	.677	17.70	17.20	M	.681	.661	17.30	16.79
E	.104	.084	2.64	2.13	N	1.03	.97	26.2	24.6
F	.885	.865	22.48	21.97	P	.775	.755	19.68	19.18
G	.135	.115	3.43	2.92	Q	.510	.490	12.95	12.45
H	.510	.490	12.95	12.45					

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (in millimeters) are given for general information only (1.00 inch = 25.4 mm).
3. Corners of case may be round or square.
4. Unless otherwise specified, tolerances are ± .010 (± 0.25 mm) for three place decimals and ± .03 (±0.8 mm) for two place decimals.

FIGURE 1. PINs M3928/10-01, M3928/10-02, and M3928/10-03.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:16Z
Check the source to verify that this is the current version before use.




Position 1. (De-energized or failsafe position),
C connects to NC connector.
Position 2. (Energized position),
C connects to NO connector.

Dimensions									
Letter	Inches		Millimeters		Letter	Inches		Millimeters	
	Max	Min	Max	Min		Max	Min	Max	Min
A	.32	---	8.1	---	J	.213 dia	.193 dia	5.41 dia	4.90 dia
B	.38	.32	9.7	8.1	K	.880	.860	22.35	21.84
C	.73	.67	18.5	17.0	L	.895	.875	22.73	22.23
D	2.2	---	56	---	M	1.780	1.760	45.21	44.70
E	.210	.190	5.33	4.83	N	2.71	---	68.8	---
F	.63	.57	16.0	14.5	P	.27	.21	6.9	5.3
G	.452	.432	11.48	10.97	Q	.56	.50	14.2	12.7
H	.895	.875	22.73	22.23	R	1.09	---	27.7	---

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (in millimeters) are given for general information only (1.00 inch = 25.4 mm).
3. Corners of case may be round or square.
4. Unless otherwise specified, tolerances are ± .010 (± 0.25 mm) for three place decimals and ± .03 (±0.8 mm) for two place decimals.

FIGURE 2. PINs M3928/10-04 and M3928/10-09.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:16Z
Check the source to verify that this is the current version before use.



Position 1. (De-energized or failsafe position), C connects to NC connector.
Position 2. (Energized position), C connects to NO connector.

Actuator and ind. ckt terminals	
Solenoid common	A
Solenoid (position 2) +28 V dc	B
Ind. ckt common	C
Ind. ckt (position 1)	D
Ind. ckt (position 2)	E

Dimensions									
	Inches		Millimeters			Inches		Millimeters	
Letter	Max	Min	Max	Min	Letter	Max	Min	Max	Min
A	.32	---	8.1	---	J	.213 dia	.193 dia	5.41 dia	4.90 dia
B	.38	.32	9.7	8.1	K	.880	.860	22.35	21.84
C	.73	.67	18.5	17.0	L	.895	.875	22.73	22.23
D	2.2	---	56	---	M	1.780	1.760	45.21	44.70
E	.210	.190	5.33	4.83	N	2.71	---	68.8	---
F	.63	.57	16.0	14.5	P	.27	.21	6.9	5.3
G	.452	.432	11.48	10.97	Q	.555	.535	14.10	13.59
H	.895	.875	22.73	22.23	R	1.09	---	27.7	---

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (in millimeters) are given for general information only (1.00 inch = 25.4 mm).
3. Corners of case may be round or square.
4. Unless otherwise specified, tolerances are ± .010 (± 0.25 mm) for three place decimals and ± .03 (±0.8 mm) for two place decimals.

FIGURE 3. PIN M3928/10-05.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:16Z
Check the source to verify that this is the current version before use.





FIGURE 4. PIN M3928/10-06.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:16Z
Check the source to verify that this is the current version before use.

SCHEMATIC



Dimensions									
Letter	Inches		Millimeters		Letter	Inches		Millimeters	
	Max	Min	Max	Min		Max	Min	Max	Min
A	.59	.53	15.0	13.5	M	2.72	2.66	69.1	67.6
B	3.47	3.41	88.1	86.6	N	1.545	1.535	39.2	39.0
C	2.945	2.935	74.80	74.55	P	.39	.33	9.9	8.4
D	2.53	2.47	64.3	62.7	Q	1.15	1.09	29.2	27.7
E	2.395	2.385	60.83	60.58	R	.59	.53	15.0	13.5
F	.18	.12	4.6	3.0	S	.50	.44	12.7	11.2
G	.30	.24	7.6	6.1	T	.873	.867	22.17	22.02
H	1.28	1.22	32.5	31.0	U	.873	.867	22.17	22.02
J	3.66	---	93.0	---	V	.10	.04	2.5	1.0
K	2.63	---	66.8	---	W	.185	.175	4.70	4.44
L	.69	.63	17.5	16.0					

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (in millimeters) are given for general information only (1.00 inch = 25.4 mm).
3. Corners of case may be round or square.
4. Unless otherwise specified, tolerances are ± .010 (± 0.25 mm) for three place decimals and ± .03 (±0.8 mm) for two place decimals.

FIGURE 4. PIN M3928/10-06 - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:16Z
Check the source to verify that this is the current version before use.





FIGURE 5. PIN M3928/10-07.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:16Z
Check the source to verify that this is the current version before use.

SCHEMATIC




Dimensions									
	Inches		Millimeters			Inches		Millimeters	
Letter	Max	Min	Max	Min	Letter	Max	Min	Max	Min
A	2.00	---	50.8	---	M	.40	.33	10.2	8.4
B	1.10	.90	27.9	22.9	N	.37	.31	9.4	7.9
C	.107	.097	2.72	2.46	P	.185 dia	.175 dia	4.70 dia	4.45 dia
D	1.10	.90	27.9	22.9	Q	1.567	1.557	39.80	39.55
E	2.00	---	50.8	---	R	2.255	2.245	57.28	57.02
F	1.03	.97	26.2	24.6	S	1.010 ref	.990 ref	25.65 ref	25.15 ref
G	3.28	3.22	83.3	81.8	T	.164-32 UNC-2B		4.17-32 UNC-2B	
H	.69	.63	17.5	16.0		x .37 DP	(No. 8)	x 9.40 DP	(No. 8)
J	4.40	---	111.8	---	U	.817	.807	20.75	20.50
K	2.78	2.72	70.6	69.1	V	1.03	.97	26.2	24.6
L	2.40	2.34	61.0	59.4	W	1.630	1.620	41.40	41.15


NOTES:
1. Dimensions are in inches.
2. Metric equivalents (in millimeters) are given for general information only (1.00 inch = 25.4 mm).
3. Corners of case may be round or square.
4. Unless otherwise specified, tolerances are ± .010 (± 0.25 mm) for three place decimals and ± .03 (±0.8 mm) for two place decimals.

FIGURE 5. PIN M3928/10-07 - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:16Z
Check the source to verify that this is the current version before use.




FAILSAFE SCHEMATIC FOR PIN M3928/10-08 AND 11



PIN M3928/10-11 HAS NO
INDICATING CIRCUIT

RF CIRCUIT




POSITION 1 (FAILSAFE POSITION) 1-3,2-4


POSITION 2 (ENERGIZED POSITION) 1 CONNECTS
TO 2 AND 3 CONNECTS TO 4

FIGURE 6. PINs M3928/10-08, M3928/10-10, and M3928/10-11.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:16Z
Check the source to verify that this is the current version before use.

LATCHING SCHEMATIC FOR PIN M3928/10-10





POSITION 1 ◄► 1-3,2-4
POSITION 2 ◄► 1-2,3-4


RF CIRCUIT

Dimensions									
	Inches		Millimeters			Inches		Millimeters	
Letter	Max	Min	Max	Min	Letter	Max	Min	Max	Min
A	3.28	3.22	83.3	81.8	L	.753	.747	19.13	18.97
B	1.78	---	45.2	---	M	2.60	---	66.0	---
C	.198 dia	.192 dia	5.03 dia	4.88 dia	N	.65	---	16.5	---
D	.35	.29	8.9	7.4	P	.730	.710	18.54	18.03
E	2.610	2.590	66.29	65.79	Q	.885	.865	22.48	21.97
F	.49	---	12.4	---	R	.138-32 UNC-2B x .25 DP (No. 6)		3.50-32 UNC-2B x 6.4 DP (No. 6)	
G	1.510	1.490	38.35	37.85					
H	.63	.57	16.0	14.5	S	.452	.432	11.48	10.97
J	.33	.27	8.4	6.9	T	.895	.875	22.73	22.23
K	.28	.22	7.1	5.6					

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (in millimeters) are given for general information only (1.00 inch = 25.4 mm).
3. Corners of case may be round or square.
4. Unless otherwise specified, tolerances are ± .010 (± 0.25 mm) for three place decimals and ± .03 (±0.8 mm) for two place decimals.

FIGURE 6. PINs M3928/10-08, M3928/10-10, and M3928/10-11 - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:16Z
Check the source to verify that this is the current version before use.



Position 1. (De-energized or failsafe position), C connects to NC connector.
Position 2. (Energized position), C connects to NO connector.

Dimensions									
Letter	Inches		Millimeters		Letter	Inches		Millimeters	
	Max	Min	Max	Min		Max	Min	Max	Min
A	1.80	---	45.7	---	G	2.53	2.47	64.3	62.7
B	.390	.370	9.91	9.40	H	2.78	2.72	70.6	69.1
C	.32	---	8.1	---	J	.63	.57	16.0	14.5
D	.166	.156	4.22	3.96	K	.93	.87	23.6	22.1
E	.890	.870	22.61	22.10	L	.28	.22	7.1	5.6
F	.890	.870	22.61	22.10	M	.23	.17	5.8	4.3

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (in millimeters) are given for general information only (1.00 inch = 25.4 mm).
3. Corners of case may be round or square.
4. Unless otherwise specified, tolerances are ± .010 (± 0.25 mm) for three place decimals and ± .03 (±0.8 mm) for two place decimals.

FIGURE 7. PIN M3928/10-12.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:16Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical and performance characteristics.

PIN M3928/10-	Fig. No.	Housing	Config.	Manual or remote	Solenoid or motor	Fail-safe or latching	Frequency range dc to GHz	VSWR	Insertion loss (dB)	Isolation (dB)	Switching time (ms)	Position indicating circuit	Life cycles x 1000	Operating voltage	Pick-up voltage	Drop-out voltage	Operating current (A) 1/	Holding current fail-safe type 1/ (A)	Power and indicator connector	Weight (oz) 2/
								max	max	min	max			nom	max	min	max			max
01N, S	1	O	1P2T	R	S	F	5.2	1.4:1	0.48	25	20	None	1000	110 V dc	84 V dc	10 V dc	0.2	0.2	Solder terminals	8 (227)
02N, S 3/	1	O	1P2T	R	S	F	5.2	1.4:1	0.48	25	20	None	1000	28 V dc	18 V dc	3 V dc	0.2	0.2	Solder terminals	8 (227)
03N, S 3/	1	O	1P2T	R	S	F	5.2	1.4:1	0.48	25	20	None	1000	115 V ac	93 V ac	5 V ac	0.2	0.2	Solder terminals	8 (227)
04N, S	2	E	1P2T	R	S	F	12.4	1.5:1	0.5	60	50	None	100	28 V dc	18 V dc	3 V dc	0.8	0.4	Solder terminals	8 (227)
05N, S	3	E	1P2T	R	S	F	12.4	1.5:1	0.5	60	50	Yes	100	28 V dc	18 V dc	3 V dc	0.8	0.4	Solder terminals	8 (227)
06N, S	4	H	1P2T	R	S	F	12.4	1.5:1	0.5	25	20	None	50	28 V dc	20 V dc	14 V dc	1.0	0.5	see Fig 4	12 (342)
07N, S	5	H	TR	R	S	F	12.4	1.5:1 5/	0.5 6/	25 7/	20 30 4/	None	50	28 V dc	20 V dc	14 V dc	1.5	0.6	see Fig 5	16 (456)
08N, S	6	H	TR	R	S	F	12.4	1.5:1 5/	0.5 6/	60 7/	30 4/	Yes	100	28 V dc	20 V dc	14 V dc	1.0	0.3	see Fig 6	16 (456)
09N, S	2	E	1P2T	R	S	F	12.4	1.5:1 5/	0.5 6/	60 7/	50	None	100	115 V dc	95 V ac	5 V ac	0.12	.12	Solder terminals	8 (227)
10N, S	6	H	TR	R	S	L	12.4	1.5:1	0.5	60	20	Yes	100	28 V dc	20 V dc	---	0.64	---	see Fig 6	12 (342)
11N,S	6	H	TR	R	S	F	12.4	1.5:1 5/	0.5 6/	60	20	None	100	28 V dc	20 V dc	14 V dc	1.5	.25	see Fig 6	12 (342)
12N, S	7	E	1P2T	R	S	F	.96 to 1.215	1.2:1	0.3	60	30	None	100	28 V dc	20 V dc	14 V dc	0.2	0.2	Solder terminals	8 (227)

1/ At nominal operating voltage and 20°C.
2/ Mass in grams in parentheses.
3/ Open port is grounded.
4/ At low and high temperature extremes.
5/ The VSWR at .225-.400 GHz for dash numbers 06 and 07 is 1.1:1. The VSWR at .100-.500 GHz for dash number 08 is 1.15:1. The VSWR at 4 GHz for dash number 10 is 1.25:1.
6/ The insertion loss at .225-.400 GHz for dash numbers 06 and 07 is 0.1 dB. The insertion loss at .100-.500 GHz for dash number 08 is 0.15 dB. The insertion loss at 4 GHz for dash number 10 is 0.25 dB.
7/ The isolation at .225-.400 GHz for dash numbers 06 and 07 is 50 dB. The isolation at .100-.500 GHz for dash number 08 is 80 dB.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:16Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configurations: See figures 1 through 7.

RF connectors: Female connectors shall mate with type N connectors in accordance with MIL-PRF-39012/1.

Nominal impedance: 50 ohms.

Termination: Open.

RF power handling capability (average): 100 watts for dash numbers 01 through 11 and 280 watts for dash number 12.

RF connectors: Series N connectors shall mate with series N male connectors in accordance with MIL-PRF-39012/1.

Electrical and performance characteristics: See table I.

Vibration: Method I.

Operating temperature: -55 º C to +85 º C.

Part or Identifying Number (PIN): M3928/10- (dash number from table I).

TABLE II. PIN to type cross-reference.

PIN M3928/10-	Type SA- /U
01	1360
02	1361
03	1362
04	---
05	---
06	---
07	---
08	---
09	---
10	---
11	---
12	---

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:16Z
Check the source to verify that this is the current version before use.

Referenced documents: In addition to MIL-DTL-3928, this specification sheet also references MIL-PRF-39012/1.

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Army - MI
Navy - AS, MC, OS, SH
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5985-2013-002)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:16Z
Check the source to verify that this is the current version before use.