INCH-POUND

MIL-DTL-3928/16B
15 August 2001
SUPERSEDING
MIL-S-3928/16A
15 July 1988

DETAIL SPECIFICATION SHEET

SWITCHES, RADIO-FREQUENCY
TRANSMISSION LINE (COAXIAL) (ELECTRICALLY OPERATED)
CLASS 5, 1P3T

This specification is approved for use by all Departments and Agencies of the Department of Defense.

Requirements for acquiring the switch described herein shall consist of this specification and MIL-DTL-3928.



FIGURE 1. Switch configuration and schematic, PIN M3928/16-02.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:18Z
Check the source to verify that this is the current version before use.



SCHEMATIC(SHOWN IN DEENERGIZED POSITION)

Dimensions									
Letter	Inches		Millimeters		Letter	Inches		Millimeters	
	Max	Min	Max	Min		Max	Min	Max	Min
A	1.60	---	40.64	---	H	2.34 dia	2.28 dia	59.4 dia	57.9 dia
B	.260	.240	6.60	6.10	J	1.380	1.370	35.05	34.80
C	.62	.56	15.7	14.2	K	.697	.677	17.70	17.20
D	.34	.28	8.6	7.1	L	1.072 dia	1.052 dia	27.22 dia	26.72 dia
E	.130	.120	3.30	3.05	M	.885	.865	22.48	21.97
F	1.560 dia	1.556 dia	39.62 dia	39.52 dia	N	1.78	1.72	45.2	43.7
G	.154 dia	.139 dia	3.91 dia	3.53 dia					

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only (1.00 inch = 25.4 mm).
3. Metric equivalents are in parentheses.
4. Unless otherwise specified, tolerances are ± .010 (± 0.25 mm) for three place decimals and ± .03 (±0.8 mm) for two place decimals.
5. Round corners of case may be squared.

FIGURE 1. Switch configuration and schematic, PIN M3928/16-02 - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:18Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical and performance characteristics.

PIN M3928/16-2/	Fig. No.	Housing	Frequency range dc to GHz	VSWR	Insertion loss (dB)	Isolation (dB)	Switch time (ms)	Position indication circuit and rating	Life cycles x 1000	Fail-safe or latching	Operating current (A) 1/	Holding current (A) 1/	Nominal operating voltage	Pickup voltage	Dropout voltage	Power and indicator connector	Weight (oz)
				Max	Max	Min	Max				Max	Max					Max
02 N, S	1	I	18	1.3:1 at 8 GHz 1.5:1	0.3 8 GHz 0.5 at 18 GHz	60	20	None	1000	None	17	17	28 V dc	20 V dc	16 V dc	RTKO7-87P (Deutsch) or equal	7

1/ PIN M3928/16-01 is deleted from this specification, there are no requirements for this item.

2/ At 28 V dc and 20 deg C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:18Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configurations: See figure 1.

Termination: Open.

Nominal impedance: 50 ohms.

RF connectors: Female connectors (4 places) shall meet the requirements of MIL-PRF-39012 and shall mate with SMA type male connectors in accordance with MIL-PRF-39012/55.

Electrical and performance characteristics: See table I.

RF power handling capability (average): 25 watts (minimum).

Operating temperature: -54 deg C to +85 deg C.

Vibration: Method I.

Part or Identifying Number (PIN): M3928/16- (and dash number from table I).

Revision letters are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - MI
Navy - AS, MC, OS, SH
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5985-1209-07)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:18Z
Check the source to verify that this is the current version before use.