00-B-580D
December 23, 1986
SUPERSEDING
00-B-580C
December 29, 1980

# FEDERAL SPECIFICATION

## BORING MACHINES, ENGINE CYLINDER (PORTABLE)

This specification is approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration, for the use of all Federal agencies.

## 1 SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers two sizes of portable boring machines for reboring engine cylinders.

1.2 Classification.

1.2.1 Sizes. The boring machines covered by this specification shall be of the following sizes as specified (see 6.2):

Size 1 - Cylinder diameters 2-5/8 through 5-1/4 inches and a length of 12-1/2 inches.
Size 2 - Cylinder diameters 3-1/2 through 7-1/2 inches and a length of 18 inches.

## 2 APPLICABLE DOCUMENTS

2.1 Government publications. The issues of the following documents, in effect on date of invitation for bids or solicitation for offers, form a part of this specification to the extent specified herein.

Federal Specifications

CC-M-1807 - Motors, Alternating Current, Fractional and Integral Horsepower (500 HP and Smaller)

Federal Standards

FED-STD-H28 - Screw-Thread Standards for Federal Services
FED-STD-123 - Marking for Shipment (Civil Agencies)

FSC 4910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and handbooks as outlined under General Information in the Index of Federal Specifications and Standards. The index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

(Single copies of this specification and other Federal specifications and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.)

(Federal Government activities may obtain copies of Federal specifications, standards, and handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications

MIL-T-152 - Treatment, Moisture- and Fungus-Resistant, of Communications, Electronic, and Associated Electrical Equipment
MIL-V-173 - Varnish, Moisture- and Fungus-Resistant (For Treatment of Communications, Electronic, and Associated Equipment)
MIL-M-18058 - Machinery, Metal and Woodworking, Preparation for Delivery of

Military Standards

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-130 - Identification Marking of US Military Property
MIL-STD-681 - Identification Coding and Application of Hookup and Lead Wire
MIL-STD-889 - Dissimilar Metals

(Copies of military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Federal Regulation

Occupational Health and Safety Administration (OSHA) 29 CFR 1910.211-222 Machinery and Machine Guarding

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

(Copies of OSHA standards and the standards which are incorporated by reference may be examined at the National Office of the Occupational Safety and Health Administration, US Department of Labor, Washington, DC 20210.)



Source: https://assist.dla.mil -- Downloaded: 2026l0-26T11:59Z
Check the source to verify that this is the currentversion before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Gear Manufacturers Association (AGMA):

AGMA 360.02 - Manual for Machine Tool Gearing
AGMA 390.03 - Gear Handbook, Volume 1, Gear Classification, Materials, and Measuring Methods for Unassembled Gears

(Application for copies should be addressed to the American Gear Manufacturers Association, 1901 North Fort Myer Drive, Arlington, VA 22209.)

American Society for Testing and Materials (ASTM):

ASTM E18 - Rockwell Hardness and Rockwell superficial Hardness of Metallic Materials
ASTM E380 - Metric Practice
ASTM D3363 - Film Hardness by Pencil Test
ASTM D3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

International Organization for Standardization (ISO):

ISO 54 - Cylindrical Gears for General Engineering and for Heavy Engineering - Modules and Diametral Pitches
ISO 1122 - Glossary of Gears - Part 1: Geometrical Definitions

(Application for copies should be addressed to the American National Standard Institute, Inc., 1430 Broadway, New York, NY 10018.)

National Fire Protection Association (NFPA), Standard:

NFPA 70 - National Electrical Code
NFPA 79 - Electrical Standard for Metalworking Machine Tools and Plastics Machinery

(Application for copies should be addressed to the National Fire Protection Association, 60 Batterymarch Street, Boston, MA 02110.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

## 3 REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3 and 6.2).



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.2 Design. The boring machines shall be new and of the manufacturer's latest design that meets the performance and product characteristics requirements of this specification (see 3.4). All parts subject to wear, breakage, or distortion shall be readily accessible for adjustment and replacement. An operation shall be defined as one complete pass.

3.2.1 Material. Materials not specifically designated herein or in the contract shall be of a quality commensurate with commercial practice within the boring machine industry, shall be suitable for the intended purpose in the design of the end item, and shall meet all requirements specified herein. Materials shall be free from defects which would adversely affect the performance or maintainability of the individual components or the overall assembly. It shall not be permissible to use reclaimed parts as is, or rebuilt from scrap or other used equipment. When dissimilar metals are used in contact with each other, suitable protection against galvanic corrosion shall be applied in accordance with MIL-STD-889.

3.3 Construction. The boring machines shall be complete so that when installed they can be used for the operations specified herein.

3.3.1 Castings and forgings. All castings shall be free from blow-holes, porosity, hard spots, shrinkage defects, cracks, or other defects. Forgings shall be free from scale, inclosure, cold shuts, excessive mismatching, and other defects that may affect their structural strength. The casting's strength, and other essential properties, shall be adequate to meet the performance requirements specified herein.

3.3.2 Welding, brazing and soldering. Welding, brazing and soldering shall be of a quality which shall sustain the performance requirements of the welded, brazed or soldered part. These operations shall not be employed as repair measures for defective parts.

3.3.3 Fastening devices. All screws, pins, bolts, and similar parts shall be installed with means for preventing loss of tightness. All such parts, when subject to removal or adjustment, shall not be swaged, peened, staked, or otherwise deformed.

3.3.4 Threads. Threads shall conform to FED-STD-H28 and the applicable Detailed Standard section referenced therein.

3.3.5 Gears. All gears and pinion designs selected for use in the boring machine or its components shall be manufactured to either English (USA) standard inch diametral pitch per AGMA 360.02 and AGMA 390.03 or Metric (SI) module ratio per the International Organization for Standardization (ISO) ISO 54 and ISO 1122 and ASTM E380. All gears shall be hardened and ground steel. Gear hardness shall be not less than Rockwell C-45 as determined in accordance with ASTM E18.

3.3.6 Lubrication. All bearings (except sealed, permanently lubricated type), mating gears, and other moving parts shall be provided means to assure adequate lubrication. Recirculating systems shall include filters which are cleanable or replaceable. Each lubricant reservoir shall have means for determining fluid levels. Oil holes, grease fittings, and filler caps shall be located to be accessible. The manufacturer shall include and install all lubricants, fluids, greases, and other compounds in accordance with the best commercial practice of the producing industry. The lubrication systems shall be temporarily capped or stopped to prevent loss of lubricants during shipment. The manufacturer shall include a warning notice in the instruction manual to remove the temporary caps or stoppers before start-up or use of the boring machine.



Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the currentversion before use.

3.3.7 Safety devices. Safety devices shall be provided for parts that present safety hazards to personnel. Safety devices shall not interfere with the operation of the machine or with the operator's performance.

3.3.7.1 Occupational safety standard. The product shall comply with OSHA standards set forth in 29 CFR 1910.211-222 with respect to machinery protection.

3.3.8 Interchangeability. All parts shall be manufactured to definite standards, clearances, and tolerances in order that any such parts of a particular type or model may be replaced, interchanged, and adjusted without modification of the replacement parts or any other parts of the unit. When practical, all parts shall be permanently and legibly marked in accordance with MIL-STD-130.

3.3.9 Gages. Gages and indicating dials shall be graduated using the inch system.

3.3.10 Plates. Instruction and identification plates shall be made of a corrosion resistant material and securely attached to the equipment. All wording shall be in the English language, unless otherwise specified, using plain bold faced letters. Lettering shall be permanently marked and have a contrasting background.

3.3.11 Lifting provisions. Where suitable boring machine surfaces are not available for shop hoist handling, a lifting eye or hook shall be provided. The eye or hook shall have an inside diameter of not less than 2 inches and a lifting capacity of three times the weight of the boring machine.

3.4 Performance and product characteristics.

3.4.1 Capacity.

3.4.1.1 Size 1. The size 1 boring machine shall be capable of boring cylinder diameters in a minimum size range of 2-5/8 through 5-1/4 inches and lengths up to at least 12-1/2 inches.

3.4.1.2 Size 2. The size 2 boring machine shall be capable of boring cylinder diameters in a minimum size range of 3-1/2 through 7-1/2 inches and lengths up to at least 18 inches.

3.4.2 Depth of cut. The boring machines shall be capable of producing a rough-cut depth of 0.040 inch and a finish-cut depth of 0.015 inch in cast iron with a Rockwell C hardness of at least 32, and a rough-cut depth of 0.020 inch and finish-cut depth of 0.008 inch in steel with a Rockwell C hardness of at least 51. Each depth of cut specified above shall be accomplished in a single pass. The hardness of the material to cut shall be determined in accordance with ASTM E18.

3.4.3 Accuracy. When the boring machine is operated at the finish-cut depth in 3.4.2, the finished bore shall be within the following limits:

| | |
|---|---|
| Diameter: | ± 0.001 inch; |
| Taper: | 0.001 inch in maximum length bore; |
| Out-of-Roundness: | 0.001 inch; |
| Surface Roughness: | 63 microinches, arithmetical average. |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.5 Details of components. The boring machines shall consist of, but not be limited to, the following principal components.

3.5.1 Mounting devices. Mounting devices shall be provided to anchor the boring machines securely to a cylinder block and shall incorporate means for accurate positioning of the spindle relative to the mean center of the cylinder to be bored.

3.5.2 Boring column. The boring column shall contain the spindle in 3.5.3. The boring column shall support and guide the spindle and tool holder to perform the boring operations specified in 3.4.

3.5.3 Spindle. The spindle shall be mounted in the boring column on bearings designed to withstand radial and thrust loads. Combination or separate radial and thrust bearings may be used. When specified (see 6.2), the spindle shall have provisions for a vacuum unit to trap and remove cuttings.

3.5.4 Spindle drive. The spindle drive shall be a positive type and shall provide the speeds and power feeds necessary to produce bores in accordance with the requirements of 3.4.2.

3.5.5 Controls. Manual controls shall be provided to change the feed and speed, to engage and disengage the power feed, and to position the spindle. A variable automatic stop shall be incorporated to limit the length of spindle travel.

3.5.6 Tool holder. The tool holder mounted on the spindle head shall provide quick and positive micrometer adjustment of the cutting tool(s) to any cutting diameter within the capacity of the boring machine. When specified (see 6.2), the tool holder shall have provisions to permit use of a vacuum pickup (see 3.5.3).

3.5.7 Tool sharpener. Tool sharpening facilities shall be incorporated as a part of the machine and shall be capable of producing a cutting edge of the proper form, rake, and clearance.

3.5.8 Carrying case. A carrying case made of wood or steel shall be furnished with each boring machine. The case shall be designed to contain, protect, and carry the boring machine with its component parts, equipment, tools, and spare parts. The carrying case shall be fitted with a hinged lid embodying positive acting latches. The carrying case shall have a carrying handle or handles suitable for man handling or sling handling.

3.5.9 Electrical equipment.

3.5.9.1 Motors. Unless otherwise specified (see 6.2), the motor shall be a squirrel-cage induction type, not less than 1/2 horsepower and operate on 115 volt, 60 hertz, single phase current, continuous duty rating and shall conform to the requirements of CC-M-1807 with class B insulation. The motor shall have a heavy-duty toggle switch and shall have thermal overload protection.

3.5.9.2 Electrical components. Electrical components of the boring machines, including starters, relays, switches, wiring, and their inclosures, shall conform to and shall be located in accordance with NFPA 79, except as specified herein. There shall be no component part used in any application where the manufacturer's rating for the part does not meet or exceed the requirements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.5.9.3 Power cord. Unless otherwise specified (see 6.2), each boring machine shall be furnished with not less than 8 feet of 3-wire No. 14 AWG, NFPA 70, type SO heavy duty, power cord. The cord shall be provided with a 3-prong grounding type connector plug of either the grip cord type or molded on type.

3.5.9.4 Color coded electrical circuitry. The wiring in the electrical system shall have individual point-to-point color coded wires in accordance with System II requirements of MIL-STD-681. The electrical system diagram/schematic furnished with each boring machine shall be an exact duplicate of the electrical system and wiring in the boring machine. The diagram/schematic shall positively identify the individual point-to-point color coded wires and wire termination points in the electrical system.

3.6 Fungus control. Components of electrical circuitry that are hermetically sealed or inherently resistant to fungus growth and moisture need not be treated. Components of electrical circuitry that are not inherently resistant to fungus growth or moisture shall be treated in accordance with MIL-T-152 and MIL-V-173.

3.7 Standard equipment. Unless otherwise specified (see 6.2), the following standard equipment shall be provided with each boring machine:

(a) Two complete sets of carbide tools.
(b) Micrometer with the required tools and attachments for measuring, calibrating, and positioning the cutter tools for boring and sharpening operations.
(c) Lapping compound and lap impregnate.

3.8 Painting. Unless otherwise specified (see 6.2), painting and finishing shall be in accordance with the best commercial practice in the industry. Before painting, all surfaces to be painted shall be clean and free of all foreign matter detrimental to painting. The paint coating shall be not less than 2.0 mil in thickness. The paint adhesion shall be such that no point shall be peeled by fiberglass tape when two intersecting cuts expose the base metal for a distance of not less than two inches. The surface hardness of the paint shall be between paint industry standards H to HB as determined in accordance with ASTM D3363.

3.9 Identification of product.

3.9.1 For military agencies. The boring machines shall be marked for identification in accordance with MIL-STD-130, including the National Stock Number.

3.9.2 For Civil agencies. A noncorrosive metal nameplate securely attached to each boring machine shall be permanently marked with the name or trademark of the manufacturer and the capacity of the equipment.

3.10 Workmanship. Standards of workmanship shall assure that the boring machine shall have the stability, strength, safety, and efficient operating characteristics found in the best commercial units and as specified in Section 3.

## 4 QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspection. The requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 First article inspection. First article inspection shall be applied to the preproduction model or initial production item noted in 3.1. Unless otherwise specified (see 6.2), first article inspection shall consist of the examination of one complete boring machine in accordance with product examination (see 4.6) and all tests under 4.7. Failure of the first article to pass the examination or any of the tests shall be cause for rejection.

4.4 Quality conformance inspection. Unless otherwise specified (see 6.2), quality conformance inspection shall be applied to production units offered for acceptance under the contract and shall consist of (a) through (c) below. Failure of any unit to pass an examination, test, or inspection shall be cause for rejection of the unit.

(a) Examination (see 4.6).
(b) Tests (see 4.7).
(c) Packaging inspection (see 4.8).

4.5 Sampling. Unless otherwise specified (see 6.2), sampling for quality conformance inspection shall be in accordance with MIL-STD-105, using the following Inspection Levels and Acceptable Quality Levels (AQL):

| Examination/Inspection | Inspection Level | AQL |
|---|---|---|
| Product examination (see 4.6) | II | 1.0 |
| Performance test (see 4.7.1) | II | 1.0 |
| Lifting test (see 4.7.2) | II | 1.0 |
| Paint test (see 4.7.3) | S-4 | 1.0 |
| Packaging inspection (see 4.8) | S-4 | 4.0 |

4.6 Product examination. Visually and manually examine the boring machine to determine conformance with the requirements of 3.2 through 3.3.11 and 3.5 through 3.10. Visual examinations shall include verification of completeness of manufacture and assembly, conformance to specified standards, adequacy of markings, proper cleaning, and freedom from the identified defects. Manual examinations shall include the operation of movable parts by hand to assure proper functioning. Inspections (examination) shall be performed during the manufacturing process to the extent



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

necessary to assure end item conformance; however, acceptance inspection shall be performed on completely finished (assembled) boring machines. Failure of the contractor to provide objective evidence that the machine and its components have passed the examinations prescribed for them by the contractor's inspection system shall be cause for rejection.

4.7 Tests.

4.7.1 Performance test. In conformance with the manufacturer's instructions, the boring machines shall be installed on an applicable engine cylinder block or a mockup and adjusted to rebore the cylinder to a preset oversize. Following the boring operations the rebored cylinders shall be checked for accuracy and surface finish to determine compliance with the limits specified in 3.4.3 and accuracy of mounting (see 3.5.1).

4.7.1.1 Size 1. The size 1 boring machine shall rebore cylinders in the following size to determine conformance to 3.4.1.1 and 3.4.2.

(a) One cylinder 12-1/2 inches long with a nominal diameter of 5-1/4 inches in cast iron.
(b) One cylinder 12-1/2 inches long with a nominal diameter of 5-1/4 inches in steel.

4.7.1.2 Size 2. The size 2 boring machine shall rebore cylinders in the following size to determine conformance to 3.4.1.2 and 3.4.2.

(a) One cylinder 18 inches long with nominal diameter of 7-1/2 inches in cast iron.
(b) One cylinder 18 inches long with a nominal diameter of 7-1/2 inches in steel.

4.7.2 Lifting test. If a lifting eye or hook is provided (see 3.3.11), attach a hoist and weigh the boring machine with accessories attached. Add weight to obtain three times normal weight. There shall be no damage to boring machine or lifting parts when lifting three times the weight of the boring machine.

4.7.3 Paint test. The hardness, adhesion and thickness of the paint used on the boring machine shall be checked as follows:

(a) The graphite point of a sharpened HB lead pencil shall be pressed at a right angle into a painted area of the boring machine until the graphite crumbles. Failure of the surface to withstand the test, as evidenced by a pitting of the paint, shall be cause for rejection.
(b) The test sample of the same metal painted with the same process and at the same time as the boring machine shall have a sharpened H lead pencil pressed into the paint as in (a). Failure of the surface to pit (paint too hard) shall be cause for rejection.
(c) Two, 2 inch intersecting lines shall be cut through the paint to the base metal of the test sample. A strip of 1/2 inch wide fiberglass tape shall be firmly pressed over the intersection and then pulled from the surface. Adhesion of any paint to the tape shall be cause for rejection.
(d) Using a paint thickness measuring instrument, or by masking a portion of the test sample during painting, measure the thickness of the paint. Failure of the paint to be at least 0.0020 inch thick shall be cause for rejection.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

4.8 Packaging inspection. Packaging inspection shall be conducted before and after packaging to determine compliance with the requirements of Section 5.

5 PREPARATION FOR DELIVERY

5.1 Military preservation, packing and marking. When specified (see 6.2), requirements for Level A preservation; Level A or B packing; and military marking shall be in accordance with MIL-M-18058.

5.2 Industrial preservation, packing and marking. Unless otherwise specified (see 6.2), preservation, packing and marking shall conform to the requirements of ASTM D3951.

5.3 Marking for civil agencies. When specified (see 6.2), marking for shipment for civil agencies shall be in accordance with FED-STD-123.

6 NOTES

6.1 Intended use. The boring machines covered by this specification are intended for use in the base and field shops for reboring engine cylinders.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Size required (see 1.2.1).
(c) First article, when specified (see 3.1).
(d) Spindle vacuum pickup provision, when specified (see 3.5.3).
(e) Tool holder vacuum pickup provision, when specified (see 3.5.6).
(f) Horse power rating, operating voltage, frequency and phase, if different (see 3.5.9.1).
(g) Power supply cord and plug connector, if different (see 3.5.9.3).
(h) Standard equipment, if different (see 3.7).
(i) Painting, if different (see 3.8).
(j) First article inspection, if different (see 4.3).
(k) Quality conformance inspection, if different (see 4.4).
(l) Sampling, if applicable (see 4.5).
(m) Military preservation, packing and marking, when required (see 5.1).
(n) Industrial preservation, packing and marking, when required (see 5.2).
(o) Civil agency shipment marking, when required (see 5.3).

6.3 Contract data requirements. Required technical data such as operator's manuals, parts lists, and other instructions for operation and maintenance, as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated into the contract.

6.4 OSHA standards. Products which meet all requirements of this specification comply with the OSHA standards published prior to the date of this specification and identified in Section 3 (see 3.3.7.1).

MILITARY INTERESTS:

Custodians

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA-FSS



Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the current version before use.

Army - AL
Navy - YD
Air Force - 99

Review Activities

Army - SM
Navy - SH
Air Force - 82

User Activities

Army - ER
Navy - MC

PREPARING ACTIVITY:

Army - AL

DoD Project 4910-0608



Source: https://assist.dla.mil -- Downloaded: 202640-26T11:59Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314




OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament Research and Development
Engineering Center
ATTN: SMCAR-EST-S
Rock Island, IL 61299-7300

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

OO-B-580D Boring Machines, Engine Cylinder (Portable)

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.