FEDERAL SPECIFICATION

DRYCLEANING FINISHING EQUIPMENT, MISCELLANEOUS

This amendment which forms a part of Federal Specification 00-D-735C, dated January 11, 1973, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 2

2.1, under "Federal Specifications": Delete "CC-M-636" and "CC-M-641" in their entirety and substitute "CC-M-1807 Motors, Alternating Current, Fractional and Integral Horsepower (500 Horsepower and Smaller)."

PAGE 3

Under "Military Standards": Add "MIL-STD-1474 - Noise Limits for Army Material".

PAGE 4

2.2, under "American Society for Testing and Materials (ASTM) Standards".

Delete lines 2, 3, 4 and 5 and substitute "A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet and Strip" and "A 176 - Stainless and Heat-Resisting Chromium Steel Plate, Sheet and Strip."

PAGE 5

3.5.1, line 3: Delete "A167-70" and "A176-71" and substitute "A 167" and "A 176" respectivelv.

PAGE 6

3.5.5, 2nd sentence: Delete and substitute "Motors shall conform to the requirements of CC-M-1807 and to the following:"

PAGE 7

Add: "3.6.9 Noise limits. The noise limits produced by the drycleaning finishing equipment shall meet the limits specified in MIL-STD-1474 and where practicable, shall not exceed 85 decibels A-weighted at the normal operator position.

FSC 3510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

PAGE 8

3.7.1.2, 2nd and 3rd sentence: Delete and substitute "The base shall be provided with anchor bolt holes and strips of resilient material for isolation at the base from the floor. The base for class 2 units shall be equipped with vibration isolators to control the transmission of vibration energy to the floor.

PAGE 11

3.7.6, end of paragraph: Add "Unless otherwise specified (see 6.2) the spotting board shall have a central air induced vacuum system with a foot operated control valve."

PAGE 15

4.3, line 2, after "4.6.6": Add ", 4.6.8".

PAGE 18

4.4.2.3, line 3, after "4.6.6": Add "and 4.6.8"

PAGE 19

Add: "4.6.8 Noise test. The drycleaning finishing equipment shall be tested for conformance with the noise limits of 3.6.9 in accordance with MIL-STD-1474".

PAGE 20

6.2: Add "(o) when a steam venturi or steam with an electric motor for local vacuum is required for the spotting board (see 3.7.6)."

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - MD
Air Force - 45

User activity:

Navy - SH

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

DC GOVT - DCG
GSA - FSS
HEW - NIH
VA - DMS

Project No. 3510-0234

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.