00-F-586B
January 13, 1975
SUPERSEDING
Fed. Spec. 00-F-586A
December 9, 1964

FEDERAL SPECIFICATION

FORMING MACHINES, SHEET METAL, SLIP ROLL, INITIAL PINCH TYPE, POWER DRIVEN, 2 THRU 6 INCH DIAMETER ROLLS

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal Agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers power driven, slip roll forming machines of the initial pinch type. Machines covered herein are used to roll flat sheets and light metal plates into cylindrical forms.

1.1.1 Federal specification coverage. Federal specifications do not include all varieties of the commodity as indicated by the title of the specification, or which are commercially available, but are intended to cover those generally used by the Federal Government.

1.2 Classification.

1.2.1 Types and sizes. This specification covers initial pinch type slip roll forming machines of the sizes shown in table I. The size machine required for a specific procurement shall be as specified (see 6.2.1).

FSC 3441

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-M-18058 - Machinery, Metal and Woodworking, Support Equipment and Associated Repair Parts, Preparation for Delivery of

Military Standards:

MIL-STD-129 - Marking for Shipment and Storage

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

MIL-STD-130 - Identification Marking of U. S. Military Property

MIL-STD-461 - Electromagnetic Interference Characteristics Requirements for Equipment

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Occupational Safety and Health Act (OSHA) of 1970:

Title 29, Code of Federal Regulations, Chapter XVII, Part 1910, and amendments	Occupational Safety and Health Administration Standards

National Bureau of Standards (NBS) Handbook H28

Screw-Thread Standards for Federal Services

(Application for copies should be addressed to the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.)

American Gear Manufacturers Association AGMA 360

Manual for Machine Tool Gearing

(Application for copies should be addressed to the American Gear Manufacturers Association, 1330 Massachusetts Ave., NW, Washington, DC 20005.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal Agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Classification of requirements. The requirements for the machine are classified herein as follows:

Requirements	Paragraph
First Article approval	3.2
General requirements	3.3
Detail requirements	3.4
Sizes & capacities	3.5
Performance requirements	3.6

3.2 First Article approval. If First Article approval is required (see 6.2.1 and 6.3). inspection therefor shall be in accordance with Section 4. A First Article comprises a preproduction model or initial production sample; approval involves testing and evaluating the First Article for conformance with the requirements herein before, or in the initial stage of, production under a contract. The approved sample shall be used as the standard for all production items manufactured to fulfill the terms of the contract.

3.3 General requirements.

3.3.1 Design. The machine shall be new and one of the manufacturer's current models capable of performing forming operations in accordance with the requirements herein. The machine shall include all components, parts, and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement, and repair.

3.3.2 Controls. All operating controls shall be located convenient to the operator at his normal work station.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the currentversion before use.

3.3.3 Safety and health requirements. Covers or other safety devices shall be provided for all parts of the machine presenting safety hazards which can be guarded without substantial interference to operation of the machine. All guards shall be removable to provide access to guarded parts. Except as otherwise specified by the procuring activity, the machine shall comply with the standards promulgated under OSHA applicable to the machine itself. Exceptions and additional requirements for safety and health shall be as specified (see 6.2.1 and 6.4).

3.3.4 Lubrication. Means shall be provided to insure adequate lubrication to all moving parts. All oil holes, grease fittings, and filler caps shall be easily accessible.

3.3.5 Interchangeability. All parts subject to replacement shall be manufactured to definite dimensional and tolerance standards which will permit installation of replacement parts without modification of the part or the machine.

3.3.6 Construction. The machine shall be constructed of parts which are new, without defects and free of repair. The structure shall be capable of withstanding all forces encountered during operation of the machine at its maximum rating and capacity without permanent distortion.

3.3.7 Castings and forgings. All castings and forgings shall be free of scale and mismatching. No process such as welding, peening, plugging, or filling with paste shall be used for reclaiming any defective part.

3.3.8 Welding, brazing, or soldering. Welding, brazing or soldering shall be used only where specified in the original design. None of these operations shall be employed as a repair measure for any defective part.

3.3.9 Fastening devices. All screws, pins, bolts, and other fasteners shall be installed in a manner to prevent change of tightness. Those subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently installed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.3.10 Surfaces. All surfaces shall be cleaned and free of sand, dirt, fins, sprues, flash, scale, flux, and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be in accordance with the manufacturer's commercial practice.

3.3.11 Painting. Unless otherwise specified (see 6.2.1), the machine shall be painted in accordance with the manufacturer's commercial practice.

3.3.12 Threads. All threaded parts shall be in the inch system and in accordance with NBS H28.

3.3.13 Plates. All words on instruction and indicating plates shall be in the English language. Characters shall be engraved, etched, embossed or stamped in boldface on a contrasting background.

3.3.14 Gears. All gears used in the machine and its components shall be machined in the inch system and shall conform to the applicable requirements of AGMA 360.

3.3.15 Fungus control. When required (see 6.2.1), fungus proofing shall be as specified.

3.3.16 Lubrication chart or plate. Unless otherwise specified (see 6.2.1), a lubrication chart or plate shall be permanently and securely attached to each machine. If a chart is furnished, it shall be placed in a transparent plastic folder, or permanently sealed between clear plastic sheets, with suitable means for mounting. The following information shall be furnished on the chart or plate:

Points of application

Service interval

Type of lubricant

Viscosity

Military or Federal Specification covering lubricants

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:59Z
Check the source to verify that this is the currentversion before use.

If there are no points on the machine requiring lubrication, the chart or plate shall be inscribed "No lubrication required" in lieu of the information required above.

3.3.17 Nameplate. Unless otherwise specified (see 6.2.1), a corrosion-resistant metal nameplate, marked in accordance with MIL-STD-130, shall be securely attached to each machine. The nameplate shall contain the information listed below. If the machine is a special model, the model designation shall include the model of the basic standard machine and a suffix identified in the manufacturer's permanent records.

Nomenclature

Manufacturer's name

Manufacturer's model designation

Manufacturer's serial number

Power input (volts, total amps, phase, frequency)

Date of manufacture

Contract Number or Order Number

Federal Stock Number, National Stock Number, or Plant Equipment Code

U S

3.3.18 Technical data. Technical data shall be furnished as specified (see 6.2.2).

3.3.19 Workmanship. Workmanship of the machine and accessories shall be of a quality equal to that of the manufacturer's commercial equipment of the type specified herein.

3.4 Detailed requirements.

3.4.1 Base and frames. The machine shall have either a cast or fabricated base and end frames. The base and frames shall have

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:59Z
Check the source to verify that this is the currentversion before use.

adequate strength and rigidity to support the working parts of the machine, and maintain all parts in alignment, while the machine is operating at its maximum rated capacity. When components are installed within the base and frame structure, access openings shall be provided for maintenance of these components. Means shall be provided for securely fastening all attachments to the machine and for securely fastening the machine to the floor or a foundation.

3.4.2 Rolls. The machine shall have three rolls, two adjustable and one non-adjustable. The rolls shall be arranged in a triangular form and shall be made from steel, adequate in size and processed in such a manner that will provide them with a surface that will not be easily marred and enable them to withstand all forces applied while forming workpieces of capacity width and thickness. Rolls 4 inches and smaller in diameter shall have three circular grooves at the right hand end of the bottom and rear rolls which shall permit forming workpieces with wired or flanged edges. The width of the circular grooves shall be 3/16, 1/4, and 5/16 (all $\pm$ 1/64) inches for 2 inch diameter rolls, and 3/8, 1/2, and 5/8 (all $\pm$ 1/64) inches for 3 and 4 inch diameter rolls. When specified (see 6.2.1), rolls larger than 4 inches in diameter shall also have circular grooves of the quantity and width specified. In addition, the rear roll of all size machines shall have one or more longitudinal grooves extending across the entire width of the roll to enable the roll to quickly pick up the workpiece as it leaves the pinch rolls. The width and depth of the grooves shall be of a size suitable for workpieces of the thickness shown under "Capacity" in table I. When specified (see 6.2.1), the lower front roll shall be grooved as described above to facilitate picking up the workpiece when it is fed from the rear of the machine to pre-roll the leading edge.

3.4.3 Roll adjustments. The top roll shall rotate on bearings that are attached at a fixed, non-adjustable location on the machine frame and dropend. The bottom roll and the rear roll shall rotate on bearings that can be relocated by adjustments as described in 3.4.3.1 and 3.4.3.2.

3.4.3.1 Bottom roll adjustment. The position of the lower roll shall be adjustable in relation to the top roll to provide adequate pinch force for rolling all gauges of sheet or light plate up to the thickness shown as "Capacity" in table I. The position of the roll and its bearings shall be manually adjustable by means of a

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

handwheel operated screw mechanism, or similar means, located at each end of the roll. The screw mechanism shall be of the type that will automatically hold its adjusted position, or a locking device shall be provided to retain the adjustment.

3.4.3.2 Rear roll adjustment. The position of the rear roll, and its bearings, shall be adjustable in relation to the pinch rolls for rolling any desired cylinder diameter within the cylinder diameter range specified in 3.6. Unless otherwise specified, the rear roll, and its bearings, shall be manually adjusted using a jacking screw type mechanism located at each end of the roll. The screw mechanism may be individually operated by handwheels, or arranged in such a manner that both screws are simultaneously operated by a single handwheel, keeping the rear roll parallel to the pinch rolls at all times. Single handwheel operated simultaneous adjustment mechanisms shall have a clutch or coupling that will permit one end of the roll to be independently adjusted for conical forming. When specified (see 6.2.1) the rear roll shall be adjusted by an electric motor driven screw-mechanism which shall simultaneously position both ends of the roll. The electric motor driven mechanism shall also have a clutch or coupling which will permit one end of the roll to be independently adjusted for conical forming. All adjusting mechanisms shall have a roll position indicator scale to assist the operator in making duplicate and parallel settings of the rolls.

3.4.4 Cone rolling attachment. When specified (see 6.2.1), the machine shall have a cone rolling attachment for forming conical shapes. The cone rolling attachment shall consist of a hardened steel roller, pin, or similar device, readily attachable to and easily removable from the right hand end of the machine. The attachment shall retard the right hand edge of the workpiece as it passes between the pinch rolls, thereby producing a conical shape.

3.4.5 Roll drive. The rolls shall be driven by an electric motor through a gear reduction unit that provides the rolling speed specified in table I. The rolls shall be gear driven with the gearing connected through link arms to maintain the gears in full mesh regardless of the position of the rolls. All three rolls shall be driven on machines having rolls 3 inches in diameter and larger. When the rolls are less than 3 inches in diameter, only the pinch rolls (top roll and lower front roll) are required to be powered.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the current version before use.

3.4.6 Reversing mechanism. The machine shall have a means for reversing the direction of rotation of the rolls. Reversing may be accomplished by reversing the rotational direction of the drive motor or any other suitable method.

3.4.7 Latching mechanism. (Free end of top roll) The machine shall have a mechanism for supporting and locking into position the free end of the top roll during forming operations and permitting the top roll to be raised, or swung out, for removal of the finished workpiece. Machines having rolls 4 inches or smaller in diameter may use either a hand operated latching lever type mechanism, or the drop-end type mechanism described below. When the latching lever type mechanism is used, it shall securely hold the end of the roll in position during the rolling operation and shall permit the roll to swing forward for removing the finished workpiece. When a drop-end type mechanism is used, the drop-end shall hinge on the base and frame of the machine and shall have sufficient strength and rigidity to support the end of the top roll when the machine is operating at its maximum rated capacity. The drop-end shall be connected to the drive end of the top roll in such a manner that when the drop-end is lowered, the free end of the top roll will be raised to facilitate removal of the workpiece. The drop-end shall have a latching mechanism which securely latches the drop-end in position while the workpiece is being formed. Unless otherwise specified, the drop-end shall be manually raised and lowered. When specified (see 6.2.1), the drop-end shall be raised and lowered by a pneumatic cylinder operated from a 90 to 120 psi shop air supply. When the drop-end is pneumatically operated, the machine shall be furnished with all the necessary control valves, pressure regulator, filter, hoses, and piping required.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:59Z
Check the source to verify that this is the currentversion before use.

TABLE I. Size and capacity

SIZE	ROLLS		CAPACITY		Drive Motor Horsepower	Rolling Speed, Feet per Minute
	Diameter, inches	Effective Working Length, inches	U. S. Standard Gage	Decimal Equivalent		
2-12	2	12	16	0.0598	1/3	16
2-18	2	18	18	0.0478	1/3	16
2-24	2	24	20	0.0359	1/3	16
2-30	2	30	22	0.0299	1/3	16
2-36	2	36	22	0.0299	1/3	16
2-42	2	42	24	0.0239	1/3	16
3-36	3	36	14	0.0747	3/4	16
3-42	3	42	15	0.0673	3/4	16
3-48	3	48	16	0.0598	3/4	16
3-60	3	60	20	0.0359	3/4	16
4-36	4	36	10	0.1345	1-1/2	15
4-48	4	48	12	0.1046	1-1/2	15
4-60	4	60	14	0.0747	1-1/2	15
4-72	4	72	16	0.0598	1-1/2	15
4-96	4	96	20	0.0359	1-1/2	15
5-36	5	36	3/16 inch	0.1875	3	15
5-48	5	48	8	0.1644	3	15
5-60	5	60	10	0.1345	3	15
5-72	5	72	12	0.1046	3	15
5-96	5	96	16	0.0598	3	15
6-48	6	48	1/4 inch	0.2500	5	16
6-60	6	60	3/16 inch	0.1875	5	16
6-72	6	72	10	0.1345	5	16
6-96	6	96	12	0.1046	5	16
6-120	6	120	14	0.0747	5	16

Requirements are not less than those shown.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.4.8 Electrical system. Unless otherwise specified (see 6.2.1), the electrical system shall be in accordance with this paragraph. The system shall be in accordance with the applicable requirements of JIC Electrical Standards for General Purpose Machine Tools. Each machine shall draw all of its electrical power from a single 230/460 volt, 3 phase, 60 Hz circuit fed through a fused safety disconnect switch. The machine shall be initially wired for operation on 230 volts. An identified terminal for grounding the machine when installed shall be mounted in or near the disconnect switch. The terminal shall be suitable for connecting the size grounding conductor specified in Table 15-1 of JIC Standards for the disconnect fuse rating.

3.4.8.1 Motors. Motors shall have ball or roller bearings. Unless otherwise specified (see 6.2.1), each motor shall meet the requirements of a dripproof enclosure. Motor horsepower shall conform to the requirements of table I.

3.5 Size and capacity. The size and capacity shall be as shown in table I for the size machine required. The size designation represents the diameter of the rolls in inches and the working length of the rolls in inches. Capacity is based on the thickest workpiece of mild steel having a tensile strength of not less than 50,000 psi and a width not less than the working length of rolls.

3.6 Performance. The machine shall be capable of rolling flat sheet or plate of the thickness shown as capacity in table I and of a width equivalent to the working length of the rolls, into plain round cylinders having inside diameters within the following size range:

(a) Smallest diameter that can be rolled - twice the diameter of the rolls.

(b) Largest diameter that can be rolled - limited only by the space above the machine.

After rolling, the leading and trailing edges of the workpiece shall be parallel within 1/8 inch per foot of rolled cylinder length. The machine shall also be capable of pre-rolling by feeding the workpiece from the rear of the rolls, with the drive direction reversed, to preform the leading edges of the workpiece.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the current version before use.

3.7 Standard equipment. Unless otherwise specified (see 6.2.1), the machine shall be furnished with all standard equipment normally furnished by the manufacturer including one set of hand tools.

3.8 Optional equipment. Optional equipment shall be furnished as specified and fully described (see 6.2.1).

3.9 Electromagnetic interference control. When specified (see 6.2.1) equipment procured under this specification shall comply with the requirements of MIL-STD-461.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification when such action is deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First Article inspection. When First Article approval is required under 3.2, First Article inspection shall be performed. Unless otherwise specified (see 6.2.1), First Article inspection shall comprise the examination in 4.4 and all tests in 4.5. Failure of the item to pass any examination or test shall be cause for disapproval of the First Article.

4.3 Quality conformance inspection. Each item shall be subjected to quality conformance inspection prior to being offered for acceptance. Unless otherwise specified (see 6.2.1), quality conformance inspection shall consist of the examination in 4.4, the tests in 4.5.1 and the inspection in 4.6. Failure of the item to pass any examination, test, or inspection shall be cause for rejection.

4.4 Examination. The machine and equipment shall be examined to determine compliance with the requirements of 3.3 through 3.9.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the current version before use.

4.5 Tests.

4.5.1 Operational test. The machine shall be operated at no load for not less than 30 minutes, during which time the controls and all operating components shall be actuated and observed to determine that they operate properly.

4.5.2 Performance test. The machine shall be used to form a mild steel sheet or plate having a width equal to the working length of the rolls and a thickness equal to that shown as capacity in table I. After pre-rolling the edge of the workpiece from the rear of the machine, it shall be formed into a cylinder having an inside diameter not greater than two times the diameter of the top roll. The inside diameter of the formed cylinder shall not deviate from true roundness more than two percent and the leading and trailing edges shall be parallel to each other within 1/8 inch per foot of cylinder length.

4.5.3 Electromagnetic interference control test. Equipment requiring electromagnetic interference control testing shall be tested for compliance with 3.9.

4.6 Inspection of preparation for delivery. Preservation - packaging, packing, and marking shall be inspected to determine compliance with the requirements of Section 5.

5. PREPARATION FOR DELIVERY

5.1 Preservation-packaging. Preservation-packaging shall be in accordance with MIL-M-18058, at Level A or C as specified (see 6.2.1).

5.2 Packing. Packing shall be in accordance with MIL-M-18058, at Level A, B, or C as specified (see 6.2.1).

5.3 Marking. In addition to the markings specified in the procurement documents, the unit packages and shipping containers shall be marked in accordance with Federal Standard 123 for Civil agencies, and MIL-STD-129 for Military activities.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. Machines covered by this specification are intended for use in fabrication shops for forming sheet metal and light plate into cylindrical shapes. When equipped with the required attachment, they may be used for forming conical shapes.

6.2 Ordering data. Purchasers should specify their requirements in procurement documents, including whether each choice is required or not required, by entering an appropriate statement identified to each of the following:

6.2.1 Procurement requirements.

(a) Title, number, and date of this specification.

(b) Size machine required (see 1.2.1 and table I).

(c) First Article approval, if required (see 3.2).

(d) Specify exceptions and additional safety and health requirements (see 3.3.3 and 6.4).

(e) Painting, if different (see 3.3.11).

(f) Specify fungus proofing, if required (see 3.3.15).

(g) Lubrication chart or plate, if different (see 3.3.16).

(h) Nameplate, if different (see 3.3.17).

(i) Specify quantity and width of circular grooves for larger than 4 inch diameter rolls, if required (see 3.4.2).

(j) Specify whether longitudinal grooves are required in lower front roll (see 3.4.2).

(k) Specify whether power adjusted rear roll is required (see 3.4.3.2).

(l) Cone rolling attachment, if required (see 3.4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

(m) Specify whether pneumatically operated drop-end is required (see 3.4.7).

(n) Electrical system, if different (see 3.4.8).

(o) Motor enclosure, if different (see 3.4.8.1).

(p) Standard equipment, if different (see 3.7).

(q) Optional equipment, if required and fully described (see 3.8).

(r) Electromagnetic interference control, if required (see 3.9).

(s) First Article inspection, if different (see 4.2).

(t) Quality conformance inspection, if different (see 4.3).

(u) Required level of preservation-packaging (see 5.1).

(v) Required level of packing (see 5.2).

6.2.2 Contract data requirements. For military procurements, required technical data, such as operators manuals, parts lists, foundation and anchor bolt plans, and other instructions for operation and maintenance as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated into the contract.

6.3 First Article. When First Article approval is required under 3.2, the solicitation should include complete information concerning examination, testing, and approval. For military procurements, the solicitation should adhere to the applicable portions of Section 1, Part 19, of the Armed Services Procurement Regulation.

6.4 Occupational Safety and Health Act (OSHA). Paragraph 3.3.3 requires compliance only with OSHA requirements concerning the machine itself. These requirements include, but are not limited to, the following sections of the OSHA Standards:

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:59Z
Check the source to verify that this is the currentversion before use.

29 CFR 1910.144 - Safety Color Code for Marking Physical Hazards

29 CFR 1910.212 - General Requirements for all Machines

29 CFR 1910.219 - Mechanical Power Transmission Apparatus

Since this specification does not require compliance with OSHA requirements concerning the operating environment, procuring agencies should insert additional requirements under 6.2.1(d) that will integrate the new machine into the work environment without exceeding OSHA hazard levels. The OSHA section applicable to this specification which is pertinent to the operating environment is:

29 CFR 1910.95 - Occupational Noise Exposure

The above sections are cited to assist procuring agencies in complying with OSHA. The machine user should measure and evaluate his safety and health requirements based on the entire contents of OSHA standards.

6.5 Mercury prohibited. When the use of mercury or its compounds in the machine and its components and accessories is prohibited, procurement documents should include a statement to that effect.

MILITARY CUSTODIANS:

Army - WC
Navy - SH
Air Force - 84

Review activities:

Army - WC
Navy - SH
Air Force - 84
DSA - GS

User activities:

Army - WV

Preparing activity:

DSA - IP

Project Number:

3441-0070

U. S. GOVERNMENT PRINTING OFFICE : 1975 - 585-648/1492

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 45 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.