OO-G-681B
October 21, 1976
SUPERSEDING
Fed. Spec. OO-G-681A
October 26, 1967

FEDERAL SPECIFICATION

GRINDING MACHINES, BRAKE LINING, PORTABLE AND BENCH MOUNTED

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers two types of grinding machines used to grind the outside surface on brake-linings to fit the internal brake-drums of vehicles.

1.1.1 Federal specification coverage. Federal specifications do not include all varieties of grinding machines indicated by the title of the specification, or which are commercially available, but are intended to cover only those generally used by the Federal Government.

1.2 Classification.

1.2.1 Types and sizes. Grinding machines covered by this specification shall be of the following types and sizes, as specified (see 6.2):

Type I--Portable, axle mounting.

Size A--Brake-shoes from 8 inches through 16 inches in diameter and up to 4 inches in shoe width.

Size B--Brake-shoes from 12 inches through 24 inches in diameter and up to 8 inches in shoe width.

Type II--Bench mounted, radius-arc movement.

Size A--Brake-shoes from 8 inches through 16 inches in diameter and up to 4 inches in shoe width.

FSC 4910

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

W-C-596 - Connector, Plug, Receptacle and Cable Outlet, Electrical Power, General Specification For.

CC-M-1807 - Motors, Alternating Current, Fractional and Integral Horsepower (500HP and Smaller).

Federal Standards:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications and Standards as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers, at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications and Standards, and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

MIL-T-152 - Treatment, Moisture- and Fungus-Resistant, of Communications, Electronic, and Associated Electrical Equipment.

MIL-M-18058 - Machinery, Metal and Woodworking Preparation for Delivery of.

MIL-I-24092 - Insulating Varnish, Electrical, Impregnating.

Source: https://assist.dla.mil -- Downloaded: 20261O-26T12:00Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of US Military Property.
MIL-STD-461 - Electromagnetic Interference Characteristic Requirements for Equipment.
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of.
MIL-STD-826 - Electromagnetic Interference Test Requirements and Test Methods.

(Copies of Military Specifications and Standards required by contractors in connection with specified procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Laws and Regulations:

29 CFR 1910 - Occupational Safety and Health Standards.

(Application for copies should be addressed to the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

National Bureau of Standards (NBS) Handbook:

H28 - Screw-Thread Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

Underwriter's Laboratories (UL), Inc.:

UL-817 - Cord Sets and Power Supply Cords.

(Application for copies should be addressed to the Underwriter's Laboratories Incorporated, 207 East Ohio Street, Chicago, IL 60611.)

Source: https://assist.dla.mil -- Downloaded: 20261O-26T12:00Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the supplier shall furnish one complete grinding machine for first article inspection. The first article may be either a preproduction model or an initial production item which conforms to the requirements of this specification. In either case, the approved first article and production items shall be identical and in accordance with the terms of the contract. Approval of the first article shall not relieve the supplier of the responsibility to furnish equipment in accordance with the requirements of this specification.

3.2 Design. The grinding machines shall be new and of the manufacturer's current model that will meet the requirements specified in this specification. All parts subject to wear shall be readily accessible for adjustment and repair.

3.2.1 Lubrication. All bearings (except the sealed-for-life type), mating gears, revolving shafts, and other working parts shall be provided with means for lubrication. Mechanisms requiring special lubrication shall be in accordance with the requirements specified herein.

3.2.2 Safety and health requirements. Covers or other safety devices shall be provided for all parts of the grinding machines presenting a safety hazard which can be guarded without substantial interference to operation of the grinding machine. All guards shall be removable to provide easy access to the guarded parts. Except as otherwise specified by the procuring activity, the grinding machines shall comply with the standards promulgated under OSHA applicable to the grinding machine itself. Exceptions and additional requirements for safety and health shall be as specified (see 6.2 and 6.3).

3.2.3 Interchangeability. All replaceable parts shall be manufactured to such standards as will permit replacement or adjustment without requiring modification to the parts or unit.

3.2.3.1 Threads. All screw threads shall be in inch units of measurement and shall comply with NBS H28.

3.3 Construction. All parts and materials used in fabrication shall be new and free from any characteristics or defects that may render the unit unsuitable or inefficient for the intended purpose. In no event shall patching processes be used for reclaiming defective parts. All surfaces of all parts shall be clean and free of extraneous materials. External surfaces shall be smooth and free of sharp edges. All screws, pins, and similar parts shall be installed with means to prevent loss of tightness. All such parts subject to adjustment or removal shall not be swaged, peened, staked, or otherwise permanently deformed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

3.3.1 Electrical connections. Connections of conductors and terminal parts shall be of the screw, pressure, or solder type. When soldered connections are used, the conductors and terminal parts shall be mechanically secured before soldering. Rosin base fluxes only shall be used in soldering operations. Connections to screw-type terminals shall be mechanically secured with a means to prevent loss of tightness.

3.4 Performance and product characteristics. The grinding machines shall be capable of grinding the outside surface of brake-linings on all types of brake-shoes to fit standard-type brake-drums.

3.4.1 Type I operation. The type I grinding machine shall perform the grinding operation, with the shoe assembly mounted on the vehicle, after centering the unit to the rotating axis and adjusting for the diameter required to fit the inside diameter of the brake-drum. Grinding shall then be accomplished by manually rotating the grinder around the common axis of the vehicle axle.

3.4.2 Type II operation. The type II bench mounted grinding machine shall perform the grinding operation after securing the brake-shoe in a clamping device and adjusting the machine to the required brake-drum diameter. Grinding shall then be accomplished by feeding the brake-shoe up to the grinding surface and rotating the lining face against the abrasive surface in a 180° arc.

3.4.3 Type I size capacity. The type I, size A grinding machine shall be capable of grinding brake-shoe assemblies for brake-drums from 8 inches through 16 inches in diameter and up to 4 inches in shoe width. The type I, size B machine shall be capable of grinding brake-shoe assemblies for brake-drums from 12 inches through 24 inches in diameter and up to 8 inches in shoe width.

3.4.4 Type II size capacity. The type II grinding machine shall be capable of grinding brake-shoes for brake-drums from 8 inches through 16 inches in diameter and up to 4 inches in shoe width.

3.4.5 Grinding accuracy. After removing 0.005 inch from the lining surface, the accuracy of the grinding operation shall meet the following requirements.

3.4.5.1 True arc diameter. The finished brake-lining shall not deviate from a true arc nor the desired diameter by more than 0.005 inch total indicator reading (t.i.r.) on the radius.

3.4.5.2 Flatness. The finished lining surface shall be flat, transversely, within 0.005 inch.

3.4.5.3 Parallelism. The lining surface shall be parallel with the rotating axis within 0.0025 inch for each inch of width up to 4 inches.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:00Z
Check the source to verify that this is the current version before use.

Brake-shoe lining surfaces wider than 4 inches shall not have a total error of parallelism with the rotating axis greater than 0.010 inch for the entire width.

3.5 Components.

3.5.1 Type I components. The principal components of the type I grinding machine shall consist of the main frame, centering devices, backing disks, feed mechanism, motor, and a carrying case.

3.5.1.1 Main frame. The main frame shall be made of cast iron, aluminum alloy, or other metals that will provide the necessary rigidity to carry the weight of the motor and connecting members. The frame shall be sufficiently rigid to insure the required accuracy in performance. Provisions shall be included to permit adjustment of the motor horizontally and remain in the same plane. A clamping device shall be provided to secure the motor assembly at the desired setting. Provisions shall be included for a feed screw to adjust the machine to the desired radius for grinding. The connecting members of the frame shall be of steel bar-stock or seamless steel tubing. The diameter of the steel bar(s), or the wall thickness of the seamless steel tube(s), shall provide the maximum rigidity and minimum vibration while grinding lining surfaces.

3.5.1.2 Centering device, or chuck. The centering device, or chuck, shall be adjustable to fit straight and tapered spindles or axles. The mounting device, or chuck, shall be so equipped that an accurate, quick change adjustment can be made for size A: 5/8-inch to 4-1/2-inch diameter, and size B: 5/8 inch to 5-1/4-inch diameter.

3.5.1.3 Backing disks. Backing disks shall be made of aluminum alloy or a comparable metal and of sufficient size to accommodate the diameter of the abrasive disks specified herein. The method of changing abrasive disks shall be simple and easy.

3.5.1.3.1 Abrasive disks. The abrasive disks shall be 24- or 36-grit aluminum oxide. The diameter of the disks shall be from 4-1/2 inches to 7 inches for size A, and 10 inches for size B grinding machines. Disks shall be precoated with pressure sensitive adhesive which shall be properly protected.

3.5.1.4 Feed mechanism. The feed mechanism shall provide micrometer adjustment to any grinding diameter within the size A or size B capacity specified. A micrometer dial shall be provided to measure the desired amount of adjustment. The dial shall be graduated in increments of 0.001 inch. The dial shall be permanently and legibly marked at least every 20 graduations in Arabic numerals.

3.5.1.5 Dust guard. Each grinding machine shall be provided with a dust guard to protect the operator from flying brake-lining particles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

3.5.1.6 Micrometer gage. A micrometer gage with extension and offset arms, if required, or one that is similar shall be provided with each grinding machine. The gage shall be equipped with a locator, micrometer adjustment, and locking device for checking the brake-drum diameter. The micrometer gage shall accurately measure the inside diameter of the brake-drum. This measurement shall be used in setting the machine before grinding.

3.5.1.7 Carrying case. A carrying case shall be furnished for each type I grinding machine. The case shall be designed to contain the grinding machine and all of its parts and equipment, spare parts, and tools. The materials used in fabrication of the case shall provide the support and durability required in transporting same from vehicle to vehicle and storage.

3.5.2 Type II components. The principal components of the type II bench mounted grinding machine shall consist of the body housing, grinding unit, dust collector, shoe clamp, feed mechanism, range setting mechanism, and the motor.

3.5.2.1 Body housing. The body housing shall be made of cast iron, aluminum alloy, or other metals of equal quality composition. The housing shall be mounted and easily secured to the top of a work bench. The grinding unit, dust collector, shoe clamp, feed and range setting mechanisms, and the drive motor shall be mounted on or in the body housing.

3.5.2.2 Grinding unit. The grinding unit shall include provisions for accurately mounting and securing the abrasive sleeve or disk. The drive spindle assembly of the grinding unit shall be equipped with bearings and shall be dustproof. The grinding unit shall be either direct or V-belt driven. If driven by a V-belt from the motor, the V-belt shall be readily accessible for tension adjustment or replacement. The method for securing the abrasive sleeve or disk shall permit easy replacement of the sleeve or disk. The abrasive sleeve or disk surface shall be of a grit necessary to remove stock and finish the shoe lining surface as specified herein.

3.5.2.3 Dust collector. A dust collector shall be provided for controlling the grinding dust. The dust shall be collected in a bag that can easily be removed and emptied. The dust bag shall be attached so that it will hang through a hole cut in the bench top or placed flat on the bench behind the grinding unit.

3.5.2.4 Shoe clamp. The shoe clamp shall provide a means of securing the brake-shoe firmly, quickly, and accurately on the grinding machine. The clamping device shall secure shoes for brakes with the so-called "floating-shoe" action and brakes with nonadjustable anchors. The method of clamping shoes for use on nonadjustable anchor brake assemblies must provide means for locating the eye of the shoe so that the shoe is ground in its actual operating position for the vehicle braking system being repaired.

Source: https://assist.dla.mil -- Downloaded: 20260-26T12:00Z
Check the source to verify that this is the current version before use.

3.5.2.5 Range locating mechanism. A quick-action locating mechanism shall be provided and shall allow moving the shoe clamp, quickly and easily, from the 8-inch diameter to the 16-inch diameter brake-shoe position and any desired position within this range. Range capacity shall be at least 0.150 inch below the minimum range and 0.500 inch over the maximum range. Such movement shall be independent of the setting adjustment mechanism. A handgrip handle shall be provided for controlling the arc movement grinding operation.

3.5.2.6 Feed setting mechanism. The arc radius feed setting mechanism shall provide easy adjustment of settings to within 0.005-inch diameter. This adjustment will be made in setting the arc radius for the amount of material to be removed from the shoe-lining on each grinding pass. This may be accomplished by a micrometer type in-feed screw knob with graduations indicating not more than 0.010-inch feed.

3.6 Electrical equipment. Unless otherwise specified (see 6.2), the grinding machines shall be wired to operate on a 115-volt, alternating current (a.c.), 60-hertz, single phase electrical power source.

3.6.1 Motor. The motor shall be an air circulating type, totally enclosed, equipped with sealed-for-life ball bearings, and shall conform to CC-M-1807. Motors for the type I, size A grinding machine shall be not less than 1/4 horsepower (h.p.). Motors for the type I, size B and type II grinding machine shall not be less than 1/2 h.p. Motors for the type II grinding machine shall be rated for continuous duty and be equipped with overload protection.

3.6.2 Motor switch. A dustproof motor switch shall be provided with the ON/OFF positions marked in a plain, visible, and permanent manner. The switch shall be convenient to the operator.

3.6.3 Power supply cord. Unless otherwise specified (see 6.2), the grinding machines shall be provided with not less than 10 feet of 3-wire, UL approved type S or SO heavy duty electrical cord. The cord shall terminate with a plug conforming to W-C-596/13. When a grinding machine is furnished with a 3-phase, a.c. motor, the machine shall be provided with a 4-wire cord and a 4-prong, polarized plug. The cord and plug shall be of the proper capacity for the current specified and the cord shall be reinforced or armored at the junction with the machine.

3.7 Electromagnetic compatibility. Unless otherwise specified (see 6.2), the grinding machines shall meet the following electromagnetic compatibility requirements.

3.7.1 Army. Grinding machines procured under this specification for the Army shall comply with the requirements of MIL-STD-461 for class IIB equipment.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:00Z
Check the source to verify that this is the current version before use.

3.7.2 Navy. Electric motors shall comply with the requirements of MIL-STD-461 relative to radiated and conducted radio interference. Tests for radio interference will not be required for motors that are identical electrically to those that have previously met the requirements of MIL-STD-461. Radio interference reduction and tests will therefore not be required for electric motors without commutation having not more than one starting contact and operated at 3,600 or less revolutions per minute.

3.7.3 Air Force. The electrical equipment shall conform to the applicable requirements of MIL-STD-826 when motors capable of producing continuous radio interference are used. Electrical motors without commutators or commutator motors with brush lifting devices which make the commutator inoperative during the running cycle are exempt from radio interference reduction treatment or test requirements.

3.8 Fungus treatment. When specified (see 6.2), electrical components and circuit elements shall be treated for fungus resistance in accordance with the type II requirements of MIL-T-152 except that the statement of treatment is not required. The windings of the electric motor shall be given two impregnating coats of varnish conforming to the requirements of MIL-I-24092, type M, class 155 through 220 (manufacturer's option).

3.9 Accessory equipment.

3.9.1 Type I, size A. The following accessory equipment shall be furnished as specified with the type I, size A grinding machine (see 6.2):

1 each - Floating shoe holder.
1 each - Adapter, Ford, Lincoln, Mercury, and Jeep for models of current and at least the previous five years.
1 each - Adapter, ring for General Motors.
1 each - Adapter, ring for Ford and Chevrolet, Lincoln, and Mercury for models of current and at least the previous five years.
1 each - Adapter, floating rear.
1 each - Adapter, universal.
1 each - Attachment, truck (light and medium).
1 each - Shoe centralizer, Ford, for models of current and at least the previous five years.
1 each - Reducer sleeve.
1 each - Motor shim.
1 each - Axle diameter gage.

3.9.2 Type I, size B. The following accessory equipment shall be furnished as specified with the type I, size B grinding machine (see 6.2).

1 each - Adapter, universal.
1 each - Adapter, plate.
1 set - Chuck pins, 6 each, 1 inch long.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

1 set - Chuck pins, 6 each, 2 inches long.
1 set - Chuck pins, 6 each, 2-1/2 inches long.
1 set - Chuck pins, 6 each, 3 inches long.
1 each - Motor spacer block assembly.
1 each - Axle diameter gage.

3.9.3 Type II. The type II grinding machine shall be furnished with 10 abrasive sleeves or disks. The abrasive shall be 24- or 36-grit aluminum oxide.

3.10 Painting. Unless otherwise specified (see 6.2), painting and finishing of the grinding machines shall be in accordance with the supplier's standard practice provided the following minimum criteria are met or exceeded: all surfaces to be painted shall have been cleaned to be free of all foreign matter detrimental to painting, and at least one coat of primer and one coat of enamel have been applied.

3.11 Identification marking.

3.11.1 Military. The grinding machines shall be marked for identification in accordance with MIL-STD-130 and unless otherwise specified (see 6.2), shall include the National Stock Number.

3.11.2 Civil agencies. Each machine shall be marked in a plain and permanent manner with the model and serial number and with the manufacturer's name or trademark of such known character that the source of manufacture may be readily determined.

3.12 Technical data. Data shall be furnished as specified (see 6.3).

3.13 Workmanship. The grinding machines, including all parts and accessories, shall be fabricated and finished in a workmanlike manner. Particular attention shall be given to freedom from blemishes, defects, burrs, and sharp edges; accuracy of dimensions and markings of parts and assemblies; thoroughness of soldering, welding, brazing, and painting; and alignment of parts and tightness of assembly screws and bolts.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:00Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) First article inspection (see 4.2.1).

(b) Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. First article inspection shall be applied to the preproduction model or initial production item noted in 3.1. Unless otherwise specified (see 6.2), first article inspection shall consist of the examination in 4.3 and all tests under 4.4. Failure of the first article to pass the examination or any of the tests shall be cause for rejection.

4.2.2 Quality conformance inspection. Unless otherwise specified (see 6.2), quality conformance inspection shall be applied to each grinding machine prior to being submitted for acceptance under the contract. The inspection shall consist of the examination in 4.3, inspection in 4.5, and the tests in 4.4. Failure of the unit to pass one or more inspection requirements shall be cause for rejection.

4.2.2.1 Sampling. When specified (see 6.2), sampling for lot acceptance shall be in accordance with MIL-STD-105 at the inspection level and acceptable quality level specified in the contract. Samples for the test shall be selected at random from the samples that passed the examination in 4.3.

4.3 Examination. Each production item or sample shall be visually examined to determine compliance with requirements in section 3, using the following checklist as a guide:

Examination checklist	Requirement reference
Design features, not as specified	3.2 through 3.2.3.1
Construction, not as specified	3.3 and 3.3.1
Type and size, not as specified	3.4.1 through 3.4.4
Principal components, not as specified or missing	3.5.1 and 3.5.2
Motor, not as specified	3.6.1
Motor switch, not as specified or missing	3.6.2
Power supply cord, not as specified	3.6.3
Electromatic compatibility, not as specified, test report required	3.7
Fungus treatment, not as specified, vendor certification required	3.8
Accessory equipment, not as specified	3.9
Painting, not as specified	3.10
Identification marking, not as specified	3.11
Technical data, not as specified	3.12
Workmanship, not as specified	3.13

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:00Z
Check the source to verify that this is the current version before use.

4.4 Test methods.

4.4.1 Operational test. A total of six brake-shoe assemblies for the type I grinding machine and six brake-shoes for the type II grinding machine, covering their respective size capacities, shall be used to determine the operational capability of each type and size machine (see 3.4.1 through 3.4.4).

4.4.2 Finish grinding. Using the same brake-shoes and set-up as that for rough grinding, the grinding machines shall be adjusted to remove 0.005-inch lining stock. One pass of the grinder shall then be made to determine the accuracy for finish grinding (see 3.4.5).

4.4.2.1 True arc diameter. The finished brake-lining shall have a true arc or diameter, within 0.005-inch t.i.r. on the radius (see 3.4.5.1).

4.4.2.2 Flatness. The finished surface shall be flat, transversely, within 0.005 inch (see 3.4.5.2).

4.4.2.3 Parallelism with rotating axis. The surface shall be parallel with the rotating axis within 0.0025 inch for each inch of shoe width up to 3 inches. Error for widths greater than 3 inches shall not be out of parallel with the rotating axis more than 0.010 inch for the entire width (see 3.4.5.3).

4.4.3 Electromagnetic compatibility tests. Tests for electromagnetic compatibility shall be as follows.

4.4.3.1 Army. The grinding machines shall be tested in accordance with test methods CE03 and RE02 of MIL-STD-461 to determine compliance with the requirements of 3.7.1.

4.4.3.2 Navy. Tests for radio interference shall be conducted in accordance with MIL-STD-461. All testing equipment, instruments, and personnel for making the test shall be furnished by the contractor. The test location shall be reasonably free from radiated and conducted interference. Tests for radio interference will not be required for electric motors that are identical electrically to those that have met the requirements of MIL-STD-461 (see 3.7.2).

4.4.3.3 Air Force. The grinding machines shall be tested in accordance with MIL-STD-826 (see 3.7.3).

4.5 Preservation, packing, and marking inspection. Preservation, packing, and marking for shipment and storage shall be examined to determine compliance with section 5. The examination shall be conducted as specified in MIL-M-18058.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, and packing. Preservation, packaging, and packing for the specified level (see 6.2) shall be in accordance with MIL-M-18058.

5.2 Marking. Marking shall be in accordance with 5.2.1 or 5.2.2 as specified (see 6.2).

5.2.1 Civil agencies. Unit and exterior shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.2.2 Military. Unit and exterior shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The grinding machines covered by this specification are to be used in automotive repair shops for grinding all types of commercial vehicle brake-shoe linings.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type and size required (see 1.2.1).
(c) First article, when required (see 3.1).
(d) Specify exceptions and additional safety and health requirements (see 3.2.2. and 6.4).
(e) Electrical equipment, if different (see 3.6).
(f) Power supply cord, if different (see 3.6.3).
(g) Electromagnetic compatibility, if different (see 3.7).
(h) Fungus treatment, if required (see 3.8).
(i) Accessory equipment required (see 3.9.1 and 3.9.2).
(j) Painting, if different (see 3.10).
(k) Identification marking, if different (see 3.11).
(l) First article inspection, if different (see 4.2.1).
(m) Quality conformance inspection, if different (see 4.2.2).
(n) Sampling, when required (see 4.2.2.1).
(o) Level of preservation, packaging, and packing required (see 5.1).
(p) Whether civil or military marking is required (see 5.2).

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:00Z
Check the source to verify that this is the current version before use.

6.3 Contract data requirements.

6.3.1 Military agencies. Required technical data such as operator's manuals, parts lists, and other instructions for operation and maintenance, as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated into the contract (see 3.12).

6.3.2 Civil agencies. The supplier shall furnish one copy of a handbook of instructions with each grinding machine. The handbook shall contain the necessary operating instruction, illustrations, parts list, part numbers, safety precautions, and maintenance procedure. Additional copies of the handbook and mailing address to which the copies shall be sent shall be specified by the procuring activity.

6.4 Safety and health determinations. In order that equipment integrated into the user's operational environment will comply with OSHA, limitation and control of noise levels, radiation, electromagnetic emission, noxious vapors, heat, etc. as applicable, specific requirements concerning guarding the point(s) of operation, and other safety and health requirements should be specified.

MILITARY INTEREST:

Custodians:

Army - WC
Navy - YD
Air Force - 99

User activities:

Navy - MC

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS
USPS - POS

PREPARING ACTIVITY: ARMY - WC

Project No. 4910-0431

Orders for this spublication are to be placed with General Services Administration acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 35 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.