00-S-00625(GSA-FSS)
July 2, 1964

INTERIM FEDERAL SPECIFICATION

SPRAY GUN, PAINT, HAND OPERATED

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20407, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION.

1.1 Scope. This specification covers a hand operated paint spray gun with a trigger squeeze type pump.

1.1.1 Federal specification coverage. Federal specifications do not include all varieties of the commodity as indicated by the title of the specification, or which are commercially available, but are intended to cover only those generally used by the Federal Government.

1.2 Classification. 4940-00-670-2930

1.2.1 Type. Spray guns covered by this specification shall be of one type as hereinafter specified.

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS.

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-585 - Boxes, Wood, Wirebound.
PPP-B-601 - Boxes, Wood-Cleated Plywood, for Domestic Shipment.
PPP-B-621 - Boxes, Wood, Nailed and Lock Corner.
PPP-B-636 - Boxes, Fiberboard.

Federal Standards:

Fed. Std. No. 102 - Preservation, Packaging, and Packing Levels.
Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

MIL-P-116 - Preservation, Methods of .
MIL-L-10547 - Liners, Case, and Sheet, Overwrap, Water-Vaporproof or Waterproof, Flexible.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following publications form a part of this specification. Unless otherwise indicated, the issues in effect on date of invitation for bids or request for proposal shall apply.

National Bureau of Standards Handbook:

H28 - Screw-Thread Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402.)

3. REQUIREMENTS.

3.1 Material. Material not hereinafter specified shall be of good commercial quality. All materials shall be free from all defects and imperfections that might affect the serviceability and appearance of the unit.

3.2 Construction. Spray guns shall be complete so that they can be used for the purpose intended.

3.2.1 Castings. If castings are used, they shall be of uniform quality, free from blow-holes, porosity, or other defects which may adversely affect the strength or serviceability of the spray gun.

3.2.2 Welding, brazing, or soldering. Welding, brazing, or soldering shall be in accordance with good commercial practice. In no event shall such processes, including plugging and peening, be used for reclaiming any defective parts of the spray guns.

3.2.3 Fastening devices. If fastening devices are used, such as screws, bolts, nuts, pins, and similar parts, they shall be installed in a manner to prevent loss of tightness and adjustment. All such parts when subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently deformed.

3.3 Washers. Washers, if necessary for proper operation of the spray gun, shall be furnished. The washers shall be impervious to paint and shall have adequate sealing qualities.

3.4 Design. The spray guns covered by this specification shall be the manufacturer's current standard commercial product. The design of units shall be such that like parts are interchangeable between all units of the same model. All parts subject to wear and service failure shall be replaceable. The materials used in the construction of the spray gun shall be corrosion resistant to the extent necessary to insure against failure.

3.5 Interchangeability. All parts shall be manufactured to definite standards, tolerance and clearance in order that any part of a particular model may be replaced or adjusted without requiring modification.

3.6 Screw threads. All threaded parts, including screws, bolts, and nuts, and except where threaded to fit a container of marking paint, shall conform to the applicable requirements of National Bureau of Standards Handbook H28.

3.7 Spray unit. The spray unit shall consist essentially of a pistol grip type handle housing, a trigger actuated pump mechanism, trigger, barrel tube, reversible nozzle, nozzle cap, cap holder, and a threaded adapter. The spray unit shall be attachable to a screw type top container of marking paint by means of the threaded adapter. The barrel tube shall extend to the bottom of the container and there shall be no visual evidence of leakage at the threaded adapter when the unit is operated. The nozzle shall be provided with either a 0.021, 0.025, or 0.030 inch orifice, as specified (see 6.2). The nozzle shall be reversible so that the orifice may be unplugged by hydraulic action of the unit. Provision shall be provided so that the nozzle cap may be fastened over the nozzle when the unit is not in use, and means shall be provided to secure the cap to the unit when the spray gun is in use.

3.8 Finish. The spray gun shall be finished in accordance with the manufacturer's commercial practice.

3.9 Identification. Each spray gun shall be plainly marked with the manufacturer's designation and with his name or trademark of such known character that the source of manufacture may be readily determined.

3.10 Instruction book. One copy of an instruction book consisting of the manufacturer's standard commercial instructions and parts list, bound together, shall be furnished with each unit.

3.11 Workmanship. The spray gun shall be constructed, assembled, and finished in a thoroughly workmanlike manner to assure good quality equipment of a neat general appearance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES.

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling for lot acceptance.

4.2.1 Inspection lot. All spray guns offered for delivery at one time shall be considered a lot for the purpose of acceptance, inspection and tests.

4.2.2 Sampling for examination. A random sample of spray guns shall be taken by the inspector from each inspection lot of material offered for Government inspection with lot acceptance based on table I and in accordance with MIL-STD-105.

Table I. - Sampling for examination - A.Q.L. (approx.) = 1.5 percent defective.

Number of spray guns in inspection lot	Number of spray guns in the sample	Acceptance number (defective)	Rejection number (defective)
15 and under	7	0	1
16 to 40	10	0	1
41 to 110	15	0	1
111 to 300	25	1	2
301 to 500	35	1	2
501 and over	50	2	3

4.2.3 Sampling for tests. One spray gun from each lot shall be taken for the tests specified in 4.4.

4.3 Examination. Each of the sample spray guns taken in accordance with table I shall be examined for compliance with this specification. Any spray gun in the sample containing one or more defects shall be rejected, and if the number of defective spray guns in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

4.4 Tests.

4.4.1 Operational testing. Each spray gun selected for test shall be attached to a quart size container of marking paint and operated to determine that the assembly of component parts are complete and of proper interrelationship. The spray gun shall be examined during operation to assure that there is no visual evidence of leakage of the marking paint (see 3.7). The nozzle shall be reversed to assure adequate reversibility. Failure of any spray gun to perform its required operation shall mean rejection of the entire lot.

4.5 Rejected lots. Rejected lots may be resubmitted for examination and tests provided the contractor has removed or repaired all nonconforming spray guns. Samples shall again be selected and inspected from such resubmitted lots to verify compliance with this specification. Rejected spray guns shall not be resubmitted for inspection without furnishing full particulars concerning previous rejections, and measures taken to overcome the defects.

4.6 Inspection of preparation for delivery requirements. An inspection shall be made to determine that packaging, packing and marking requirements are in compliance with section 5 of this specification. Defects shall be scored in accordance with table II. For examination of contents, the sample unit shall be one shipping container fully prepared for delivery selected just prior to the closing operations. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 6 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

Table II. - Classification of preparation for delivery defects.

Examine	Defect
Markings (exterior and interior)	Omitted; incorrect; illegible; or improper size, location, sequence, or method of application.
Materials	Any component missing, or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, sealing and closure not as specified. Bulging or distortion of container.

5. PREPARATION FOR DELIVERY.

(For civil agency procurement, the definitions and applications of the levels of packaging and packing shall be in accordance with Fed. Std. No. 102.)

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. Each complete spray gun shall be packaged in accordance with MIL-P-116, method IC-2 or IC-5.

5.1.2 Level B. Each complete spray gun shall be packaged in a close-fitting box conforming to PPP-B-636, type I, class 1, style RSC. Closure shall be in accordance with the appendix to the box specification.

5.1.3 Level C. The spray guns shall be packaged in accordance with the suppliers commercial practice.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. The spray guns shall be packed in any of the containers conforming to the following specifications at the option of the contractor:

Specification	Type or class
PPP-B-585	Class 3 use
PPP-B-601	Overseas type
PPP-B-621	Class 2
PPP-B-636	Class 2

Each container shall have a case liner conforming to, and closed and sealed in accordance with MIL-L-10547. Case liners for fiberboard containers may be omitted provided they are waterproof sealed with tape in accordance with the appendix to the fiberboard box specification. The shipping containers shall be closed, sealed and banded in accordance with the applicable container specification or appendix thereto. The gross weight of the wood or wood-cleated boxes shall not exceed 150 pounds; of the fiberboard boxes, the weight limitations of the fiberboard box specification.

5.2.2 Level B. Twelve spray guns shall be packed in a close-fitting box conforming to PPP-B-636, type I, class 1, style RSC. Each box shall be closed in accordance with the appendix to the box specification.

5.2.3 Level C. The spray guns shall be packaged to insure carrier acceptance and safe delivery to destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special markings required by the contract or order (see 6.2), the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military activities. In addition to any special markings required by the contract or order (see 6.2), the interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

6. NOTES.

6.1 Intended use. The spray guns covered by this specification are intended for applying paint markings, to items such as trees, for the purpose of identification.

6.2 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Size orifice desired (see 3.7).
(c) Level of packaging required (see 5.1).
(d) Level of packing required (see 5.2).
(e) Special marking if required (see 5.3).

GSA DC 65-219

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.