00-S-811D
Amendment 1
31 October 1989

FEDERAL SPECIFICATION

SURFACERS (PLANERS), WOODWORKING

This amendment, which forms a part of 00-S-811D, dated 6 January 1989, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

Page 17

Add: Table I, page 17, attached.

MILITARY INTERESTS:

Custodians

Army - ME
Navy - SH
Air Force - 99

Review Activities

Navy - YD
Air Force - 84
DLA - GS

User Activities

Army - CE
Navy - MC

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA-FSS

PREPARING ACTIVITY:

DLA - IP

PROJECT NUMBER:

3220-0160

FSC 3220

DISTRIBUTION STATEMENT A. Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

Table I. Sizes and capacities.

Characteristics	Type I								Type II						
Size, workpiece cross section dimensions, inches, width-thickness	Class A			Class B			Class C		Class C	Class D	Class E				
	Size 12x5	Size 18x6	Size 24x8	Size 24x8	Size 30x8	Size 36x8	Size 30x8	Size 36x8	Size 30x7	Size 30x14	Size 18x18	Size 24x8	Size 30x8	Size 36x8	Size 36x12
Cutting circle diameter, inches	2-1/2	3	4	5	5	5	5	5	5-1/2	6	5	5	5	5	5
Number of cutterhead knives	3	3	4	4	4	4	4	4	4	4	4	4	4	4	5
Cutterhead speed, RPM															
Direct drive	3600	3600	3600	3600	3600	3600	3600	3600	3600	3600	4500	4500	4500	4000	3600
Belt drive	4500	4500	4500	5000	5000	4000									
Cutterhead, motor HP															
Upper cutterhead, Std.	3	5	5	7-1/2	10	15	25	25	25	25	25	25	25	25	25
Opt.	2,5	7-1/2	7-1/2, 10,15	10,15	15,20, 25,30	7-1/2 10,25, 40	20,30, 40	20,30, 40	20,30, 40	30,40,	30,40, 50,60, 75	30,40, 50,60, 75	30,40, 50,60, 75	30,40, 50,60, 75	30,40, 50,60, 75
									20,25 15	20 15,25, 30	25 30,40, 50,60, 75	25 30,40, 50,60, 75	25 30,40, 50,60, 75	25 30,40, 50,60, 75	25 30,40, 50,60, 75
Feed drive, motor HP	1/3	1/3	1	1-1/2	2	2	2	2	5	7-/12	3	3	3	5	5
Feed range, lines 1 foot per minute	15-25	20-35	20-60	30-60	20-60	25-60	25-60	25-60	30-75	60-150	30-90	30-90	30-90	30-90	20-60
Horizontal distance between cutterhead, inches											40	40	40	35	72
Separate motor drives feed, optional (see 3.4.1.5)															

Note: Requirements are "not less than those shown." When a range is shown, the performance shall encompass a range from the stated "minimum or less" to the stated "maximum or greater."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.