FEDERAL SPECIFICATION

WRENCH, IMPACT, PNEUMATIC, PORTABLE

This amendment, which forms part of Federal Specification 00-W-891e, dated August 25, 1967, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

Page 3, Table I, column 7: For Spindle size 1, delete "5" seconds and substitute "8" seconds.

Page 7, Table IV: Delete and substitute:

"TABLE IV. Dimensions of test specimens

Spindle size inches	Nominal 1/ hex, size A, inches	Overall length B, inches	"C" length, inches, ±0.005	"D" diameter, inch, ± 0.0005	"E" diameter, inch, ± 0.005
3/8	1/2	4	0.500	0.250	0.480
1/2	5/8	4-1/4	.750	.320	.680
5/8	7/8	4-1/2	1.000	.430	.680
3/4	1	4-1/2	1.000	.510	.880
1	1-1/8	4-1/2	1.000	.680	.980
1-1/2	1-3/8	5	1.500	1.000	1.000

1/ Distance across flats of hexagon bar."

Page 10, "Preparing activity:": Delete "GSA-FSS" and substitute "Navy - SH".

Custodians:
Army - GL
Navy - SH
Air Force - 84

Review activities:
Army - GL
Navy - SH
Air Force - 84

User activities:
Navy - YD, MC

Civilian Agency Interest:
GSA -FSS

Preparing activity:
Navy - Sil
(Project 5130-0149)

FSC 5130

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.