INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

WRENCH, IMPACT, PNEUMATIC, PORTABLE

This interim amendment was developed by the Department of the Navy, Naval Ship Engineering Center, Center Building, Prince George's Center, Hyattsville, Maryland 20782, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Service Administration has authorized the use of this interim amendment as a valid exception to Federal Specification OO-W-891e.

Page 1

1.2.1: Delete and substitute:

"1.2.1 Sizes. The wrenches shall be furnished with the following square male drive sizes, as specified (see 3.11 and 6.1):

Size 3/8 (1/4-inch capacity), straight drive.
Size 3/8 (1/4-inch capacity), angle drive.
Size 1/2 (3/8-inch capacity), straight drive.
Size 1/2 (3/8-inch capacity), angle drive.
Size 5/8 (5/8-inch capacity).
Size 3/4 (3/4-inch capacity).
Size 1 (1-1/4-inch capacity).
Size 1-1/2 (1-3/4-inch capacity), standard duty.
Size 1-1/2 (1-3/4-inch capacity), heavy duty."

2.1: Add:

"Federal Specification:
PPP-P-40 - Packaging and Packing of Hand Tools."

2.1: Delete:

"Federal Standard:
Federal Standard No. 123 - Marking for Domestic Shipment (Civilian Agencies).

Military Specification:
MIL-P-12829 - Packaging of Pneumatic Hand Tools with Attachments and Accessories.

Military Standard:
MIL-STD-129 - Marking for Shipment and Storage."

Page 2

2.1: Delete source paragraph for Military Specifications and Military Standards.

1/ CHANGES FROM PREVIOUS ISSUE. THE OUTSIDE MARGINS OF THIS DOCUMENT HAVE BEEN MARKED "#" TO INDICATE WHERE CHANGES (DELETIONS, ADDITIONS, ETC.) FROM THE PREVIOUS ISSUE HAVE BEEN MADE. THIS HAS BEEN DONE AS A CONVENIENCE ONLY AND THE GOVERNMENT ASSUMES NO LIABILITY WHATSOEVER FOR ANY INACCURACIES IN THESE NOTATIONS. BIDDERS AND CONTRACTORS ARE CAUTIONED TO EVALUATE THE REQUIREMENTS OF THIS DOCUMENT BASED ON THE ENTIRE CONTENT AS WRITTEN IRRESPECTIVE OF THE MARGINAL NOTATIONS AND RELATIONSHIP TO THE LAST PREVIOUS ISSUE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

2.2: Delete in its entirety all reference to "American Standards Association (ASA) Publications" and substitute the following:

"AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)
ANSI B5.38-1958 - Driving and Spindle Ends for Portable Air and Electric Tools.
ANSI S5.1-1971 - Test Code for the Measurement of Sound from Pneumatic Equipment.

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, New York 10018.)"

3.2: Delete and substitute:

"3.2 Qualification. Portable penumatic wrenches furnished under this specification shall be products which are qualified for listing on the applicable qualified products list at the time set for opening of bids (see 4.2 and 6.3)."

3.3: Delete and substitute:

"3.3 Materials. The materials used in the construction of items and components shall be sound, of uniform quality and condition and shall conform in composition, heat treatment and suitability to the standard practices of manufacturers producing tools of the types required in this specification. Equipment and parts shall be new and high grade commercial quality."

3.6, 3.6.1, and 3.6.2: Delete and substitute:

"3.6 Lubrication.

"3.6.1 Primary lubrication. Wrenches shall be provided with an oil reservoir, either built-in or of the airline lubricator type. Capacity of the reservoir shall assure metered lubrication of all moving parts in the air stream, from one filling, for a minimum operating period of 8 hours.

"3.6.2 Secondary lubrication. Wrenches requiring periodic lubrication of parts other than those in the air stream shall be provided with external means of applying the required lubricant without disassembling the tool."

After 3.10, add the following paragraph as 3.10.1:

"3.10.1 Sound pressure level. The sound pressure level shall not exceed the following decibel limits on the A weighted scale in any prescribed microphone location (see 4.8).

95 dbA	Sizes 1/2 inch and smaller
103 dbA	Sizes 5/8 inch and larger"

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

Page 3 (con.)

Table I: Delete and substitute:

"Table I - Weight, dimensional and performance requirements.

Spindle size	Weight max.	Length max.	Spindle offset max.	Air[1/] inlet (NPT-NPTF)	Air consumption[2/] at load max.	Time to twist specimen 180° max.
Inches	Pounds	Inches	Inches	Inch	CFM	Seconds
3/8	5	9-1/4	1-1/4	1/4	15	5
1/2	7	10-5/8	1-3/8	1/4	30	5
5/8	12	12	1-5/8	1/4	35	5
3/4	35	16	2	3/8	50	5
1	35	21-1/8	2-1/2	3/8	60	8
1-1/2 standard duty	40	20	3	1/2	85	20
1-1/2 heavy duty	100	25	3-/16	3/4	140	10

[1/] Other air inlet sizes will be permitted provided adapters are finished in the sizes which will permit connections of air hoses in accordance with this table.

[2/] Air consumption at load measured during test specimen twist test.

Page 6

3.15: Delete and substitute:

"3.15 Angle drive. When specified (see 6.1), the 3/8 and 1/2 inch size wrenches shall be of the angle drive type with the axis of the drive shaft 90° from the axis of the wrench housing. Angle drive wrenches may exceed the length requirements of table I by no more than 4 inches."

3.19, line 1: Delete ("torque)" throughout.

4.1: Delete and substitute:

"4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

4.2, last line: Delete "Provisions Governing Qualification" and substitute "Provisions Governing Qualification SD-6".

Page 7

4.6.1, line 3: Delete "SAE grade 1" and substitute "plain carbon (1020 series)".

4.6.1, lines 4 and 5: Delete "maximum hardness of 95" and substitute "hardness of 60-70".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

Page 7 (con.)

Table IV: Delete and substitute:

Table IV - Dimensions of test specimens.

Spindle size inches	Nominal[1] hex, size A, inches	Overal length B, inches	"C" length, inches +0.005	"D" diameter,[2] inch ±0.0005	"E" diameter inch ±0.005
3/8	1/2	4	0.500	0.250	0.480
1/2	5/8	4-1/4	.750	.320	.680
5/8	7/8	4-1/2	1.000	.430	.680
3/4	1	4-1/2	1.000	.510	.880
1	1-1/8	4-1/2	1.000	.680	.980
1-1/2	1-3/8	5	1.500	1.000	1.000

[1] Distance across flats of nexagon bar.

[2] "D" diameter for testing corresponding sizes of angle drive wrenches shall be not less than 75 percent of that shown.

Page 8

Figure 6: In the drawings, delete "Bolt" and substitute "Test specimen".

Page 9

4.6.2, last sentence: Delete "bolt".

Add the following paragraphs:

"4.8 Sound pressure level test. The sound pressure level test shall be conducted in accordance with the applicable provisions of ANSI S5.1, except as modified herein. The test fixture shall be equivalent to figure 18 of ANSI S5.1 and the acceptable limits shall be as specified in 3.10.1.

4.8.1 Acoustical calibration. The entire instrumentation system shall be calibrated before each test series, allowing a minimum instrument warmup period of 5 minutes if transistorized and 1/2 hour if vacuum tube. Recalibration shall be performed if any instrument adjustment is necessary during progress of the test.

4.8.2 Background sound level. The ambient noise level shall be at least 10 dbA less than the measurement taken with the tool running in all tool and microphone orientations. In addition, the sound produced by the energy absorbing device used in the "on load" test must be at least 10 dbA below the machine's own sound output."

5.1: Delete and substitute:

"5.1 Preservation, packaging, packing, and marking. Impact wrenches shall be preserved, packaged, packed, and marked in accordance with PPP-P-40. The level of preservation, packaging, and packing shall be level A, B, or C as specified (see 6.1)."

5.2, 5.2.1 and 5.2.2: Delete in their entirety.

6.1(g): Delete.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.

Page 9 (con.)

Add the following new paragraph:

"6.2.2 Maximum sound pressure levels have been set to insure against occupational noise-induced hearing losses. The tools covered by this specification are considered intermittent duty tools, used in short burts of two minutes duration or less, 0.5 "on-fraction". The exposure time for tool sizes up to and including 1/2 inch is four hours. The larger sizes are considered to be less intermittent, and have an exposure time of two hours."

Page 10

6.3: Delete and substitute:

"6.3 With respect to products requiring qualification, awards will be made only for products which are at the time set for opening of bids, qualified for inclusion in applicable Qualified Products List QPL-OO-W-891, whether or not such products have actually been so listed by that date. The attention of the suppliers is called to this requirement, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. The activity responsible for the Qualified Products List is the Naval Ship Engineering Center, Prince George's Center, Center Building, Hyattsville, Maryland 20782, and information pertaining to qualification of products may be obtained from that activity. Application for Qualification tests shall be made in accordance with "Provisions Governing Qualification SD-6" (see 6.3.1).

"6.3.1 Copies of "Provisions Governing Qualification SD-6" may be obtained upon application to Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, Pennsylvania 19120."

Under "Preparing activity": Delete "GSA-FSS" and substitute "Navy - SH".

Preparing activity:
Navy - SH
(Project 5130-N253)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:00Z
Check the source to verify that this is the current version before use.