INCH-POUND

MIL-C-48551 (AR)
AMENDMENT 3
10 APRIL 1991

SUPERSEDING
AMENDMENT 2
10 July 1988

MILITARY SPECIFICATION

CARTRIDGE, CALIBER .38 SPECIAL BALL, PGU-12/B

This amendment forms a part of Military Specification MIL-C-48551 (MU), dated 9 June 1975, and is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, DRAWINGS:

Delete "F7553763 - Packing and Marking; Cartridge, Caliber .38, Special Ball, Cartons; Box Ammunition, M2A1; Box, Wirebound." and substitute "F9396206 - Packaging and Marking for Wirebound Box Assembly for Cartridge, Small Caliber".

PAGE 2

3.5, line 2:

Delete "plus or minus 25 ft/sec" and substitute "plus 50 ft/sec minus 25 ft/sec".

PAGE 4

4.3.2, Delete in its entirety and substitute the following:

"4.3.2 Examination. Each charged cartridge case shall be examined for propellant charge (wt) minimum, requirement of 3.12. Method of examination shall be approved by the contracting officer. The equipment design shall provide control(s) that will assure rejection of defective propellant charge (wt), in the cartridge case. One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a class basis in accordance with the classification of defects, Table I, using applicable sampling plans and acceptance criteria of MIL-STD-105. The acceptance quality level (AQL) for the major class shall be 0.25 percent and the AQL for the minor class shall be 1.50 percent.".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:31Z
Check the source to verify that this is the current version before use.

PAGE 7

* 4.3.3.1: Delete in its entirety and substitute the following:

"4.3.3.1 Primer sensitivity. Prior to performance of the tests cited in Table II, a sample of primed cases shall be tested for primer sensitivity. The sample shall be selected from the entire lot or from individual sub-lots, at the option of the contractor, provided that the size of each sub-lot is not less than 200,000. The test sample shall be representative of the entire lot or sub-lot as applicable, and shall consist of the quantity required for performance of a complete run-down test wherein fifty primers are tested at each height. If the average critical height (H) plus five standard deviations (5 Sigma) exceeds 11 inches, or if the average critical height (H) minus two standard deviations (2 Sigma) is less than 1 inch, the lot or sub-lot shall be rejected subject to performance of a second complete run-down test wherein one hundred primers are tested at each height. Failure of the second sample to comply with the above criteria shall be cause for rejection of the lot or sub-lot as applicable".

* 4.3.3.2, Table II:

Delete "Residual stress (mercurous nitrate)" and substitute "Residual stress (mercurous nitrate) 1/".

Under propellant charge (wt) 5/ delete quantity "50" and substitute "315".

PAGE 11

* 4.4.11: Delete in its entirety and substitute the following:

"4.4.11 The primer sensitivity test shall be conducted on empty primed cases in accordance with TECP 700-700, Vol. III. The primed cases may be obtained by either of the following methods, provided that the method is consistent throughout the entire sample:

a. Preferred method: Primed cases shall be obtained by selecting samples from primed, unloaded cartridges (prior to loading), providing that these samples are representative of the loaded cartridge lot.

b. Alternate method: Primed cases may be obtained for special cases by disassembly of complete cartridges which have been randomly selected from the loaded cartridge lot. This disassembly shall be accomplished in such a manner as to cause the least possible distortion of the cartridge case."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:31Z
Check the source to verify that this is the current version before use.

5.1, line 2: Delete "F7553763" and substitute "F9396206".

NOTE: The margins of the amendment are marked with asterisks to indicate where changes additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity
Army - AR

(Project 1305-AD27)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:31Z
Check the source to verify that this is the current version before use.