MIL-D-51370A(EA)
16 January 1986
SUPERSEDING
MIL-D-51370(MU)
30 May 1973

MILITARY SPECIFICATION

DISPERSER, RIOT CONTROL AGENT, PORTABLE, 3 GALLON, M33

This specification is approved for use within U.S. Army Chemical Research and Development Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers *one* type of disperser.

2* APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

PPP-B-26 - Bag, Plastic, (General Purpose)'
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-C-1120 - Cushioning Material, Uncompressed Bound Fiber, for Packaging.
PPP-F-320 - Fiberboard: Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes.
PPP-P-291 - paperboard, Wrapping and Cushioning.
PPP-T-76 - Tape, Packaging, Paper (For Carton Sealing).

: Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed: to: Commander, U.S. Army Chemical Research and Development Center, ATTN: SMCCR-SPD-TS, Aberdeen Proving Ground, MD 21010-5423 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 1040

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116 - Preservation, Methods of.
MIL-B-117 - Bags, Sleeves and Tubing - Interior Packaging.
MIL-B-2427 - Box, Ammunition Packing; Wood, Nailed.
MIL-c-5501/7 - Caps and Plugs, Protective, Dust and Moisture Seal (Cap-Plug, General Purpose).

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

2.1.2 Other Government documents and drawings. The following other Government documents and drawings form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation

DRAWINGS AND TECHNICAL DATA PACKAGE LIST (TDPL)

U.S. ARMY ARMAMENT, MUNITIONS AND CHEMICAL COMMAND

CHEMICAL RESEARCH AND DEVELOPMENT CENTER

TDPL 116-3-54 - Disperser, Riot Control Agent, Portable, 3 Gallon, M33.

(Copies of specifications, standards, drawings and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence, Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on TDPL 116-3-54 or on the Subsidiary drawings shall conform to the specifications listed thereon or to the specific characteristics set forth on the drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

3.1.2 Components. All components of the disperser shall *conform* to the specifications and drawings listed on TDPL 116-3-54 and subsidiary drawings.

3.2 Assembly. The disperser shall be assembled as shown on Drawing 116-3-54.

3.3 Functioning. When the high pressure cylinder is charged to **2100 + 100** pounds per square inch gage (psig), the regulator shall deliver air at 180 + 20 psig, the gun shall function freely, and the assembly shall not leak when tested in accordance with 4.4.4.1.

3.4 Container (Drawing 116-3-101).

3.4.1 Leakage and deformation. The container shall not leak or be permanently deformed when subjected to a minimum hydrostatic pressure of 350 psig for l-minute when tested-in accordance with 4.4.4.2.

3.4.2 Rupture. The container shall not rupture prior to sustaining a minimum hydrostatic pressure of 800 psig when tested in accordance with 4.4.4.3.

3.5 Gun. The gun shall function freely and not leak when subjected to a minimum hydrostatic or air pressure of 180 + 20 psig when tested in accordance with 4.4.4.4.

3.6 Container assembly. The container assembly shall not leak at a minimum air pressure of 200 psig when tested in accordance with 4.4.4.5.

3.7 preproduction. Prior to the start of regular production, a preproduction sample of dispersers and components shall be produced for examination and tests in accordance with this specification.

3.8 Workmanship. The disperser and components shall be free from damage and foreign matter that could impair their intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system *or* quality program.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 preproduction inspection.

4.3.1 Lot. A preproduction sample of five assembled dispersers, *38* containers and five guns shall be manufactured using the same methods, materials, equipment, and processes as will be used during regular production.

4.3.2 Inspection procedure.

4.3.2.1 For nondestructive tests. The assembled dispersers shall be tested in accordance with 4.4.4.1. The containers shall be tested in accordance with *4.4.4.2*. **The guns** shall be tested in accordance with 4.4.4.4.

1.3.2.2 For destructive tests. Twenty-two containers shall be tested in accordance with 4.4.4.3. If one container fails the test, the remaining sixteen containers shall be tested in accordance with 4.4.4.3.

4.3.3 Acceptance/rejection criteria. The preproduction sample shall comply with 1.3.2.1 and 4.3.2.2 to be acceptable except for the containers. If two or more containers fail the test the entire sample of containers shall be destroyed. The contractor shall obtain written approval from the contracting activity prior to proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. For rupture test, a lot shall consist of 200 consecutively manufactured containers of one interfix number.

4.4.2 Sampling for destructive test. One container shall be taken at random from each lot.

4.4.3 Inspection procedures.

4.4.3.1 For examination and nondestructive test. The disperser and the level A packaging shall be examined in accordance with the classification of defects and with MIL-STD-105. Each assembled disperser shall be tested in

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

accordance with 4.4.4.1. The acceptance number is zeros Each container shall be tested in accordance with 4.4.4.2. Each gun shall be tested in accordance with 4.4.4.4.

4.1.3.2 For destructive test. Each sample agent container shall be tested in accordance with 4.4.4.3. A failure of any one sample to meet the specified pressure shall be cause to reject the entire lot from which the sample was drawn.

4.4.3.3 Critical defects. Each cylinder in the lot shall be inspected for its critical characteristics listed in the classification of defects.

4.4.3.4 Classification of defects.

(a) Cylinder, compressed gas (Drawing *116-3-64)*.

Categories	Defects
Critical:	
1	Torque incorrect

(b) Container assembly (Drawing 116-3-74).

Categories	Defects	Acceptance standards
Critical:	None defined	
Major:	AQL 1.0 percent defective	
101	Leakage	*4.4.4.5*

(c) Frame assembly (Drawing 116-3-67).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Component missing or incorrectly assembled
102	Dimension (2.88) incorrect
103	Dimension (6.88) incorrect
104	Dimension (2.25) incorrect
105	Dimension (3.00) incorrect
106	Dimension (13.12) incorrect
107	Angle (30° ± 5°) incorrect
108	Nameplate missing or incorrectly marked
109	Protective finish missing or incorrect

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

110	Clamping incorrect (use an empty agent tank and an unpressurized air cylinder to check the strap assemblies for proper clamping and snug fit)
111	Workmanship (rivets loose, metal straps bent, damage, foreign matter, burrs, sharp edges) (3.8)

(d) Jet spray unit (Drawing 116-3-96).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Diameter of hole incorrect
102	Finish at hole incorrect
Minor:	AQL 4.0 percent defective
201	Counterbore incorrect
202	Length of spray tip incorrect

(e) Orifice (Drawing 116-3-107).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	O.D. incorrect
102	I.D. incorrect
103	Length incorrect

(f) Agitator (Drawing 116-3-106).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Torque incorrect

(g) Container (Drawing 116-3-101).

Categories	Defects	Acceptance Standards
Critical:		
1	Leakage and deformation	4.4.4.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

(h) Packaging (section 5).

Categories	Defects
Critical:	None defined
Major:	AQL 4.0 percent defective
101	Components or repair parts missing
102	Components and repair parts not cleaned and dried as specified
103	Preservation missing
104	Packaging method incorrect
105	Container incorrect
106	Containers closure incorrect
107	Container or package damaged
108	Marking missing or incorrect
109	Strapping loose or missing
110	*Carriage* bolts not peened

4.4.4 Tests. Tests shall be conducted as follows:

4.4.4.1 Functioning. Connect a test gage between the low pressure pneumatic hose and the quick-disconnect at the regulator outlet. Charge the high pressure cylinder to 2100 ± 100 psig air, and connect it to the disperser. slowly open the high pressure valve. Record the regulator outlet pressure when needle has stabilized. Using a suitable leak-detecting solution, check all joints for leakage. Discharge the disperser in 5-second bursts, pausing 5 seconds between bursts to check the gun for leakage. During periods of air flow, listen for a "rattling" sound, indicating presence of agitator (see 6.2)-

4.4.4.2 Leakage and deformation. The container shall be subjected to the specified hydrostatic pressure for the indicated time (see 6.2).

4.4.4.3 Rupture. The container shall be subjected to hydrostatic pressure until the container leaks or ruptures. Record the leak or rupture pressure.

4.4.4.4 Gun. The gun shall be connected to a regulated source of air or hydrostatic pressure. Gradually increase the pressure to 180 ± 20 psig. Maintain that pressure for a minimum period of 1 minute, and observe for leakage. Pull the trigger to operate the gun for a 5-second burst. The gun shall function freely and when the trigger is released the flow of air or water shall stop.*

(Note: This test may be performed at the same time as 4.4.4.l with the air connected to the disperser*

4.4.4.5 Container assembly. The container less the cam action closure shall be tested for the specified pressure for the specified time and checked with a suitable leak detection solution.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Cleaning. The interior and exterior surfaces of the disperser components shall be cleaned, as necessary, to be free of foreign matter that could result in deterioration or affect satisfactory performance of the the assembled unit in use. Cleaning shall be in accordance with cleaning process Cl and drying shall be in accordance with any of the drying procedures outlined in MIL-P-116.

5.2 Preservation and packaging. Level shall be as specified (see 6.1).

5.2.1 Level A.

5.2.1.1 Disperser assembly. The agent container, air cylinder and associate hoses and fittings, cleaned in accordance with 5.1, shall be prepared as follows : The wing nut shall be tightened on the neck of the agent container to secure the adapter and the manifold and prevent leakage. The discharge opening in the manifold shall be closed by use of a plastic cap-plug conforming to MIL-c-5501/7. The loose harness shall be secured to the frame as necessary to prevent excessive movement.

5.2.1.2 Gun and hose. The gun and hose shall be cleaned in accordance with 5.1, and packaged as follows. The unattached hose and the gun shall have the openings closed by means of plastic capplugs conforming to MIL-C-5501/’7. The hose shall be loosely coiled and with the gun shall be enclosed together in a fiberboard box conforming to class domestic, style FOL, type CF, grade 175, SW of PPP-B-636, having inside dimensions in inches of 10 by 2-3/4 by 15-1/4 length, width and depth respectively. The hose shall not be kinked or bent severly enough to cause permanent deformation that would affect its performance in use. A piece of bound fiber cushioning material, size 1 by 9 by 12 inches and conforming to type IV, Class A, of PPP-C-1120 shall be included to restrict free movement of the gun and hose. The box shall be closed in accordance with method II or IV in the appendix to PPP-B-636. The closed box shall be sealed in a barrier bag conforming to type II, Class E, style 1 of MIL-B-117. Included air volume shall be kept to a practicable minimum when sealing the bag .

5.2.1.3 Technical publications. Applicable technical publications shall be sealed within a polyethylene bag, size 12 by 14 inches, conforming to type II, style 1 of PPP-B-26. Included air volume shall be kept to a practical minimum when bag is sealed.

5.2.1.4 Closure plug, cam-action type. The closure plug shall be sealed, one per bag, in a polyethylene bag, size 4 by 6 inches conforming to type I, style 1, of PPP-B-26. Included air volume shall be kept to a practical minimum when sealing the bag.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

5.2.1.5 Static strap and clamp. The strap and clamp shall be sealed, one of each, together in a polyethylene bag, size 4 by 6 inches, conforming to type I, style 1, of PPP-B-26. Included air volume shall be kept to a practicable minimum when sealing the bag.

5.2.1.6 Cylinder, compressed gas. The compressed gas cylinder shall be packaged within a fiberboard box conforming to grade W5c, style RSC of PPP-B-636. Inside dimensions of the box shall be 4-1/4 by 4-1/4 by 17 inches length, width and depth respectively. A mailing tube measuring 2 inches in diameter by 2-3/8 inches long shall be used as a collar to surround the cam-action type closure and shall bear on the cylinder neck. As an alternate, the collar may be formed from PPP-P-291, style 1, type 111 material measuring 3 by 22 inches. The loose end shall be secured with PPP-T-76 tape. Closure of the fiberboard box shall be in accordance with the overseas closure requirements of PPP-B-636, appendix.

5.2.1.7 Container assembly, agent. The agent container shall be packaged within a fiberboard box conforming to W5c, style RSC of PPP-B-636. Inside dimensions of the box shall be 7-1/8 by 7-1/8 by 23-3/4 inches length, width, and depth respectively A sleeve conforming to grade W5c of PPP-F-320 shall be constructed to measure 4 by 4 by 3-3/8 inches length, width, and depth respectively, having a 2 inch MFR joint. The sleeve shall be placed over the cam-action closure to rest on the cylinder neck. The MFR joint shall be stapled in six places. Closure of the fiberboard box shall be in accordance with the overseas closure requirements of PPP-B-636, appendix.

5.2.2 Level C.

5.2.2.1 Disperser assembly. The disperser assembly shall be prepared in accordance with 5.2.1.1.

5.2.2.2 Gun and hose. The gun and hose shall be packaged in accordance with 5.2.1.2 except the barrier bag wrap is omitted.

5.2.2.3 Technical publications. Packaging shall be in accordance with 5.2.1.3.

5.2.2.4 Closure plug, cam-action type. The closure plug shall be packaged in accordance with 5.2.1.4.

5.2.2.5 Static strap and clamp. Packaging shall be in accordance with 5.2.1.5.

5.3 Packing. Level shall be as specified (see 6.1).

5.3.1 Level A.

5.3.1.1 Disperser assembly. The disperser assembly, gun and hose, technical publications, strap and clamp and closure plug, prepared in accordance with 5.2.1, shall be packed together in a shipping storage chest in accordance with Drawing 116-3-97.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

5.3.1.2 Cylinder, compressed gas and container assembly, agent. Two of each of the cylinders (cylinder, compressed gas and container assembly, agent), packaged as specified above, shall be packed together in a wood box conforming to type II, class 2, grade A of MIL-B-2427. The box shall be of minimum size to contain the four packaged cylinders. Fiberboard pads conforming to grade W5c of PPP-F-320 shall be used as required to restrict movement within the container.

5.3.2 LevelB. Packing shall be in accordance with 5.3.1 except the box shall be Grade B without wood preservative treatment.

5.3.3 Level C. The disperser assembly, gun and hose, technical publications, strap and clamp and closure plug, prepared or packaged as specified shall be packed together in a shipping and storage chest in accordance with Drawing 116-3-97 except the box (chest) shall be Grade B without preservative treatment.

5.4 Marking. In conjunction with information furnished in the contract or order, marking shall be as specified herein.

5.4.1 Package marking. The component packages (5.2) shall be marked by labeling in accordance with requirements for interior package marking in MIL-STD-129. The disperser assembly shall be marked by tagging in accordance with MIL-STD-129. Marking shall include information pertinent to the Federal Stock Number, item description, quantity and unit of issue, contract or purchase order number, level of preservation and packaging and date packaged, as applicable. Technical publications packages will not require additional identification marking when enclosed document is identifiable through the transparent bag .

5.4.2 Packing marking. The shipping and storage container shall be marked in accordance with Drawing 116-3-83.

5.5 Palletization. Unless otherwise specified in the contract or order, dispensers shall be palletized in accordance-with Drawing 116-3-109.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Level of packaging and packing required.
(c) Preproduction.

(1) Time allowed for contractor submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

(3) Time required for the Government to notify the contractor whether to proceed with production.

(d) Serial numbers assigned for the dispersers.

6.2 Caution. Due to the hazards inherent in testing with high pressures, contractors are advised that every precaution possible should be exercised for the safety and protection of personnel engaged in such testing.

6.3 Component specification. The following specifications reflect the components required to complete this item:

Regulator	MIL-R-51516(EA)
Service Kit, *M254* -	MIL-S-51371 (EA)

Custodian:

Army-EA

Preparing activity:

Army - EA

Project No. 1040-A171

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form *for use* in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge (DO NOT STAPLE), and mailed. In block S, be as specific as possible about particular problem areas such as wording which required interpetation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is fried out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers deviations or clarification of specification requirement on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion *of the* referenced document(s) or to amend "contractual requirements.

(Fold along this line)

(Fold along this line)

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 Alexandria, VA

POSTAGE WILL BE PAID BY

Commander
U.S. Army Chemical Research and Development Center
ATTN : SMCCR-SPD-TS
Aberdeen Proving Ground, MD 21010-5423

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

{See Instructions - Reverse Side)

DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-D-51370A(EA)	DISPERSER, RIOT CONTROL AGENT, PORTABLE, 3 GALLON, M33

3a NAME OF SUBMITTING ORGANIZATION .

. ADDRESS(Street, *City,Stafe,ZIP Code)*

4.TYPEOF ORGANIZATION (Murk one)

•1 VENDOR

• 1 USE R

MANUFACTURER

❑ OTHER (Specify):

5. PROBLEM AREAS

a Paragraph Number arid Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

70. NAME OF SUBMiTTER ***(Last, First, MI)*** - Optionai

b. WORK TELEPHONE NUMBER (Include Area *Code)* - **Optional**

. MAILING ADDRESS *(Street, City, State, ZIP Code)* - Optional

8. DATE OF SUBMISSION (YYMMDD)

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil - Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

MIL-D-51370A(EA)
AMENDMENT 1
20 April 1987

MILITARY SPECIFICATION

DISPERSER, RIOT CONTROL AGENT, PORTABLE, 3 GALLON, M33

This amendment forms a part of MIL-D-51370A(EA), dated 16 January 1986, and is approved for use within the Chemical Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2 "

Under "MILITARY STANDARDS" add the following:

"Ms51525 - Adapter, Straight, Tube to Boss, O-Ring, 37 Deg. Flared"

PAGE 7

After paragraph 4.4.3.4(h) add the following *new* paragraph:

"(i) Regulator assembly (Drawing 1.6-3-114).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	External components missing or incorrectly assembled
102	"O" ring missing (Note 6)
103	Alignment incorrect (Note 5)
104	Nipple class or end style incorrect
105	Thread incorrect (MS51525-B4)
106	Strainer missing or loose (Drawing 116-3-71)"

Custodian:

Army-EA

Preparing activity:

Army - EA

project No. 1040-A183

AMSC N/A

FSC *1040*

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.

NOTICE OF INACTIVATION
FOR NEW DESIGN

INCH-POUND

MIL-D-51370A(EA)
NOTICE 1
28 September 1995

MILITARY SPECIFICATION

DISPERSER, RIOT CONTROL AGENT, PORTABLE, 3 GALLON, M33

This notice should be filed in front of MIL–D–51370A(EA), dated 16 January 1986, with Amendment 1, dated 20 April 1987.

MIL–D-51370A(EA) is inactive for new design and is no longer used except for replacement purposes.

Preparing activity:

Army - EA

Project No. 1040-A218

AMSC N/A

FSC 1040

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:58Z
Check the source to verify that this is the current version before use.