MILITARY SPECIFICATION

DRILLING MACHINE, UPRIGHT, FLOOR TYPE, ROUND AND
BOX COLUMN, SLIDING HEAD, PLAIN TABLE, POWER FEED

This Amendment forms a part of Military Specification MIL-D-80002D dated 21 October 1982 and is approved for use by all Departments and Agencies of the Department of Defense.

Page 5

3.3.7 Delete in its entirety and substitute the following: "3.3.7 Dials. All feed screw dials that indicate stock removal or tool movement shall be graduated in increments not larger than 0.001 inch. Quill position shall be indicated by either a graduated scale engraved on or attached to the quill, or by a feed depth dial. The scale or the feed depth dial shall be graduated in increments of not more than 1/8 inch. Dial diameters shall be such that graduations may be read from the normal operating position."

Page 7

3.4.4 Delete in its entirety and substitute the following: 3.4.4 Column. "The column shall be mounted on the base and reinforced to provide support and minimize deflection. Machines with cylindrical columns shall be cross sectionally round on the lower column with the exterior surface machined for vertical adjustment of the work table; and the upper columns shall be cross sectionally round with the exterior surface machined for vertical adjustment of the sliding head or rectangular with machines guideways for vertical adjustment of the sliding head. Machines with box lower columns shall have machined guideways for vertical adjustment of the work table; and the upper columns shall be sectionally round with the exterior surface machined for vertical adjustment of the sliding head or rectangular with machined guide ways for vertical adjustment of the sliding head.

Page 7

3.4.7 Delete in its entirety and substitute the following: 3.4.7 Sliding Head. "The sliding head shall be an iron or iron alloy casting or a steel weldment, arranged to support the spindle/quill assembly. The head shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:31Z
Check the source to verify that this is the current version before use.

mounted to the column and be vertically adjustable. Means shall be provided for adjustment to take up wear. A locking device shall be provided to lock the sliding head in position after adjustment. The sliding head shall be counterbalanced or vertically adjusted by the use of a high mechanical advantage drive to facilitate ease of adjustment.

3.4.7.1 Delete in its entirety and substitute the following: 3.4.7.1 Spindle/Quill Assembly. The quill shall be machined of steel alloy, and shall be fitted to the sliding head. Vertical travel of the quill shall be accomplished by means of a rack and pinion drive. Quill position shall be indicated by either a graduated scale engraved on the quill in increments of not more than 1/8 inch, or by a feed depth dial. The spindle shall be machined from steel alloy and shall rotate within the quill on ball or roller bearings. The characteristics of the spindle shall comply with ANSI B5.10, The quill/spindle assembly shall be counterbalanced and be power fed for accomplishing performance specified herein. The spindle feed shall be obtained through a variable speed motor drive arrangement coupled to the pinion drive by a positive engagement type clutch.

Page 10

TABLE II: Delete "Column guideways with working surface of the worktable, in longitudinal and tranverse planes" and substitute "Spindle/quill assembly travel square with working surface of the worktable, in longitudinal and tranverse planes. Maximum Allowable Deviation 0.003"/12"."

Custodians
Army - AL
Navy - SH
Air Force - 99

Review Activities
Army - AL
Navy - SH
Air Force - None
DLA - GS

Preparing Activity:
DLA - IP

Project Number
3413-0126

FSC 3413

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:31Z
Check the source to verify that this is the current version before use.