MILITARY SPECIFICATION

ELECTRICAL DISCHARGE MACHINE, VERTICAL, RAM AND QUILL TYPE

This amendment forms a part of Military Specification, MIL-E-80023D, dated 22 May 1987 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Delete paragraph 1.1 and substitute the following paragraph:

"1.1 Scope. This specification covers one type of electrical discharge machine having a vertical ram and quill, electro-hydraulic feed or DC servo drive with external power supply and complete equipment and accessories as specified herein."

PAGE 5

Paragraph 3.2.1.2 Digital readout system., line 8, delete "0.0001 inch" and substitute "0.0004 inch."

Paragraph 3.2.1.2.2, line 3, delete "0.70 inch high" and substitute ".375 inch high."

PAGE 11

Paragraph 3.4.6.1 Capabilities., delete subparagaraph a in its entirety and substitute the following: "a. When specified, units having current output capacities of 20 to 150 amperes shall be capable of controlling the overcut over a range of 0.0005 to 0.004 inch per side and producing a surface finish of 10 microinch."

Subparagraph b, line 2, delete "0.15 inches" and substitute "0.025 inch."

AMSC N/A FSC 3410
DISTRIBUTION STATEMENT A. Approved for public release; distribution in unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.

PAGE 13

Paragraph 3.9.1 Optional equipment., subparagraph d, delete in its entirety.

PAGE 16

Paragraph 4.7.5 Smoothest surface finish., delete in its entirety.

Custodians:
Navy - SH
Air Force - 99

Review activities:
Army - CR
Navy - AS, MC
Air Force - 84
DLA - GS

User activities:
Army - AR
Navy - OS

Preparing activity:
DLA - IP

Project (3410-0044)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:32Z
Check the source to verify that this is the current version before use.