MILITARY SPECIFICATION

IGNITION ELEMENT, ELECTRICAL, PARTS FOR

This amendment forms a part of Military Specification MIL-I-50860 (MU) dated 18 February 1971, and is approved for use by the U.S. Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.3, Line 2, delete: "...1.30..." and substitute: "...1.40...".

3.4 Delete in its entirety.

3.5:

Lines 2 and 3 delete: "...direction..." and substitute: "...plane...".

Line 3, delete: "...40 pounds..." and substitute: "...30 pounds...".

PAGE 6

4.3.2, Last line, delete: "...4.3.5)" and substitute "...4.3.4)".

4.3.2.1:

Category 104, delete: "True position of lance pattern diameter to I.D. of cup" and substitute: "True position of intersection of slit pattern to I.D. of cup."

Category 204 delete: "...hole" and substitute: "...cup wall".

FSC 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

PAGE 7

4.3.2.3, Category 205, delete "(see 3.6)" and substitute: "(see 3.6 and 6.6)".

PAGE 8

4.3.2.4, Category 102, delete in its entirety.

PAGE 9

4.3.2.7, Category 102:

Delete: "Inside diameter of outer edge" and substitute: "Outside diameter".

Delete: "07002" and substitute "07006".

PAGE 10

4.3.3.2:

Line 2 delete: "...MIL-STD-414, Inspection Level IV..." and substitute: "...MIL-STD-105, Sampling Plan S-4...".

Last line, delete: "(see 6.6)".

4.3.3.3, Delete in its entirety and substitute:

"Relative quickness (informational). The relative quickness of the front support shall be determined at the time of first article testing at 8500 psi using a sufficient number of randomly selected front supports to provide a loading density of 0.2 g/cc in a nominal 200 cc closed bomb. A minimum of three separate tests shall be conducted. Testing shall be in accordance with MIL-STD-286, Method 801.1 and shall be conducted at 70 $\pm$ 2°F. A minimum of three comparison tests shall be performed using M26E1 propellant (See 6.5)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.

PAGE 11

4.3.3.4:

Lines 2 and 5 delete: three references to "...direction..." and substitute "...plane..."

Line 3 delete: ..."MIL-STD-414, Inspection Level IV..." and substitute "...MIL-STD-105 Sampling plan S-4...".

Line 7 delete: "...(see 6.6)".

4.3.3.5:

Line 2 delete: "...MIL-STD-414, Inspection Level IV..." and substitute "...MIL-STD-105, Sampling Plan S-4...".

Line 6 delete: "...(see 6.6)".

PAGE 14

6.5, Delete in its entirety and substitute:

"6.5 submission of test results. One copy of all results of informational testing shall be forwarded to Picatinny Arsenal, ATTN: SMUPA-ND2."

6.6, Delete in its entirety and substitute:

"6.6 Definition of chips. Chips at intersecting areas on the front support may be 3/16 inch maximum in any dimension. If this condition exists, then any other set of adjacent intersecting areas shall be limited to chips of 1/16 inch maximum in any direction."

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1320-A725)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:40Z
Check the source to verify that this is the current version before use.