INCH-POUND

MIL-PRF-71229C(AT)
AMENDMENT 1
13 May 2002

PERFORMANCE SPECIFICATION

MOUNT, GUN, 120 MM

This Amendment forms a part of MIL-PRF-71229C(AT), dated 23 August 2001, and is approved for use by the U.S. Army Tank-automotive and Armaments Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

Paragraph 3.5.2 - Delete and substitute:

"3.5.2 Identification. Unless otherwise specified (see 6.2), each gun mount shall have a primary permanent serial number identifier placed as an integral part of the cradle near the breech (see 4.7.2)."

PAGE 6

Paragraph 3.6.1.1 - Delete and substitute:

"3.6.1.1 Recoil cycle time. The recoil cycle time under climatic conditions at 100% and 113 + 4% impulse levels between 0 degrees and 35 degrees elevation shall be as follows:

Temperature (+/-5°F)	Elevation in degrees (+/-2)	Max cycle time (sec)
-50	0 & 35	N/A
+70	0	0.6
+70	35	2.5
+125	0 & 35	0.6

PAGE 12

Paragraph 4.7.2 - Delete and substitute:

"4.7.2 Identification inspection. The presence and correct assignment of the primary serial number shall be verified visually."

Custodian:
Army - AT

Preparing Activity:
Army - AT

(Project 1015-0348)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:30Z
Check the source to verify that this is the current version before use.