INCH-POUND

MIL-P-63137B (AR)
AMENDMENT 2
31 July 1990
SUPERSEDING
AMENDMENT 1
29 January 1982

MILITARY SPECIFICATION

PROJECTILE, 8-INCH, HE, RA, M650
WARHEAD SECTION, FORWARD

This amendment forms a part of Military Specification MIL-P-63137B (AR), dated 18 December 1981, and is approved for use within the U.S. Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

4.3.1: Delete: "Warhead Section Forward" and substitute: "Warhead Section Forward before coating."

Add the following:

"Warhead Section Forward after anodic coating, 9287954, 5 each.
Warhead Section Forward after all coating, 9287954, 10 each.

PAGE 5

4.3.2, Table I: Delete: "Examination for Defects" and substitute: "Examination for defects before coating."

Add the following:

"Examination for defects after anodic coating, 5 each, 3.2, 4.4.2.2.

Examination for defects after all coating, 10 each, 3.2, 4.4.2.2."

PAGE 8

4.4.2.1: Delete: "Warhead Section, Forward" from title block and substitute: "Warhead Section, Forward before Painting."

Delete Minor defects 204, 205, and 215.

Add Paragraph 4.4.2.2: Title: "Warhead Section, Forward after painting", Drawing Number "928795."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:18Z
Check the source to verify that this is the current version before use.

4.4.2.2: Add the following Minor defects:

"201 Protective Finish improper or missing, 0.65%, 3.2, 4.5.1.
202 Painted surface with total exposed or damaged area in excess of 1/4 square inch, 0.65%, 3.2, Visual
203 Marking missing or unidentifiable, 0.65%, 3.2, Visual."

PAGE 9

* 4.4.3.1.1 Delete in its entirety and substitute the following:

"4.4.3.1.1 Salt spray. After qualification in accordance with TT-C-490, two (2) salt spray samples shall be taken each week, one during the first 30 minutes of production and a second at any other time. Failure to comply with the requirements of the applicable drawings shall be cause for taking the corrective action prescribed in TT-C-490."

* 4.5.1.1 Salt spray testing. Salt spray testing shall be accomplished on production warheads or sectioned warheads that were acceptable at the time of conversion coating and were sectioned subsequent to conversion coating. If sectioned warheads are used, sectioning shall be accomplished to allow testing of all major areas of the warheads on an alternating basis. The salt spray test shall be performed utilizing the equipment and procedures specified by ASTM-B117 and TT-C-490 with the exception that test samples shall be selected in accordance with 4.4.3.1.1.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1320-AC13)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:18Z
Check the source to verify that this is the current version before use.