MILITARY SPECIFICATION

TREEDOZERS, TRACTOR MOUNTING

This amendment forms a part of Military Specification MIL-T-52582A(ME), dated 20 September 1972, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 1

2.1, under SPECIFICATIONS, Federal, add:
"XX-D-385 - Dispensing Pump, Hand Driven, Liquid Petroleum Fuel."
2.1, under SPECIFICATIONS, Military, delete:
"MIL-D-43095 - Dispensing Pump, Hand Driven, Piston Type."

Pages 2 and 3

2.2, delete:

"DEPARTMENT OF THE ARMY

SC-4940-97-CL-E05 - Department of the Army Supply Catalog - Shop Equipment, Contact Maintenance, Truck Mounted.

(Application for copies should be addressed to Commanding Officer, U.S. Army Adjutant General, Publications Center, 1655 Woodson Road, St. Louis, MO 63114.)"

Page 4

3.5, line 5 from top of page, after "4940-97-CL-E05" insert "(see 6.7)".
3.7.1, line 3, after "and limbs." insert: "The cab shall conform to SAE J395, Roll Over Protective Structure (ROPS) and SAE J231, Falling Object Protective Structure (FOPS)."

Page 5

After 3.7.1.5, add the following new paragraphs:
"3.7.1.6 Seat belt. A seat belt conforming to SAE J386, type I shall be provided, including all hardware and instructions for mounting on the Government-loaned tractor.
3.7.1.7 Cab mounts. The rear mounts of the cab shall be bolted to the level gear case of the tractor and the front mounts of the cab shall be welded to the main frame of the tractor. The cab mounts shall not interfere with operation of the tractor including track oscillation. Each mount shall distribute induced loads over sufficient areas of the tractor so as not to be detrimental to the tractor structure."

FSC 3830

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:26Z
Check the source to verify that this is the current version before use.

Page 6

3.7.5, line 1, delete "MIL-D-43095" and substitute "XX-D-385, type III".

Page 11

4.4, add the following: "In addition to any test specified as part of the initial production test, the Government reserves the right to conduct any and all other tests contained in this specification as part of the initial production test and failure of such additional tests shall have the same effect as failure of those tests specified as initial production tests."

Page 13

4.6.1, table II, add the following:

1	2	3	4		5
"X	X	X	122.	Seat belt and mounting hardware not as specified.	3.7.1.6
X	X	-	123.	Frame mounts not as specified.	3.7.1.7"

4.6.2, table III, add the following:

1	2	3	4	5
"X	-	-	ROPS and FOPS	4.7.7"

Page 14

After 4.7.6, add the following new paragraph:

"4.7.7 Rollover and falling object protective structures. The ROPS and FOPS shall be tested in accordance with SAE J395 and SAE J231 respectively Failure of the structures to meet the requirements of SAE J395 and SAE J231 shall constitute failure of this test."

4.8, lines 5 and 6, delete "equal - - - production inspection" and substitute "in compliance with specification requirements".

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:26Z
Check the source to verify that this is the current version before use.

4.8, add the following: "In addition to any test specified as part of the inspection comparison, the Government reserves the right to conduct any and all other tests contained in this specification as part of the inspection comparison and failure of such additional tests shall have the same effect as failure of those tests specified as inspection comparison."

4.8.1, line 1, delete "any" and substitute "an inspection comparison".

4.8.1, line 3, insert "inspection comparison" between "the" and "treedozer"

Page 16

After 6.6, add the following new paragraph:

"6.7 Supply catalog. The contracting officer should arrange to furnish Supply Catalog 4940-97-CL-E05 as specified in 3.5."

Custodian:

Army - ME

Preparing activity:

Army - ME

Project No. 3830-A147

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:26Z
Check the source to verify that this is the current version before use.