INCH-POUND

MIL-DTL-7885/11
25 April 1996

DETAIL SPECIFICATION SHEET

RIVETS, BLIND, STRUCTURAL, UNIVERSAL PROTRUDING HEAD, 5056 AL ALLOY SLEEVE, MECHANICALLY LOCKED CRES SPINDLE (TYPE I, STYLE A, CLASS 1)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the blind rivets described herein shall consist of this document and the latest issue of MIL-R-7885.

DESIGN AND USAGE LIMITATION. Rivets shall be used in compliance with the limitations of MS33522.

INSTALLATION. The blind rivets shall have the capability of being installed by a tool conforming to MIL-R-85188. Lubricant shall not be removed prior to installation.

REQUIREMENTS:

MATERIAL:

Sleeve: 5056 Al Alloy per QQ-A-430 (UNS A95056).
Spindle: 15-7PH CRES in accordance with AMS 5657 (UNS S15700), or A-286 CRES per AMS5737 (UNS S66286).
Locking Feature: A-286 CRES per AMS 5731 (UNS S66286) or 5056 Al Alloy per QQ-A-430 (UNS A95056).
Lubricant: See general specification (MIL-R-7885).
Grip Adjusting Feature (Optional): AISI 1038 carbon steel (UNS G10380), 8740 alloy steel per AMS 6322 (UNS G87400), or 7050-T73 AL Alloy per QQ-A-430 (UNS A97050).

PROTECTIVE TREATMENT:
5056 Al Alloy: Chemically treated per MIL-C-5541.
15-7 CRES: Cadmium plate in accordance with QQ-P-416, Type I, Class 2 at manufacturer's option.
A-286 CRES: Passivate per QQ-P-35.
1038 or 8740 steel: Cadmium plate in accordance with QQ-P-416, Type II, Class 2.
7050-T73 Al Alloy: Chemically treated per MIL-C-5541.

SURFACE TEXTURE: Surface texture shall have a roughness average of 125 Ra in accordance with ANSI/ASME B46.1.

TOLERANCES: Unless otherwise specified, decimals +/- .010, angles +/- 2 ^{o}.

Unless otherwise specified, dimensions are in inches.

Break all sharp edges and remove all burrs and slivers.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:27Z
Check the source to verify that this is the current version before use.



Optional Driving Anvil gold Colored to Identify Style "A" Rivets.
Head Marking Visible After Installation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:27Z
Check the source to verify that this is the current version before use.

TABLE I

NOMINAL SIZE	BASIC BODY DIA	⌀A		⌀D		H		INSTALLATION HOLE LIMITS	
		MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
4	.125	.260	.240	.129	.125	.064	.054	.132	.129
5	.156	.322	.302	.160	.156	.077	.067	.164	.160
6	.187	.385	.365	.192	.188	.090	.080	.196	.192

TABLE II

GRIP LIMITS		NOMINAL SIZE								
		4			5			6		
MIN	MAX	DASH NO.	L +.000 -.030	K MAX	DASH NO.	L +.000 -.030	K MAX	DASH NO.	L +.000 -.030	K MAX
(a)	.062	01	.161	.380	01	.187	.410	01	.219	.470
.063	.125	02	.224	.450	02	.230	.470	02	.262	.510
.126	.187	03	.287	.510	03	.293	.530	03	.325	.570
.188	.250	04	.349	.570	04	.355	.590	04	.387	.640
.251	.312	05	.412	.630	05	.418	.650	05	.450	.700
.313	.375	06	.474	.700	06	.480	.720	06	.512	.760
.376	.437	07	.537	.760	07	.543	.770	07	.575	.820
.438	.500	08	.599	.820	08	.605	.840	08	.637	.880
.501	.562	09	.662	.880	09	.668	.900	09	.700	.950
.563	.625				10	.730	.960	10	.762	1.010
.626	.687				11	.793	1.02	11	.825	1.070
.688	.750							12	.887	1.130

(a) Do not use part number M7885/11-4-01 below .025 grip.
Do not use part number M7885/11-5-01 below .031 grip.
Do not use part number M7885/11-6-01 below .037 grip.

Source: https://assist.dla.mil -- Downloaded: 2026-01-17T09:27Z
Check the source to verify that this is the current version before use.

EXAMPLE OF PART NUMBER:



Custodians:
Army - AR
Navy - AS
Air Force - 99

Review Activities:
Army - AV
Navy - MC
Air Force - 82

Preparing Activity:
DLA-IS

(Project No. 5320-0812-01)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:27Z
Check the source to verify that this is the current version before use.