MILITARY SPECIFICATION

RIVETS, BLIND, STRUCTURAL, 100° FLUSH HEAD,
5056 AL ALLOY SLEEVE, MECHANICALLY LOCKED 8740 ALLOY STEEL SPINDLE
OVERSIZED DIAMETER (TYPE I, STYLE B, CLASS 2)

This amendment forms a part of MIL-R-7885/7C, dated 18 April 1988, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 2

Change dimension "E" Max values to the following

Nominal Size	E (Max.)
4	010
5	012
6	012

PAGE 3

Change the grip limits for the -02 and add a -04-01 grip Also delete the first two footnotes so the Table reads as follows

TABLE II

Grip Limits		Nominal Sizes								
		4			5			6		
Min	Max	Dash No	L +.000 -.030	K Max	Dash No	L +.000 -.030	K Max	Dash No (a)	L +.000 -.030	K Max
045	062	-01	.200	450						
063	.125	-02	.238	450	-02	266	.470	-02	265	480
126	.187	-03	301	.520	-03	.309	.530	-03	328	550
.188	.250	-04	.363	.580	-04	.371	600	-04	.390	620
.251	.312	-05	426	650	-05	434	.660	-05	453	.680
313	.375	-06	488	.710	-06	.496	.720	-06	515	740
.376	.437	-07	.551	780	-07	.559	.790	-07	.578	.820
.438	500	-08	.613	840	-08	621	.850	-08	.640	890
.501	.562	-09	.676	.900	-09	.684	.910	-09	.703	.950
563	625				-10	.746	.980	-10	.765	1 010
626	687				-11	809	1 040	-11	828	1 070
688	750							-12	890	1 140

(a) Do not use part number M7885/7-6-02 below .073 sheet thickness (grip)

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:27Z
Check the source to verify that this is the current version before use.

Military Interests

Custodians
Army - AR
Navy - AS
Air Force - 99

Review Activities
Army - AV
Navy - MC
Air Force - 82

Preparing Activity
DLA - IS

(Project No 5320-0826)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:27Z
Check the source to verify that this is the current version before use.