MIL-R-7885/9B
18 April 1988
SUPERSEDING
MIL-R-007885/9A(AS)
23 September 1982

MILITARY SPECIFICATION SHEET

RIVETS, BLIND, STRUCTURAL, 100° FLUSH HEAD, NICKEL-COPPER ALLOY SLEEVE, MECHANICALLY LOCKED 15-7PH CRES SPINDLE, OVERSIZE DIAMETER (TYPE I, STYLE B, CLASS 2)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the blind rivets described herein shall consist of this document and the latest issue of MIL-R-7885.

DESIGN AND USAGE LIMITATION. The blind rivets shall be used in accordance with the limitations of MS33522.

INSTALLATION. The blind rivets shall have the capability of being installed by a tool conforming to MIL-R-85188. Lubricant shall not be removed prior to installation.

REQUIREMENTS:

MATERIAL:

Sleeve: Nickel-Copper alloy (Monel) in accordance with QQ-N-281 (UNS N04405).
Spindle: CRES 15-7PH in accordance with AMS5657 (UNS S15700).
Locking Feature: A-286 CRES per AMS 5731 (UNS S66286) or 5056 Al Alloy per QQ-A-430 (UNS A95056).
Lubricant: See general specification (MIL-R-7885).
Grip Adjusting Feature (Optional): 15-7PH CRES per AMS 5657.

PROTECTIVE TREATMENT:

A-286 CRES: Parts manufactured after August 1988 shall be passivated per QQ-P-35.

SURFACE TEXTURE: Surface texture shall be measured per ANSI B46.1 and shall not exceed 125 microinches.


TOLERANCES: Unless otherwise specified, decimals $\pm$.010, angles $\pm$2°.

Unless otherwise specified, dimensions are in inches.

Break all sharp edges and remove all burrs and slivers.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:27Z
Check the source to verify that this is the current version before use.



Optional Driving Anvil Silver Colored to Identify Style "B" Diameter Rivets. Head Marking Visible After Installation.

TABLE I

Nominal Size	Basic Body Dia	A Dia (Theoretical)		D Dia		E		H	Installation Hole Limits	
		Max	Min	Max	Min	Max	Min	Ref	Max	Min
4	.125	.229	.221	.143	.139	.015	.005	.035	.146	.143
5	.156	.290	.282	.176	.172	.015	.005	.047	.180	.176
6	.187	.357	.349	.204	.200	.015	.005	.063	.209	.205

Source: https://assist.dla.mil -- Downloaded: 202610-17T09:27Z
Check the source to verify that this is the current version before use.

TABLE II

Grip Limits		Nominal Sizes								
		4			5			6		
Min	Max	Dash No.	L +.000 -.030	K Max	Dash No.	L +.000 -.030	K Max	Dash No.	L +.000 -.030	K Max
(a)	.125	-02	.238	.450	-02	.266	.470	-02	.265	.480
.126	.187	-03	.301	.520	-03	.309	.530	-03	.328	.550
.188	.250	-04	.363	.580	-04	.371	.600	-04	.390	.620
.251	.312	-05	.426	.650	-05	.434	.660	-05	.453	.680
.313	.375	-06	.488	.710	-06	.496	.720	-06	.515	.740
.376	.437	-07	.551	.780	-07	.559	.790	-07	.578	.820
.438	.500	-08	.613	.840	-08	.621	.850	-08	.640	.890
.501	.562	-09	.676	.900	-09	.684	.910	-09	.703	.950
.563	.625				-10	.746	.980	-10	.765	1.010
.626	.687				-11	.809	1.040	-11	.828	1.070
.688	.750							-12	.890	1.140

(a) Do not use part number M7885/9-4-02 below .045 sheet thickness.
Do not use part number M7885/9-5-02 below .063 sheet thickness.
Do not use part number M7885/9-6-02 below .073 sheet thickness.

EXAMPLE OF PART NUMBER:

M7885/9 - 4 - 02

- 02 — Grip length dash no. in .062-inch increments (see Table II).
- 4 — Nominal sizes in .0312-inch increments (see Table I).
- M7885/9 — Specification Sheet No.

Custodians:
Army - AR
Navy - AS
Air Force - 99

Review Activities:
Army - AV
Air Force - 82
DLA - IS

User Activities:
Navy - MC

Preparing Activity:
Navy - AS
(Project No. 5320-0441)

★U.S. GOVERNMENT PRINTING OFFICE: 1988 - 505-033/93443

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:27Z
Check the source to verify that this is the current version before use.